

Page 1 of 7 SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

SDS Revision Date: 6/10/2015

1.1	1. PRODUCT & COMPANY IDENTIFICATION 1. Product Name: DECYLT® D. SERIES, 59/, SRRAY (D/N DES 6)		
1.1	Floudel Name.	DEOXIT® D-SERIES, 5% SPRAY, (P/N D5S-6),	
		(RADIOSHACK® P/N 640-0249), 142 grams, VOC Compliant	
1.2	Chemical Name:	NA	
1.3	Synonyms:	DeoxIT® D Series, 5% Spray; P/N D5S-6	
1.4	Trade Names:	DeoxIT® D Series, 5% Spray; P/N D5S-6	
1.5	Product Uses & Restrictions:	Clean, deoxidize & improve electrical contacts & connectors	
1.6	Distributor's Name:	CAIG Laboratories, Inc.	
1.7	Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA	
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)	
1.9	Business Phone / Fax:	+1 (800) 224-4123	

according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

Classification: Aerosols 1

Hazard Statements (H): H229 – Pressurized container; may burst if heated. H304 – May be fatal if swallowed and enters airways.

Precautionary Statements (P): P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 – Do not pierce or burn, even after useP301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P332+P313 – If skin irritation occurs: get medical advice/attention. P405 – Store locked up. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 – Dispose of



3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-CHEMICAL NAME(S) CAS No. RTECS No. **EINECS No** TLV STEL TWA STEL PEAK PEL STEL IDLH OTHER 40-70 64742-88-7 XS5250000 265-191-7 100 NA 100 NF NF NA NA NA PETROLEUM NAPTHA Asp. Tox. 1; H304 75-37-6 K14100000 200-866-1 10-30 1000 NA 1000 NF NF NA NA NA SKIN DIELLIOPETHANE (P-152A)

contents/container to a licensed treatment, storage or disposal facility (TSDF).

DIFLUORETHANE (R-152A)		Flom Gos 1	; Lig. Gas;H220, H280			
			RY – TRADE SECRET 3-7 NA NA NF NF NF NA NA NA			
DEOXIT® D-SERIES, D100L		PROPRIETA	INT - INAL DECKET 5-7 INA INA INF INF INF INA INA INA			
			4 FIRST AID MEACHDES			
	<u></u>		4. FIRST AID MEASURES			
4.1	First Aid:	Ingestion:	Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.			
Eyes: Splashes are not likely; however, if pro water for at least 15 minutes lifting uppe Get medical attention. Skin: Wash thoroughly with soap and water. It least 15 minutes. Treat for frostbite if ne		Eyes:				
		<u>Skin</u> :	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.			
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.			
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea.			
		Eyes:	Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.			
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.			
		Inhalation:	None expected.			
4.3	Symptoms of Overexposure:	Ingestion:	Nausea, intestinal discomfort, vomiting and/or diarrhea.			
		Eyes:	Overexposure in eyes may cause redness, itching and watering.			
		Skin:	Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.			
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin.				



Page 2 of 7 SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0



Page 3 of 7

SDS-E-640-0249-D5S-A

SDS Revision: 4.0 repared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 6/10/2015 4. FIRST AID MEASURES - cont'd 4.5 Chronic Health Effects: Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis. 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 2 0 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride). Extinguishing Methods: 52 Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct 7.2 Storage & Handling: sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. Special Precautions: Clean all spills promptly. 7.3 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OSHA OTHER ppm (mg/m³) CHEMICAL NAME(S) TLV STEL ES-TWA ES-STEL ES-PEAK STEL IDLH PEL PETROLEUM NAPTHA 100 NΑ 100 NF NF NΑ NΑ NΑ DIFLUORETHANE (R-152A) 1000 NA SKIN 1000 NF NA NA NA DEOXIT® D-SERIES, D100L NA NF NF NF NA NA 15 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station). 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. Eve Protection: Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.



Page 4 of 7 SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

8.5	Hand Protection:	8. EXPOSURE CONTROLS & PERSONAL PROTECTION None required under normal conditions of use. However, may cause skin irritation in some
8.5	Hand Protection:	
ļ		sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.
		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Appearance:	
9.2	Odor:	Light red aerosol spray/mist
9.3	Odor Threshold:	Ethereal hydrocarbon odor NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA NA
9.6	Initial Boiling Point/Boiling	171.1-204 °C @ 760 mm Hg
0.7	Range: Flashpoint:	-
9.7	Upper/Lower Flammability	48.8 – 54.4°C (120 - 130 °F)
9.0	Limits:	NA
9.9	Vapor Pressure:	NA NA
9.10	Vapor Density:	4.9 (air = 1.0)
9.11	Relative Density:	0.75
9.12	Solubility:	Not soluble in water
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature: Decomposition Temperature:	NA Las
9.15 9.16	Viscosity:	NA Laboration and the second s
9.10	Other Information:	10.0 cPs
9.17	Other information.	VOC 588 g/L
		10. STABILITY & REACTIVITY
10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.
		44 TOVICOLOGICAL INFORMATION
		11. TOXICOLOGICAL INFORMATION
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product.
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).
11.5	Suspected Carcinogen:	No.
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
11.7	Reproductive Toxicity: Irritancy of Product:	This product is not reported to cause reproductive effects in humans.
11.7	Biological Exposure Indices:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. NE
11.9	Physician Recommendations:	Treat symptomatically.
	,	i near of infrastructionity.
		12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:	There is no specific data available for this product.
		There are an experimental and the social black of the product
12.2 12.3	Effects on Plants & Animals: Effects on Aquatic Life:	There are no specific data available for this product. There are no specific data available for this product; however, very large releases of this product may be harmful or fatal



Page 5 of 7 SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

	40 DIODOCAL CONCIDED ATIONS				
	T	13. DISPOSAL CONSIDERATIONS			
13.1	Waste Disposal:	Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations.			
13.2	Special Considerations:	California Waste Code: 331			
		14. TRANSPORTATION INFORMATION			
		nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.			
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or			
	, ,	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020			
14.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or			
		ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)			
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)			
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L);			
		or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"			
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)			
14.6	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)			
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)			
		15. REGULATORY INFORMATION			
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.			
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.			
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.			
15.4	CERCLA Reportable Quantity (RQ):	NA			
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).			
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol)			
15.7	State Regulatory Information:	Difluoroethane can be found on the following state criteria lists: MA and NJ. No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).			
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Petroleum Naphtha: Flammable, Harmful (F, Xn). Risk Phrases (R): 10-65 – Flammable. Harmful: may cause lung damage if swallowed. Safety Phrases (S): 2-23-24-62 – Keep away from children. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS or the container label. WARNING! Flammable aerosol. Colorless, volatile liquid with ethereal and faint sweetish odor. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. MAL-KODE (DK): 1-3			



Page 6 of 7

SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

	16. OTHER INFORMATION				
16.1	Other Information:	ENTERS AIRWAYS. Use only as directed. Ke lung damage if swallowed. Avoid contact with	LY BURST IF HEATED. MAY BE FATAL IF SWALLOWED AND ep out of reach of children. Do not breathe fumes/spray. May cause skin. In case of accident or if you feel unwell seek medical advice skin irritation occurs: get medical advice/attention. KEEP LOCKED UP		
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.			
16.3	Disclaimer:	government regulations must be reviewed for Laboratories, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein rela	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other applicability to this product. To the best of ShipMate's & CAIG contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are ates only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to		
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/	CAIG LABORATORIES, INC.		
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate* Dangerous Goods Training & Consulting		



Page 7 of 7

SDS-E-640-0249-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

SDS Revision Date: 6/10/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:


CAS No.	S No. Chemical Abstract Service Number	
EXPOSURE LIMITS IN AIR:		
ACGIH	American Conference on Governmental Industrial Hygienists	
С	Ceiling Limit	
ES	ES Exposure Standard (Australia)	
IDLH	IDLH Immediately Dangerous to Life and Health	
OSHA	OSHA U.S. Occupational Safety and Health Administration	
PEL	PEL Permissible Exposure Limit	
STEL Short-Term Exposure Limit		
TLV	Threshold Limit Value	
TWA	Time Weighted Average	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the hody


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	1 Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Е			
F		THE SECOND	





Splash Goggle



















Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit	
mg/m3	milligrams per cubic meter	
NA	Not Available	
ND	Not Determined	
NE	Not Established	
NF	Not Found	
NR	No Results	
ppm	parts per million	
SCBA Self-Contained Breathing Apparatus		

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:		
Autoignition	Minimum temperature required to initiate combustion in air with no other	
Temperature	source of ignition	
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will	
	explode or ignite in the presence of an ignition source	
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will	
	explode or ignite in the presence of an ignition source	

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NOHSC	National Occupational Health and Safety Commission (Australia)				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((2)		\odot	(4)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

F.		*	¥		S	X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment