

Page 1 of 6 SDS-E-D100S-2

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.0 SDS Revision Date: 2/19/2015 1. PRODUCT & COMPANY IDENTIFICATION 1.1 Product Name: DEOXIT[®] D-SERIES, 100% SPRAY, (P/N D100S-2), 57 g 1.2 Chemical Name NA 1.3 Synonyms NA 1.4 Trade Names: DeoxIT® D-Series, 100% Spray, (P/N D100S-2), 57g 1.5 Product Uses & Restrictions: Clean, Deoxidize & Improve Electrical Contacts & Connectors 1.6 Distributor's Name: CAIG Laboratories, Inc. 12200 Thatcher Court, Poway, CA 92064-6876 USA Distributor's Address: 1.7 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX) Business Phone / Fax: 1.9 +1 (800) 224-4123 2. HAZARDS IDENTIFICATION 2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). Classification: Aerosols 2; Asp. Haz. 2 Hazard Statements (H): H223 - Flammable aerosol. H229 - Pressurized container; may burst if heated. H305 – May be harmful if swallowed and enters airways. Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on open flames or other ignition source. P251 – Do not pierce or burn, even after use. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician. P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: get medical advice/attention. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF). 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-CHEMICAL NAME(S) TLV STEL PEL STEL IDLH CAS No. RTECS No. EINECS No. OTHER % TWA STEL PEAK 75-37-6 K14100000 200-866-1 60-100 1000 NA 1000 NF NF NA NA NA 1,1-DIFLUOROETHANE (R-152A) Flam. Gas 1; Liq. Gas; H220, H280 PROPRIETARY – TRADE SECRET 3-7 NA NA NF NF NF NA NA NA DEOXIT® D-SERIES, D100L Asp. Haz. 2; H305 4. FIRST AID MEASURES 4.1 First Aid: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm Eyes: water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persist repeat flushing. Get medical attention. Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give Inhalation: artificial respiration. Keep person warm, quiet and get medical attention. 4.2 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in <u>Skin:</u> some sensitive individuals. Inhalation: None expected. 4.3 Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Eyes: Overexposure in eyes may cause redness, itching and watering. <u>Skin</u>: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause

drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin.



Γ

SAFETY DATA SHEET

Page 2 of 6 **SDS-E-D100S-2**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0 SDS

SDS Revision Date: 2/19/2015

	4. FIRST AID MEASURES – cont'd								
4.5	Chronic Health Effects:	Overexposure may trigger asthma-like symptoms in som respiratory hypersensitivity. Possible allergic dermatitis.	ne sensitive	e individ	uals. N	lay also	induce	e skin ser	nsitization and
4.6	Target Organs:	Eyes, Skin, Respiratory System.							
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disc	orders of th	he HE	ALTH				1
	riggratated by Exposition	target organs (eyes, skin, and respiratory system).		FL/		BILITY			2
				PH	YSICA	L HAZ	ARDS		2
				PR	OTECI	FIVE E	QUIPM	IENT	В
				EYE	ES	SKIN			
		5. FIREFIGHTING MEA	SURE	S					
5.1	Fire & Explosion Hazards:	Level 2 Aerosol (NFPA 30B). Aerosols may burst at tem	nperatures	above 1	20 °F.	Cool un	involve	d	
		containers to prevent possible bursting. Aerosols may aerosols are bursting, stay clear until bursting is comple decompose at high temperatures to form toxic gases (e.g	, be projec ete. If invo	ctile haz olved in	ards wh a fire, tl	nen bur: his proc	sting.	lf	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to co							
5.3	Firefighting Procedures:	breathing apparatus (pressure-demand) and full protecti after the fire is out. Use water spray to cool fire-expose fire upwind. Avoid spraying water directly into storage of Prevent runoff from fire control or dilution from entering any natural waterway. Firefighters must use full bunke	Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or						
		6. ACCIDENTAL RELEASE	MEAS	URES	5				
6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. <u>Small Spills</u> : Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product any liquid and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a metal or plastic container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a metal or plastic container.							
		7. HANDLING & STORAGE IN	NFORM	ΙΑΤΙΟ)N				
7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this produc container(s). When used as intended, no additional pro contact is possible. Wash unintentional residues with soa	otective eq	quipment	is nece				
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e sunlight. Avoid temperatures above 120 °F. Keep away damage. To avoid unintentional spraying keep cap in pla	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use.						
7.3	Special Precautions:	Clean all spills promptly.							
		8. EXPOSURE CONTROLS & PERS	ONAL	PRO	ГЕСТ	ION			
8.1	Exposure Limits:		NOHSC			OSHA		OTHER	
	ppm (mg/m ³)			S-PEAK	PEL	STEL	IDLH		
9.2	Ventilation 9 East	DIFLUOROETHANE (R-152A) 1000 NA 1000	NF	NF	NA	NA	NA	<u> </u>	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).							
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.							
8.4	Eye Protection:	Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.							



Page 3 of 6 **SDS-E-D100S-2**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0 SDS R

SDS Revision Date: 2/19/2015

8. EXPOSURE CONTROLS & PERSONAL PROTECTION				
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.		
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., \geq 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.		

9. PHYSICAL & CHEMICAL PROPERTIES

		9. PHYSICAL & CHEMICAL PROPERTIES	
9.1	Appearance:	Aerosol. Light red liquid.	
9.2	Odor:	Ethereal/hydrocarbon odor	
9.3	Odor Threshold:	NA	
9.4	pH:	NA	
9.5	Melting Point/Freezing Point:	NA	
9.6	Initial Boiling Point/Boiling Range:	-25 °C @ 760 mmHg	
9.7	Flashpoint:	240 °C (464 °F)	
9.8	Upper/Lower Flammability Limits:	LEL: 3.9 % v/v; UEL: 16.9 % v/v	
9.9	Vapor Pressure:	87 psig @ 20 °C	
9.10	Vapor Density:	< 1.0 (air = 1.0)	
9.11	Relative Density:	0.75-0.85	
9.12	Solubility:	Not soluble in water	
9.13	Partition Coefficient (log Pow):	NA	
9.14	Autoignition Temperature:	440 °C (824 °F) at 1,009.0 - 1,017.0 hPa (756.8 - 762.8 mmHg)	
9.15	Decomposition Temperature:	NA	
9.16	Viscosity:	10.0 cPs	
9.17	Other Information:	Evaporation Rate: 0.11 (n-BuAc = 1.0); VOC: 588 g/L (75%)	
		10. STABILITY & REACTIVITY	
10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.	
10.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.	
10.3	Hazardous Polymerization:	Will not occur.	
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.	
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Store away from oxidizers.	
		11. TOXICOLOGICAL INFORMATION	
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES	
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product.	
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.	
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).	
11.5	Suspected Carcinogen:	No.	
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.	
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.	
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.	
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.	
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.	
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.	
11.8	Biological Exposure Indices:	NE	
11.9	Physician Recommendations:	Treat symptomatically.	
		12. ECOLOGICAL INFORMATION	
12.1	Environmental Stability:	There is no specific data available for this product.	
12.2	Effects on Plants & Animals:	There are no specific data available for this product.	
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.	



Page 4 of 6 **SDS-E-D100S-2**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/19/2015

		13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:	Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations:	U.S. EPA RCRA Hazardous Waste Code: D001 (Characteristic – Ignitability)
Tho	basic description (ID Num	14. TRANSPORTATION INFORMATION nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional
		e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) – until 12/31/2020
14.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL \leq 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL \leq 0.5 L)
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)
14.6	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)
		15. REGULATORY INFORMATION
15.1	SARA Reporting	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.
15.2	Requirements: SARA Threshold Planning	There are no specific Threshold Planning Quantities for the components of this product.
15.3	Quantity: TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity	NA
15.5	(RQ): Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol)
15.7	State Regulatory Information:	Difluoroethane can be found on the following state criteria lists: Massachusetts Hazardous Substances List (MA) and New Jersey Right-to-Know List (NJ). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: <u>1.1-Difluoroethane</u> : Extremely Flammable, Harmful (F+, Xi). <u>Risk Phrases</u> (R): R12-37-65-67 – Extremely flammable. Irritating to respiratory system. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness or dizziness. <u>Safety Phrases</u> (S): S2-7-9-16-24/25-26- 33-45-53 – Keep out of the reach of children. Keep container tightly closed. Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Take precautionary measures against static discharges. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). Avoid exposure - obtain special instructions before use. WARNING ! Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces.



Page 5 of 6 **SDS-E-D100S-2**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/19/2015

		16. OTHER INFORMATION		
16.1	Other Information:	WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER; MAY BURST IF HEATED. MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on open flames or other ignition source. Do not pierce or burn, even after use. IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician. Do NOT induce vomiting. If skin irritation occurs: get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.		
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.		
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/		
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com		



Page 6 of 6 SDS-E-D100S-2

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/19/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists	
C	Ceiling Limit	
ES	Exposure Standard (Australia)	
IDLH	IDLH Immediately Dangerous to Life and Health	
OSHA	OSHA U.S. Occupational Safety and Health Administration	
PEL	PEL Permissible Exposure Limit	
STEL	STEL Short-Term Exposure Limit	
TLV	Threshold Limit Value	
TWA	Time Weighted Average	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:


Α	0		G		8	1
В			н			
С			I		8	
D	B		J		() ()	
Е			κ			
F	8	🔇 🚯 🕲	X		ur supervisor on ndling direction	
Sa	afety Glasse	es Splash Goggles		e Shield & tive Eyewea	r Glov	ves
	Boots	Synthetic Apron	Protect &	tive Clothing Full Suit	g Dust Res	spirator
Full I	Face Respire	rator Dust & Vapor Half- Mask Respirator		ull Face espirator	Airline Ho or SC	
отн	OTHER STANDARD ABBREVIATIONS:					
	ML Maximum Limit					
	mg/m3	milligrams per cubic meter				
	NA	Not Available				
	ND	Not Determined				
	NE	Not Established				
	NF	Not Found				
	NR	No Results				
	ppm	parts per million				
	SCBA	Self-Contained Breathing App	paratus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:			
	Autoignition Minimum temperature required to initiate combustion in air with no other			
Temperature	source of ignition			
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that wil				
	explode or ignite in the presence of an ignition source			
UEL				
	explode or ignite in the presence of an ignition source			

HAZARD RATINGS: 0 Minimal Hazard 1 Slight Hazard 2 Moderate Hazard 0 Operate Hazard

2 Moderate Hazard	
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

REGULATORT IN ORMATION.							
WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	U.S. Department of Transportation						
TC	Transport Canada						
EPA	U.S. Environmental Protection Agency						
DSL	Canadian Domestic Substance List						
NOHSC	National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List						
PSL	Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act						
EU	European Union (European Union Directive 67/548/EEC)						
WGK	Wassergefährdungsklassen (German Water Hazard Class)						
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System						

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	Workit EAGE HAZARDOGG MATERIALG IDERTIFICATION (WITHIN) OF OTEM.							
\bigcirc	۲	۲		Ð	۲			
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive	

EC (67/548/EEC) INFORMATION:

		2×	¥	8	® X	×	×
С	E	F	Z	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\:		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment