













		<h1>MATERIAL SAFETY DATA SHEET</h1>				Page 1 of 7 MSDS-E-D5MS-15A	
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards				MSDS Revision: 2.0		MSDS Revision Date: 01/25/2008	
1. PRODUCT IDENTIFICATION						CHEMICAL RESPONSE CARD: 02	
1.1	Product Name:	DeoxIT®, D5MS-15, 5% Spray, 14 g				RESPONSE TEAM PPE:	 
1.2	Chemical Name:	See ingredients listed in section 3				WHMIS:	  
1.3	Synonyms:	DeoxIT®, D5MS-15, 5% Spray					
1.4	Trade Names:	DeoxIT®, D5MS-15, 5% Spray					
1.5	Product Use:	Clean, deoxidize & improve electrical contacts & connectors				HEALTH: 1	
1.6	Manufacturer's Name:	CAIG Laboratories, Inc.				FLAMMABILITY: 2	
1.7	Manufacturer's Address:	12200 Thatcher Court, Poway, CA 92064-6876				REACTIVITY: 0	
1.8	Business Phone:	+1 (800)-224-4123				PERSONAL PROTECTION: B	
1.9	Emergency Phone:	CHEMTREC 1-800-424-9300/1-703-527-3887					
1.10	Other Product Names:	DeoxIT®, D5S-6, 5% Spray, 142 g					
2. HAZARD IDENTIFICATION							
2.1	Hazard Identification: Colorless, volatile liquid with ethereal and faint sweetish odor. Flammable aerosol. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. This product is Classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (1999)] and ADG Code (Australia).						
2.2	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure: EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract.						
2.4	Symptoms of Overexposure: EYES: Mild irritation, redness, and watering. SKIN: Contact dermatitis, characterized by localized red or puffy dry skin and itching. INGESTION: Nausea, vomiting, and diarrhea. INHALATION: Mouth, nose, and throat irritation, dizziness, nausea, light-headedness, drunkenness, and loss of coordination.						
2.5	Acute Health Effects: INGESTION: Gastrointestinal irritation and central nervous system depression. EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract.						
2.6	Chronic Health Effects: EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract.						
2.7	Target Organs: Eyes, skin and respiratory system.						
NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.							

	<h1 style="margin: 0;">MATERIAL SAFETY DATA SHEET</h1>	Page 2 of 7 MSDS-E-D5MS-15A																				
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 01/25/2008																						
3. COMPOSITION & INGREDIENT INFORMATION																						
					EXPOSURE LIMITS IN AIR (mg/m ³)																	
					ACGIH ppm		NOHSC ppm			OSHA ppm			OTHER									
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES-TWA	ES-STEL	ES-PEA K	TLV	STEL	IDLH										
PETROLEUM NAPHTHA	64742-88-7	XS5250000	265-191-7	≤ 75	100	NE	100	NE	NE	100	NE	NE										
DIFLUOROETHANE	75-37-6	KI4100000	200-866-1	≤ 20	1000	NA	1000	NA	NA	1000	NA	NA	SKIN									
DeoxIT® D100L	TRADE SECRET	NA	NA	≤ 5	NA	NA	NA	NA	NA	NA	NA	NA										
4. FIRST AID MEASURES																						
4.1	First Aid: EYES: Flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If irritation persists, seek immediate medical attention. SKIN: Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. INGESTION: Drink plenty of water. If irritation persists, contact a physician. INHALATION: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.																					
4.2	Medical Conditions Aggravated by Exposure: None reported by the manufacturer.						<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #FF0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #FFFF00; color: black;">REACTIVITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td colspan="2" style="background-color: #000000; color: white;">PROTECTIVE EQUIPMENT</td> </tr> <tr> <td style="text-align: center;">EYES</td> <td style="text-align: center;">SKIN</td> </tr> </table>						HEALTH	1	FLAMMABILITY	2	REACTIVITY	0	PROTECTIVE EQUIPMENT		EYES	SKIN
HEALTH	1																					
FLAMMABILITY	2																					
REACTIVITY	0																					
PROTECTIVE EQUIPMENT																						
EYES	SKIN																					
5. FIREFIGHTING MEASURES																						
5.1	Flashpoint & Method: 48.8 °C - 54.4 °C (120 °F - 130 °F). Level 2 aerosol.																					
5.2	Autoignition Temperature: NA																					
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	NA		Upper Explosive Limit (UEL):	NA																
5.4	Fire & Explosion Hazards: Carbon dioxide, carbon monoxide, hydrocarbons.																					
5.5	Extinguishing Methods: CO₂, Alcohol foam, Dry Chemical, Water Fog																					
5.6	Firefighting Procedures: Wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing. Use a water spray to cool containers involved in fire. Do not use direct water stream. Container storage areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Keep containers cool until well after the fire is out to prevent rupture. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.																					

		<h1 style="text-align: center;">MATERIAL SAFETY DATA SHEET</h1>		Page 3 of 7 MSDS-E-D5MS-15A	
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards			MSDS Revision: 2.0		MSDS Revision Date: 01/25/2008
6. ACCIDENTAL RELEASE MEASURES					
6.1	Spills: Secure spill area and deny entry to all unprotected individuals. Individuals involved in the cleanup should wear appropriate personal protective equipment. Area may become slippery. Absorb product onto porous material, such as sand, clay, diatomaceous earth or commercial absorbent material. Place into leak-proof, U.S. DOT-approved containers. If necessary, cover all drains and dike well ahead of the spill to prevent runoff into sewers, drains, and all waterways. Contact appropriate local or provincial authorities for assistance and/or reporting requirements.				
7. HANDLING & STORAGE INFORMATION					
7.1	Work & Hygiene Practices: Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.				
7.2	Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Normal shelf-life: 2-3 years.				
7.3	Special Precautions: Empty containers can contain flammable vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.				
8. EXPOSURE CONTROLS & PERSONAL PROTECTION					
8.1	Ventilation & Engineering Controls: Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).				
8.2	Respiratory Protection: None required, when used with adequate ventilation.				
8.3	Eye Protection: Wear safety glasses with side shields (ANSI Z87) under normal use conditions.				
8.4	Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear rubber or impervious plastic gloves.				
8.5	Body Protection: Use as necessary to prevent skin contact.				
9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	0.75			
9.2	Boiling Point:	171.1 °C – 204 °C @ 760 mmHg			
9.3	Melting Point:	NA			
9.4	Evaporation Rate:	0.11 (n-Butyl Acetate = 1.0)			
9.5	Vapor Pressure:	35 psig @ 20 °C, 50 psig @ 50 °C			
9.6	Molecular Weight:	NA			
9.7	Appearance & Color:	Light red, aerosol			
9.8	Odor Threshold:	Ethereal/hydrocarbon odor			
9.9	Solubility:	Not soluble in water			
9.10	pH	ND			
9.11	Viscosity:	10.0 cps			
9.12	VOC (grams/liters)	588 g/l			
9.13	Other Information:	Vapor Density = 4.9 (Air = 1.0)			

		<h1>MATERIAL SAFETY DATA SHEET</h1>		Page 4 of 7 MSDS-E-D5MS-15A	
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards			MSDS Revision: 2.0		MSDS Revision Date: 01/25/2008
<h2>10. STABILITY & REACTIVITY</h2>					
10.1	Stability: Stable under normal conditions of use (see section 7).				
10.2	Hazardous Decomposition Products: Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.				
10.3	Hazardous Polymerization: Will not occur.				
10.4	Conditions to Avoid: Use or storage near open flames, sparks, high heat (>100 °F) or other heat sources, and proximity to incompatible substances and heavily trafficked areas.				
10.5	Incompatible Substances: Strong oxidizers.				
<h2>11. TOXICOLOGICAL INFORMATION</h2>					
11.1	Toxicity Data: This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have not been presented in this document.				
11.2	Acute Toxicity: See section 2.5				
11.3	Chronic Toxicity: See section 2.6				
11.4	Suspected Carcinogen: NE				
11.5	Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans.				
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.			
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.			
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.			
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.			
11.6	Irritancy of Product: See Section 2.3				
11.7	Biological Exposure Indices: NE				
11.8	Physician Recommendations: Treat symptomatically.				
<h2>12. ECOLOGICAL INFORMATION</h2>					
12.1	Environmental Stability: This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds.				
12.2	Effects on Plants & Animals: There is no specific data available for this product.				
12.3	Effects on Aquatic Life: Releases of large volumes of this product are expected to be harmful or fatal to overexposed aquatic life.				
12.4	Environmental Impact (Percent by Weight): VOC content: 75.0 %				
<h2>13. DISPOSAL CONSIDERATIONS</h2>					
13.1	Waste Disposal: Dispose of in accordance with federal, state or local regulations.				
13.2	Special Considerations: EPA Waste Code: D001 (characteristic – ignitability)				

		<h1>MATERIAL SAFETY DATA SHEET</h1>		Page 5 of 7 MSDS-E-D5MS-15A	
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards		MSDS Revision: 2.0		MSDS Revision Date: 01/25/2008	
14. TRANSPORTATION INFORMATION					
The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGR and the CTDGR.					
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L)				
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 500 ml) UN1950, AEROSOLS, 2.1 (> 500 ml)				
14.3	IMDG (OCN): UN1950, AEROSOLS, 2, LTD QTY (≤ 1.0 L)				
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)				
14.5	ADR/RID (EU): UN1950, AEROSOLS, 2.1, ADR, LTD QTY (≤ 1.0 L)				
14.6	SCT (MEX): UN1950, AEROSOLS, 2.1, CANTIDAD LIMITADA (≤ 1.0 L)				
14.6	ADGR (AUS): UN1950, AEROSOLS, 2.1, LTD QTY (≤ 1.0 L)				
15. REGULATORY INFORMATION					
15.1	U.S. EPA SARA Reporting Requirements: NA				
15.2	U.S. EPA SARA Threshold Planning Quantity: NA				
15.3	U.S. EPA TSCA Inventory Status: All chemical substances of this product are listed on the TSCA inventory or are otherwise exempt from inventory status.				
15.4	U.S. EPA CERCLA Reportable Quantity (RQ): NA				
15.5	Other U.S. Federal Requirements: NA				
15.6	Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List.				
15.7	U.S. State Regulatory Information: The primary component of this product is not listed on the following state lists: California OSHA; California Proposition 65; Massachusetts Right to Know List of Chemicals; New Jersey Right to Know List 8:59 Appendix A; Pennsylvania Hazardous Substances List 34 323 Appendix A; Wisconsin Hazardous Substances List NR 605.09; Minnesota Hazardous Substances List; and Florida Toxic Substances List.				
15.8	67/548/EEC (European Union) and Australia NOHSC:2011 (2003) Requirements: The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: Petroleum Naphtha: Flammable, Harmful (F, Xn). R: 10-65 – Flammable. Harmful: may cause lung damage if swallowed. S: 2-23-24-62 – Keep away from children. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS or the container label.				

		<h1 style="text-align: center;">MATERIAL SAFETY DATA SHEET</h1>		Page 6 of 7 MSDS-E-D5MS-15A	
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards			MSDS Revision: 2.0		MSDS Revision Date: 01/25/2008
16. OTHER INFORMATION					
16.1	Other Information: NA				
16.2	Terms & Definitions: See last page of this MSDS.				
16.3	Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.				
16.4	Prepared for: CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone +1 (858) 486-8398 fax http://www.caig.com/				
16.5	Prepared by: ShipMate, Inc. P.O. Box 787 780 Buckaroo Trail Suite D Sisters, OR 97759 +1 (310) 370-3600 phone +1 (310) 370-5700 fax http://www.shipmate.com				

	<h1 style="margin: 0;">MATERIAL SAFETY DATA SHEET</h1>	Page 7 of 7 MSDS-E- D5MS-15A
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards		MSDS Revision: 2.0
MSDS Revision Date: 01/25/2008		
DEFINITION OF TERMS		

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard




NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-W	Use No Water
OX	Oxidizer











TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₅₀ or TC, TC₀, LC₁₀, & LC₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution






















REGULATORY INFORMATION:














WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

							
C	E	F	N	O	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

PERSONAL PROTECTION RATINGS:

A		G			
B		H			
C		I			
D		J			
E		K			
F		X	Consult your supervisor or S.O.P. for special handling directions.		

 Safety Glasses	 Splash Goggles	 Face Shield & Eye Protection	 Gloves
 Boots	 Synthetic Apron	 Full Suit	 Dust Respirator
 Vapor Respirator	 Dust & Vapor Respirator	 Full Face Respirator	 Airline Hood/Mask or SCBA
 Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.			

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus