

Page 1 of 6 SDS-E-DCC-V510A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/2/2015

.1 Product Name:	DEOXIT® CONTACT CLEANER WASH, (P/N DCC-V510), 10 oz. (284 g)
.2 Chemical Name:	See ingredients listed in section 3
.3 Synonyms:	DeoxIT® Contact Cleaner Wash : PN DCC-V510
.4 Trade Names:	DeoxIT® Contact Cleaner Wash ; PN DCC-V510
.5 Product Uses & Restrictions:	Cleaner compound
.6 Distributor's Name:	CAIG Laboratories, Inc.
.7 Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA
.8 Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)
.9 Business Phone / Fax:	+1 (800) 224-4123

2. HAZARDS IDENTIFICATION

Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR

DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Aerosol 1; Flam. Liq. 2; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3

Hazard Statements (H): H229 - Pressurized container; may burst if heated. H225 - Highly flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H315 - Causes

Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing fume/gas/mist/vapor/spray. P264 - Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective gloves/ eye protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P304 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POINSON CENTER/doctor if you feel unwell. P332+P313 - If skin irritation occurs: get medical advice/attention. P405 - Store locked up. . P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

						EXPOSURE LIMITS IN AIR (mg/m³)							
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ICOLIEVANIE	107-83-5	NA	203-523-4	60-100	1800	NA	500	1760	NF	1800	3600	NA	
ISOHEXANE	Flam. Liq. 2; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aquatic Chronic 2; H225, H304, H315, H336, H411												
DIFLUORETHANE (R-152A)	75-37-6	K14100000	200-866-1	10-30	1000	NA	1000	NF	NF	NA	NA	NA	SKIN
DIFLOORE THANE (K-152A)	Flam. Gas 1; L	iq. Gas;H220, H2	180										
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	1-5	1000	3000	1000	1800	NF	1000	1900	3300	
ETHANOL (SD ALCOHOL 40B)	Flam. Liq. 2; H	225											
1													· · · · · · · · · · · · · · · · · · ·

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persist repeat flushing. Get medical attention.
		<u>Skin</u> :	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea.
		Eyes:	Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	None expected.



Page 2 of 6

SDS-E-DCC-V510A Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/2/2015 4. FIRST AID MEASURES - cont'd Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. Acute Health Effects: 4.4 Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin. 4.5 Chronic Health Effects: Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis. 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 4 1 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride). Extinguishing Methods: 52 Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill

or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. 7.3 Special Precautions: Clean all spills promptly.



Page 3 of 6 SDS-E-DCC-V510A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

		8. EXPOSURE CO	NIK	ULS	& PER	SONA	L PRO	IECI	ION		
8.1	Exposure Limits:		AC			NOHSC	,		OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOHEXANE	1800	NA	500	1760	NF	1800	3600	NA	2.00
		DIFLUORETHANE (R-152A)	1000	NA	1000	NF	NF	NA	NA	NA	SKIN
		ETHANOL (SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
8.2	Ventilation & Engineering Controls:	exhaust ventilation to effective	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).								
8.3	Respiratory Protection:	instances where dusts of this protection authorized by 29	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or								
8.4	Eye Protection:	Avoid eye contact. None required when handling or using large					use. Safety	glasse	s could	be used	
8.5	Hand Protection:	None required under norma sensitive individuals. When himpervious plastic gloves.									
8.6	Body Protection:	No apron required when han eye wash stations and deluginvolving large quantities of the	je show	ers sh	ould be av	ailable.	Upon comp	letion o	f work	activities	S
		9. PHYSIC	NI 9	CHE	MICAL	DDO	DEDTIE	<u> </u>			
0.1	Annogrange	1		CUE	IVIICAL	. FRU	FEKIIE	<u>.</u>			
9.1	Appearance:	Colorless to pale yellow liquid									
9.2	Odor:	Mild									
9.3	Odor Threshold:	NA									
9.4	pH:	NA									
9.5	Melting Point/Freezing Point:	NA									
9.6	Initial Boiling Point/Boiling Range:	195 °F									
9.7	Flashpoint:	15 °F (lowest component) TC	С								
9.8	Upper/Lower Flammability Limits:	LEL 1.2 % ; UEL 6.7%									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	NA									
9.11	Relative Density:	3.5									
9.12	Solubility:	Negligible									
9.13	Partition Coefficient (log Pow):	NA									
9.14	Autoignition Temperature:	NA									
9.15	Decomposition Temperature:	NA									
9.16	Viscosity:	0.83 cSt @ 100 °F									
9.17	Other Information:										
J. 11	Salor mormanon.	VOC >94%									
		10 6	TADI	LITV	O DE	\CTI\/	ITV				
10 1	Oral State				& REA						
10.1	Stability: Hazardous Decomposition	Stable under normal condition Change in color signifies expo						Will no	t degrad	de to un	stable products.
	Products:	Discard solution.					J =:				
10.3	Hazardous Polymerization:	Will not occur.									
10.4	Conditions to Avoid:	Open flames, sparks, high he		_				t.			
10.5	Incompatible Substances:	Avoid extreme heat and ignition	on sour	ces. Sto	ore away f	om oxidiz	zers.				
		44 TOVI			`		ATION				
11 1	Poutos of Entre	11. TOXI	COL	JUIL				ı		Ingoc	ion: VEC
11.1	Routes of Entry: Toxicity Data:	Inhalation: YES This product has NOT been t	ested o	n anima			YES gy data. To	oxicoloa	y data.	Ingesti found in	1.20
11.3	Acute Toxicity:	available for some of the com	ponents	s of the	product.						
	,	drowsiness, dizziness, heada	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.								
11.4	Chronic Toxicity:	This material may aggravate a	any pre-	existing	g skin cond	dition (e.g	., dermatitis).			
11.5	Suspected Carcinogen:	No.									



Page 4 of 6 SDS-E-DCC-V510A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/2/2015 11. TOXICOLOGICAL INFORMATION - cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. Mutagenicity: Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices ΝE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. 12.2 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations. Special Considerations: California Waste Code: D001 (characteristic ignitable) 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1950. AEROSOLS. 2.1 (LTD QTY. IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020 14.2 IATA (AIR): UN1950. AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) IMDG (OCN): 143 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory **CERCLA Reportable Quantity** 15.4 Ethanol: 2270 kg; 5000 lbs. (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics) 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol) 15.7 State Regulatory Information: Ethanol is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Pennsylvania Right-to-Know List (PA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ). <u>Difluoroethane</u> can be found on the following state criteria lists: MA and NJ. No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).



Page 5 of 6 SDS-E-DCC-V510A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

ТТОРС	2100 10 001 11 1, 1100, 11110	1, NOTICE, WHIME, 2001/00 & 121/2/2000/E0 Standards						
		15. REGULATORY INFORMATION – cont'd						
15.8	Other Requirements:							
13.0	Other Requirements.	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:						
		Isohexane: Flammable (F); Harmful (Xn); Environmental Hazard (N).						
		Risk Phrases (R): 11-38-65-67-51/53 – Highly flammable. Irritating to skin. Toxic to aquatic						
		organisms, may cause long-term adverse effects in the aquatic environment. Harmful; may cause						
		lung damage if swallowed. Vapors may cause drowsiness and dizziness.						
		Safety Phrases (S): (2-)9-16-29-33-61-62 – Keep container in a well-ventilated place. Keep away						
		from sources of ignition – No smoking. Don not empty into drains. Take precautionary measures against static discharges. Avoid release to the environment. Refer to special instructions/safety						
		data sheets. If swallowed, do not induce vomiting; seek medical advice immediately and show this						
		container or label.						
		Ethanol: Flammable (F).						
		Risk Phrases (R): 11 – Flammable. Safety Phrases (S): 2-7-16 – Keep out of reach of children.						
		Keep container tightly closed. Keep away from sources of ignition – No smoking.						
		Troop container lightly closed. Heap area, non-course or ignition. He contains						
		16. OTHER INFORMATION						
16.1	Other Information:	DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR						
		CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND						
		ENTERS AIRWAYS. Use only as directed. Keep container in a well-ventilated place. Keep away from sources of						
		ignition – No smoking. Don not empty into drains. Take precautionary measures against static discharges. Avoid releas						
		to the environment. Refer to special instructions/safety data sheets. If swallowed, do not induce vomiting; seek medical						
40.0	Tarres & Daffieldings	advice immediately and show this container or label. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.						
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other						
		government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIC Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however						
		accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, ar						
		provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with						
		other materials, all component properties must be considered. Data may be changed from time to time. Be sure to						
		consult the latest edition.						
16.4	Prepared for:	CAIG Laboratories, Inc.						
		12200 Thatcher Court						
		Poway, CA 92064-6876						
		Tel: +1 (800) CAIG-123 (244-4123)						
		Fax: +1 (858) 486-8398 fax						
		http://www.caig.com/						
16.5	Prepared by:	ShipMate, Inc.						
		P.O. Box 787						
		Sisters, Oregon 97759-0787 USA ShipMate						
		Tel: +1 (310) 370-3600						
		Fax. +1 (310) 370-3700						
		http://www.shipmate.com						



Page 6 of 6 SDS-E-DCC-V510A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:


CAS No.	Chemical Abstract Service Number				
EXPOSURE LIMITS IN AIR:					
ACGIH	ACGIH American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	HA U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV Threshold Limit Value					
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Е			
F		THE SECOND	

























Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit			
mg/m3	mg/m3 milligrams per cubic meter			
NA Not Available				
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA	SCBA Self-Contained Breathing Apparatus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature	source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals				
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{Io}	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{io} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS						
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA U.S. Environmental Protection Agency						
DSL Canadian Domestic Substance List						
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((2)		\odot	(4)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

V1.4			*		® X	X	×	
С	E	F	N	0	Т	Xi	Xn	
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful	

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment