

Page 1 of 6 SDS-E-DFW-V710A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/2/2015

1. PRODUCT & COMPANY IDENTIFICATION					
.1 Product Name:	DEOXIT® FLUX WASH, (P/N DFW-V710), 10 oz. (284 g)				
.2 Chemical Name:	See ingredients listed in section 3				
.3 Synonyms:	DeoxIT® Flux Wash; PN DFW-V710				
.4 Trade Names:	DeoxIT® Flux Wash; PN DFW-V710				
.5 Product Uses & Restrictions:	Cleaner compound				
.6 Distributor's Name:	CAIG Laboratories, Inc.				
.7 Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA				
.8 Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)				
.9 Business Phone / Fax:	+1 (800) 224-4123				

2. HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS Hazard Identification: according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR

DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Classification: Aerosol 1; Flam. Liq. 2; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3

Hazard Statements (H): H229 - Pressurized container; may burst if heated. H225 - Highly flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H315 - Causes

Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing fume/gas/mist/vapor/spray. P264 - Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective gloves/ eye protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P304 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POINSON CENTER/doctor if you feel unwell. P332+P313 - If skin irritation occurs: get medical advice/attention. P405 - Store locked up. . P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE L	MITS IN	AIR (mg	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ISOHEXANE	107-83-5	NA	203-523-4	60-100	1800	NA	500	1760	NF	1800	3600	NA	
ISOHEXANE	Flam. Liq. 2; A	Flam. Liq. 2; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aquatic Chronic 2; H225, H304, H315, H336, H411											
DIFLUORETHANE (R-152A)	75-37-6	K14100000	200-866-1	10-30	1000	NA	1000	NF	NF	NA	NA	NA	SKIN
DIFLOORE THANE (K-152A)	Flam. Gas 1; L	iq. Gas;H220, H2	180										
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	1-5	1000	3000	1000	1800	NF	1000	1900	3300	
ETHANOL (SD ALCOHOL 40B)	Flam. Liq. 2; H	225	•		•	•	•	•			•		

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persist repeat flushing. Get medical attention.
		<u>Skin</u> :	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea.
		Eyes:	Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	None expected.



7.2

7.3

Storage & Handling:

Special Precautions:

SAFETY DATA SHEET

Page 2 of 6 SDS-E-DFW-V710A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/2/2015 4. FIRST AID MEASURES - cont'd Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. Acute Health Effects: 4.4 Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Frostbite like effect to skin. 4.5 Chronic Health Effects: Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis. 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 4 1 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride). Extinguishing Methods: 52 Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.

damage. To avoid unintentional spraying keep cap in place when not in use.

Clean all spills promptly.

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical



Page 3 of 6 SDS-E-DFW-V710A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

		8. EXPOSURE CO	NTR	OLS	& PER	SONA	L PRO	TECT	ION		
8.1	Exposure Limits:		AC	GIH		NOHSC			OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOHEXANE	1800	NA	500	1760	NF	1800	3600	NA	
		DIFLUORETHANE (R-152A)	1000	NA	1000	NF	NF	NA	NA	NA	SKIN
		ETHANOL (SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
8.2	Ventilation & Engineering Controls:	exhaust ventilation to effective	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or gene exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of the product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).							n the handling of thi	
8.3	Respiratory Protection:	instances where dusts of this protection authorized by 29	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or								
8.4	Eye Protection:	Avoid eye contact. None req when handling or using large					ise. Safety	glasse	s could	be used	
8.5	Hand Protection:	None required under norma sensitive individuals. When himpervious plastic gloves.	l condi andling	tions o large q	of use. H uantities (e	owever, r e.g., ≥ 1 ga	nay cause allon (3.8 L)	skin irı), wear	ritation rubber,	in some nitrile o	
8.6	Body Protection:	No apron required when han eye wash stations and deluginvolving large quantities of the	ge show	ers sh	ould be av	/ailable.	Upon comp	letion o	of work	activities	
		9. PHYSIC	ΔI &	CHE	ΜΙζΔΙ	PROI	PERTIE	S			
9.1	Appearance:			JIIL		- 1 1101	LIVIIL				
9.1		Colorless to pale yellow liquid									
	Odor:	Mild									
1.3	Odor Threshold:	NA NA									
9.4	pH:	NA									
9.5	Melting Point/Freezing Point:	NA									
9.6	Initial Boiling Point/Boiling Range:	195 °F									
9.7	Flashpoint:	15 °F (lowest component) TC	С								
8.6	Upper/Lower Flammability Limits:	LEL 1.2 % ; UEL 6.7%									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	NA									
9.11	Relative Density:	3.5									
9.12	Solubility:	Negligible									
9.13	Partition Coefficient (log Pow):										
9.13	Autoignition Temperature:	NA									
9.15	Decomposition Temperature:	NA									
9.16	Viscosity:	NA									
	,	0.83 cSt @ 100 °F									
9.17	Other Information:	VOC >94%									
		10. S	<u>ı ABI</u>	<u>LITY</u>	' & RE/	<u> ACTIVI</u>	<u> </u>				
10.1	Stability:	Stable under normal condition	ns; unst	able wi	th heat or o	contamina	tion.				
10.2	Hazardous Decomposition Products:	Change in color signifies expo	osure to	ultravi	olet light o	r exceedin	g shelf life.	Will no	t degrad	de to un	stable products.
10.3	Hazardous Polymerization:	Will not occur.									
10.4	Conditions to Avoid:	Open flames, sparks, high he	at, inco	mpatibl	le substand	ces and di	rect sunligh	t.			
10.5	Incompatible Substances:	Avoid extreme heat and igniti									
		11. TOXI	COL	OGIC	CAL IN	FORM	ATION				
11.1	Routes of Entry:	Inhalation: YES		1			YES			Ingesti	on: YES
11.2	Toxicity Data:	This product has NOT been t			als to obtai			oxicolog	y data,		120
	Acute Toxicity:	available for some of the components of the product. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause descriptions beadaches and pauses.									
11.3		drowsiness, dizziness, heada	ches ar	nd naus	sea.						
11.3	Chronic Toxicity:	drowsiness, dizziness, heada This material may aggravate a				dition (e.a.	, dermatitis).			



SAFETY DATA SHEET Page 4 of 6 SDS-E-DFW-V710A Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/2/2015 11. TOXICOLOGICAL INFORMATION - cont'd 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. Mutagenicity: Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices ΝE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. 12.2 Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations. Special Considerations: California Waste Code: D001 (characteristic ignitable) 13.2 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1950. AEROSOLS. 2.1 (LTD QTY. IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020 14.2 IATA (AIR): UN1950. AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) IMDG (OCN): 143 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: TSCA Inventory Status: 15.3 The components of this product are listed on the TSCA Inventory **CERCLA Reportable Quantity** 15.4 Ethanol: 2270 kg; 5000 lbs. (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics) 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol) 15.7 State Regulatory Information: Ethanol is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Pennsylvania Right-to-Know List (PA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ).

<u>Difluoroethane</u> can be found on the following state criteria lists: MA and NJ.

No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).



Page 5 of 6 SDS-E-DFW-V710A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

Порс	iled to Ooria, Acc, Aivo	, NORSC, WHIMIS, 2001/38 & 12/2/2008/EC Standards SDS REVISION: 3.0 SDS REVISION Date: 2/2/2015
		45 DECULATORY INCORMATION contid
	T	15. REGULATORY INFORMATION – cont'd
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Isohexane:</u> Flammable (F); Harmful (Xn); Environmental Hazard (N). <u>Risk Phrases</u> (R): 11-38-65-67-51/53 — Highly flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful; may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. <u>Safety Phrases</u> (S): (2-)9-16-29-33-61-62 — Keep container in a well-ventilated place. Keep away from sources of ignition — No smoking. Don not empty into drains. Take precautionary measures against static discharges. Avoid release to the environment. Refer to special instructions/safety data sheets. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label. <u>Ethanol</u> : Flammable (F). <u>Risk Phrases</u> (R): 11 — Flammable. <u>Safety Phrases</u> (S): 2-7-16 — Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition — No smoking.
		Reep container lightly closed. Reep away from sources or ignition. The smoking.
		16. OTHER INFORMATION
16.1	Other Information:	DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AN ENTERS AIRWAYS. Use only as directed. Keep container in a well-ventilated place. Keep away from sources ignition – No smoking. Don not empty into drains. Take precautionary measures against static discharges. Avoid release to the environment. Refer to special instructions/safety data sheets. If swallowed, do not induce vomiting; seek medic advice immediately and show this container or label. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Oth government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAI Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, an provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure consult the latest edition.
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com ShipMate ShipMate ShipMate ShipMate ShipMate ShipMate ShipMate



Page 6 of 6 SDS-E-DFW-V710A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/2/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number				
EXPOSURE LIMITS IN AIR:					
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Е			
F		THE SECOND	





Splash Goggle













Full Face Respirator





Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition	Minimum temperature required to initiate combustion in air with no other					
Temperature	source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD50	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((2)		\odot	(4)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

1 ***	11		*		® X	X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment