

Page 1 of 7

MSDS-E-G5MS-15A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 01/25/2008 02 1. PRODUCT IDENTIFICATION CHEMICAL RESPONSE CARD: 1.1 Product Name: DeoxIT® GOLD, G5MS-15, 5% Spray, 14 g **RESPONSE** 1.2 Chemical Name: See ingredients listed in section 3 **TEAM PPE:** 1.3 Synonyms: DeoxIT® GOLD, G5MS-15, 5% Spray WHMIS: 1.4 Trade Names: DeoxIT® GOLD, G5MS-15, 5% Spray 1.5 Product Use: Conditioner, enhancer for contacts & connectors **HEALTH:** 1 1.6 Manufacturer's Name: CAIG Laboratories, Inc. 2 FLAMMABILITY: 1.7 Manufacturer's Address: 12200 Thatcher Court, Poway, CA 92064-6876 REACTIVITY: 0 1.8 Business Phone: +1 (800)-224-4123 PERSONAL PROTECTION: В 1.9 Emergency Phone: CHEMTREC 1-800-424-9300/1-703-527-3887 1.10 Other Product Names: DeoxIT® GOLD, G5S-6, 5% Spray, 142 g 2. HAZARD IDENTIFICATION 2.1 Hazard Identification: Colorless, volatile liquid with ethereal and faint sweetish odor. Flammable aerosol. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. This product is Classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (1999)] and ADG Code (Australia). 2.2 Routes of Entry: Inhalation: YES YES YES Absorption: Ingestion: 2.3 Effects of Exposure: EYES: Mild to moderate irritation. Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized SKIN: redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract. Symptoms of Overexposure: 2.4 EYES: Mild irritation, redness, and watering. SKIN: Contact dermatitis, characterized by localized red or puffy dry skin and itching. INGESTION: Nausea, vomiting, and diarrhea. Mouth, nose, and throat irritation, dizziness, nausea, light-headedness, drunkenness, and loss of coordination. INHALATION: Acute Health Effects: 2.5 INGESTION: Gastrointestinal irritation and central nervous system depression. EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract. 2.6 Chronic Health Effects EYES: Mild to moderate irritation. Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized SKIN: redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant. Irritating to the upper respiratory tract. Target Organs: 2.7 Eyes, skin and respiratory system.

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used

NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.



natural waterway.

MATERIAL SAFETY DATA SHEET

Page 2 of 7

MSDS-E-G5MS-15A

D:			0.0001/50.50	201	1.1000	D = 1		1	1,1000	D : : :		01 ′	0.5./00:	00
Prep	pared to OSHA, A	CC, ANSI, NOHSC, WHMIS	& 2001/58 EC	2 Standards	MSDS	Revision	1: 2.0		MSDS	Revisio	n Date	e:01/	25/200	08
		2 COM	DOCITION	L O INICOE	DIEN:	- INIE/	> DAA	ATIO	<u> </u>					
		3. CON	recomor	N & INGRE	DIEN	INF	JKM			4170 111	4 ID (/ 2		
						4.0	CIII	EXPOSU				•		
							GIH om		NOHSO ppm			OSHA ppm	<u> </u>	OTHE
								ES-	ES-	ES-		Ι		0
	CHEMICAL NAM	ME(S) CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	TLV	STEL	IDLH	
PETROLEUM NAPHTHA 647		64742-88-7	XS5250000	265-191-7	≤ 75	100	NE	100	NE	NE	100	NE	NE	
OIFLU	JOROETHANE	75-37-6	KI4100000	200-866-1	≤ 20	1000	NA	1000	NA	NA	1000	NA	NA	SKIN
		TRADE SECRET	NA	NA	≤ 5	NA	NA	NA	NA	NA	NA	NA	NA	
<i>-</i>	CIT COLD CITOL	IKADE SEGKEI	IVA			IIA	IIA	IVA	IIA	IVA	IIA	IVA	INA.	
			4. FI	RST AID M	EASU	RES								
4.1	First Aid:													
	EYES:	Flush eyes thoroughly							s, hol	ding e	yelid(s) ope	n to	ensure
		complete flushing. If it	ritation persis	ts, seek immed	diate m	edical d	attentic	on.						
	SKIN:	Remove contaminate										sists, s	seek p	oromp
		medical attention. Do			-		it has	been p	roperly	y clean	ed.			
INGESTION: Drink plenty of water. If irritation persists, contact a physician.														
	INHALATION:	Remove victim to fresh		_		•		supple	menta	loxyge	en and	l seel	k imm	ediate
		medical attention. If b	reathing stop	s, perform artif	icial res	piration	١							
4.2	Medical Conditions	Medical Conditions Aggravated by Exposure: HEALTH 1												
	None reported	by the manufacturer.												
								FLAM	MAI	BILITY	<u> </u>			2
								REAC	TIVI	ΤΥ				0
						r e		PROTECTIVE EQUIPMENT		NIT				
							<u>_</u>	PROI	<u>EÇII</u>	VE E	ROIL	ME	NI	
								EYES	SK	(IN				
			5. FIRE	FIGHTING	MEA	SURE	S							
5.1	Flashpoint & Method	:												
	48.8 °C - 54.4 °C	C (120 °F – 130 °F). Level 2	aerosol.											
5.2	Autoignition Tempera	•												
	NA													
5.3	Flammability Limits:		Lower Explo	sive Limit (LEL):		NA		Upper E	risolax	ve Limit	(UEL):		N	Α
5.4	Fire & Explosion Haza	rds:		(===).		,	1		1. 23.		/-			
	Carbon dioxide	, carbon monoxide, hydr	ocarbons.											
5.5	Extinguishing Method													
	CO ₂ , Alcohol foam, Dry Chemical, Water Fog													
5.6	Firefighting Procedur													
	Wear NIOSH/MS	SHA approved self-contai	ined breathin	g apparatus a	nd prot	ective o	clothin	g. Use	a wate	er		X	0	>
		containers involved in fire												
		ect flame contact should									X.		1	
		ontainer structure. Keep										V		
	Prevent runoff f	rom fire control or dilutio	on from enter	ing sewers, dr	ains, dr	inking	water	supply,	or an	У				



Page 3 of 7

MSDS-E-G5MS-15A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 01/25/2008

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Secure spill area and deny entry to all unprotected individuals. Individuals involved in the cleanup should wear appropriate personal protective equipment. Area may become slippery. Absorb product onto porous material, such as sand, clay, diatomaceous earth or commercial absorbent material. Place into leak-proof, U.S. DOT-approved containers. If necessary, cover all drains and dike well ahead of the spill to prevent runoff into sewers, drains, and all waterways. Contact appropriate local or provincial authorities for assistance and/or reporting requirements.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.

7.2 Storage & Handling:

Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Normal shelf-life: 2-3 years.

7.3 Special Precautions:

Empty containers can contain flammable vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls:

Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).

8.2 Respiratory Protection:

None required, when used with adequate ventilation.

8.3 Eye Protection

Wear safety glasses with side shields (ANSI Z87) under normal use conditions.

8.4 Hand Protection:

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear rubber or impervious plastic gloves.

8.5 Body Protection:

Use as necessary to prevent skin contact.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.75
9.2	Boiling Point:	171.1 °C – 204 °C @ 760 mmHg
9.3	Melting Point:	NA NA
9.4	Evaporation Rate:	0.11 (n-Butyl Acetate = 1.0)
9.5	Vapor Pressure:	35 psig @ 20 °C, 50 psig @ 50 °C
9.6	Molecular Weight:	NA NA
9.7	Appearance & Color:	Light yellow, aerosol
9.8	Odor Threshold:	Ethereal/hydrocarbon odor
9.9	Solubility:	Not soluble in water
9.10	рН	ND
9.11	Viscosity:	10.0 cps
9.12	VOC (grams/liters)	588 g/l
9.13	Other Information:	Vapor Density = 4.9 (Air = 1.0)



Page 4 of 7

MSDS-E-G5MS-15A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 01/25/2008 10. STABILITY & REACTIVITY 10.1 Stability: Stable under normal conditions of use (see section 7). Hazardous Decomposition Products: Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution. 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Use or storage near open flames, sparks, high heat (>100 °F) or other heat sources, and proximity to incompatible substances and heavily trafficked areas. 10.5 Incompatible Substances: Strong oxidizers. 11. TOXICOLOGICAL INFORMATION 11.1 Toxicity Data: This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity: See section 2.5 11.3 Chronic Toxicity: See section 2.6 Suspected Carcinoaen: 11.4 11.5 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. This product is not reported to produce embryotoxic effects in humans. Embryotoxicity: This product is not reported to produce teratogenic effects in humans. Teratogenicity: This product is not reported to produce reproductive effects in humans. Reproductive Toxicity: 11.6 Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indices: 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. 12.2 Effects on Plants & Animals: There is no specific data available for this product. 12.3 Effects on Aquatic Life: Releases of large volumes of this product are expected to be harmful or fatal to overexposed aquatic life. 12.4 Environmental Impact (Percent by Weight): VOC content: 75.0 % 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state or local regulations. Special Considerations: 13.2 EPA Waste Code: D001 (characteristic – ignitability)



Page 5 of 7

MSDS-E-G5MS-15A


Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 01/25/2008

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGR and the CTDGR.





15. REGULATORY INFORMATION

5.1 U.S. EPA SARA Reporting Requirements:

UN1950, AEROSOLS, 2.1, LTD QTY (≤ 1.0 L)

NA

15.2 U.S. EPA SARA Threshold Planning Quantity:

NA

15.3 U.S. EPA TSCA Inventory Status:

All chemical substances of this product are listed on the TSCA inventory or are otherwise exempt from inventory status.

15.4 U.S. EPA CERCLA Reportable Quantity (RQ):

NA

15.5 Other U.S. Federal Requirements:

N/

15.6 Other Canadian Regulations

This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.



15.7 U.S. State Regulatory Information:

The primary component of this product is not listed on the following state lists: California OSHA; California Proposition 65; Massachusetts Right to Know List of Chemicals; New Jersey Right to Know List 8:59 Appendix A; Pennsylvania Hazardous Substances List 34 323 Appendix A; Wisconsin Hazardous Substances List NR 605.09; Minnesota Hazardous Substances List; and Florida Toxic Substances List.

15.8 67/548/EEC (European Union) and Australia NOHSC:2011 (2003) Requirements::

The primary component of this product is listed in Annex I of EU Directive 67/548/EEC:

<u>Petroleum Naphtha</u>: Flammable, Harmful (F, Xn). R: 10-65 – Flammable. Harmful: may cause lung damage if swallowed. S: 2-23-24-62 – Keep away from children. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS or the container label.







Page 6 of 7

MSDS-E-G5MS-15A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 01/25/2008

16. OTHER INFORMATION

16.1 Other Information:

NA

16.2 Terms & Definitions:

See last page of this MSDS.

16.3 Disclaimer:

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone



http://www.caig.com/

16.5 Prepared by:

Prepared by: ShipMate, Inc.

P.O. Box 787 780 Buckaroo Trail Suite D

+1 (858) 486-8398 fax

Sisters, OR 97759 +1 (310) 370-3600 phone

+1 (310) 370-5700 fax

http://www.shipmate.com





Page 7 of 7

MSDS-E-G5MS-15A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 01/25/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists	
TLV Threshold Limit Value		
OSHA	U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit		
IDLH	Immediately Dangerous to Life and Health	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α	S			
В	S	and the second		
С	B	and the second	*	
D		and the second	*	
D E	⊕			





OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion
Temperature	in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of
	volume, that will explode or ignite in the presence of
	an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of
	by volume, that will explode or ignite in the presence of
	an ignition source

HAZARD RATINGS:

Minimal Hazard
Slight Hazard
Moderate Hazard
Severe Hazard
Extreme Hazard
Acidic
Alkaline
Corrosive
Use No Water
Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the			
	exposed animals s			
LC ₅₀	Lethal concentration (gases) which kills 50% of the			
	exposed animal			
ppm	Concentration expressed in parts of material per			
	million parts			
TD _{lo}	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or			
TC, TCo, LCio, & LCo	toxic effects			
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	CF Bioconcentration Factor			
TLm	Median threshold limit			
log Kow or log Koc	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	WHMIS Canadian Workplace Hazardous Material Information System		
DOT	U.S. Department of Transportation		
TC	Transport Canada		
EPA	A U.S. Environmental Protection Agency		
DSL	DSL Canadian Domestic Substance List		
NDSL	NDSL Canadian Non-Domestic Substance List		
PSL	PSL Canadian Priority Substances List		
TSCA	U.S. Toxic Substance Control Act		
EU	EU European Union (European Union Directive 67/548/EEC)		

EC INFORMATION:

		No.	*		Q	X	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful