

Page 1 of 6

	LABORATORIES, INC.		SAFE	ETY D	ATA	S	HE	:E					_	S-E-L260AF
Prepa	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS	, 2001/58 & 1272	/2008/EC Standar	ds		SDS	Revisio	n: 3.0		SDS	Revision	Date:	2/3/2015
				CT & COM										
1.1	Product Name:	DEOXIT® GREASE, TYPE L260AP (ALUMINUM PARTICLES)												
1.2	Chemical Name:	NA												
1.3	Synonyms:	DeoxIT® Grease Type L260AP, (Part No. L260AP)												
1.4	Trade Names:	DeoxIT® Grease Type L260AP; P/N L260-A2G (2 g); P/N L260-A1 (28 g); P/N L260-A50G (50 g); P/N L260-A8TP (226 g); P/N L260-A8 (226 g); P/N L260-A35 (15.9 Kg)												
1.5	Product Uses & Restrictions:	Lubricating (	Grease	`	<u> </u>									
1.6	Distributor's Name:	CAIG Labora	atories, Inc.											
1.7	Distributor's Address:	12200 Thato	cher Court, Pow	ay, CA 92064-6	876 USA									
1.8	Emergency Phone:	<b>CHEMTR</b>	EC: +1 (703	) 527-3887 /	+1 (800	) 424	-9300	CC)	XX N	(XXX	)			
1.9	Business Phone / Fax:	+1 (800) 224	4-4123	•	•									
		This product is classified as a HAZARDOUS SUBSTANCE but NOT as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).  The highly refined mineral oil contains < 3% (w/w%) DMSO extract, according to IP346.  DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  Hazard Statements (H): H304 – May be fatal if swallowed and enters airways.  Precautionary Statements (P): P280 – Wear protective gloves and eye protection. P302 + P352 – IF ON SKIN – Wash with plenty of soap and water. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 – Do NOT induce vomiting. P321 – Refer to section 4 of this Safety Data Sheet (First Aid). P305+P351+P338 – IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P405 – Store locked up. P501 – Dispose of contents/container through licensed treatment, storage or disposal facility.												
	1	· ·		TION & INC	GREDI	ENT	INF	ORN	/AT	ION				
											IMITS IN	I AIR (mg	/m³)	
						AC			NOHSC			OSHA		
						pp	om I	FS-	ppm ES-	ES-		ppm		
	ICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
	UM GREASE LUBRICATING	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	

	J. U		IOIT & IIT	JINEDI			Oivi	· · ·	1011				
								EXPO	SURE L	IMITS IN	I AIR (m	g/m³)	
					AC	ACGIH		NOHSC		OSHA			
					pį	om		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
LITHIUM GREASE LUBRICATING	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
BASE OIL CONTAINING ONE OR MORE OF THE FOLLOWING INGREDIENTS:													
DISTILLATES (PETROLEUM),	64742-65-0	SE7500000	265-169-7	NA	5	10	NF	NF	NF	100	10	NA	RESP MIST
SOLVENT-DEWAXED HEAVY PARAFFINIC	Carc. 1B; H35	50											
RESIDUAL OILS (PETROLIUM)	64742-01-4	NA	265-101-6	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
SOLVENT-REFINED													
DISTILLATES (PETROLEUM),	64741-88-4	PY8040500	265-090-8	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
SOLVENT-DEWAXED HEAVY PARAFFINIC													
ZINC ALKYLDITHIOPHOSPHATE	68649-42-3	NA	272-028-3	NA	NA	NA	NF	NF	NF	NA	NA	NA	
ZINC ALKTEDITHIOPHOSPHATE													
ALUMINUM OXIDE	1344-28-1	BD1200000	NA	≤ 10.0	0.2	NA	NF	NF	NF	0.1	NA	100	RESP DUST
ALOMINOM OXIDE													
DeoxIT® PROPRIETARY MIX	TRADE SECF	RET		NA	NA	NA	NF	NF	NF	NA	NA	NA	
DEUXIT PROPRIETART WIX													

#### 4. FIRST AID MEASURES First Aid: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an Ingestion: unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm Eyes: water for at least 15 minutes lifting upper and lower lids, occasionally. Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at Skin: Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give Inhalation: artificial respiration. Keep person warm, quiet and get medical attention.



7.3

Special Precautions:

bodies of water.

### **SAFETY DATA SHEET**

Page 2 of 6

Empty containers may

SDS-E-L260AP Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/3/2015 4. FIRST AID MEASURES 42 Effects of Exposure: If product is swallowed, may cause nausea, temporary gastrointestinal irritation. vomiting and/or diarrhea. Ingestion: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: None expected. 4.3 Nausea, intestinal discomfort, vomiting and/or diarrhea. Symptoms of Overexposure: Ingestion: Eyes: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high 4.4 Acute Health Effects: concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 None reported by the manufacturer. 46 Target Organs: Eyes, Skin Medical Conditions Aggravated by Exposure: 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 target organs (eyes). **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO,CO<sub>x</sub>). 52 Extinguishing Methods: Water, Foam, CO<sub>2</sub>, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g.,  $\geq 1$  gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink, or smoke while handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk covered. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Container is not designed to contain pressure. Don not use

pressure to empty container or it may rupture with explosive force. Normal shelf-life: 2-3 years.

Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

contain product residues. Avoid contaminating soil or releasing this material into sewage and drainage systems and



Page 3 of 6 SDS-E-L260AP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/3/2015

3.1		8. EXPOSURE CON	<u>IK</u> O	<u> </u>	PERS	<u>UNA</u> L	<u> </u>	<u>اا تا:</u>	<u>UN</u>							
0.1	Exposure Limits:		AC	GIH		NOHSC			OSHA		OTHER					
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH						
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	100	10	NA	RESP MIST					
		RESIDUAL OILS (PETROLIUM) SOLVENT-REFINED	5	10	NF	NF	NF	5	10	NA	RESP MIST					
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	5	10	NA	RESP MIST					
		ALUMINUM OXIDE	0.2	NA	NF	NF	NF	0.1	NA	100	RESP DUST					
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensu that an eyewash station, sink or washbasin is available in case of exposure to eyes.														
8.3	Respiratory Protection:	necessary, use only respirator §1910.134, or applicable U.S.	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.													
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.														
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber or impervious plastic gloves.														
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.														
		9. PHYSICAI	_ & C	HEM	IICAL I	PROPE	RTIES									
9.1	Appearance:	Amber														
9.2	Odor:	Ethereal / hydrocarbon odor														
9.3	Odor Threshold:	NA														
9.4	pH:	NA														
9.5	Melting Point/Freezing Point:	NA														
9.6	Initial Boiling Point/Boiling Range:	> 240 °C (464 °F)														
9.7	Flashpoint:	> 244 °C (471 °F) COC (Clevela	and Ope	n Cup)												
9.8	Upper/Lower Flammability Limits:	NA	·	.,												
	Vapor Pressure:	< 0.01 mm Hg @ 20 °C (68 °F)														
9.9	Vapor Density:	NA														
		0.72														
9.10	Relative Density:	0.72														
9.10 9.11	Relative Density:  Solubility:	Insoluble														
9.10 9.11 9.12																
9.10 9.11 9.12 9.13	Solubility:	Insoluble														
9.10 9.11 9.12 9.13 9.14	Solubility: Partition Coefficient (log Pow):	Insoluble NA														
9.10 9.11 9.12 9.13 9.14 9.15	Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	Insoluble NA NA NA														
9.10 9.11 9.12 9.13 9.14 9.15	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	Insoluble NA NA														
9.10 9.11 9.12 9.13 9.14 9.15 9.16	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	Insoluble NA NA NA 5.4 – 7.5 cSt @ 104 °F NA	ΔRII	ITV &	2 REAC	TIVIT	<b>V</b>									
9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:	Insoluble  NA  NA  NA  S.4 – 7.5 cSt @ 104 °F  NA  10. ST	ABIL	ITY 8	k REAC	TIVIT	Y									
9.9 9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:  Stability: Hazardous Decomposition	Insoluble  NA  NA  NA  S.4 – 7.5 cSt @ 104 °F  NA  10. ST						ngerou	s pressi	ure.						
9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:  Stability:	Insoluble NA NA NA 5.4 – 7.5 cSt @ 104 °F NA  10. ST This product is stable. Oxides of carbon (CO, CO <sub>2</sub> ) and						ngerou	s pressi	ure.						
9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17	Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information:  Stability: Hazardous Decomposition Products:	Insoluble  NA  NA  NA  S.4 – 7.5 cSt @ 104 °F  NA  10. ST	d sulfur	(SO <sub>2</sub> ). L				ngerou	s pressi	ure.						



Page 4 of 6 SDS-E-L260AP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/3/2015 11. TOXICOLOGICAL INFORMATION Inhalation: YES Ingestion: YES 11.1 Routes of Entry: Absorption: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis). Suspected Carcinogen: 11.5 Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. This product contains alkyl dithiophosphates Mutagenicity: (ZDDPs). Several ZDDPs have been reported to have weak mutagenic activity in cultured mammalian cells but only at concentrations that were toxic. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Biological Exposure Indices: 11.8 NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: There is no specific data available for this product. 12.1 Effects on Plants & Animals: 12.2 There are no specific data available for this product. 12.3 Effects on Aquatic Life Ethanol: EC<sub>50</sub> (Daphnia magna (water flea), 48h): 7.7 - 11.2 mg/L; LC<sub>50</sub> (Pimephales promelas (fathead minnow), 96h) > 100 mg/L; Alkyl Dimethyl Benzyl Ammonium Chloride: LC<sub>50</sub> (Morone saxatilis (Striped bass, 96h): 10.4 - 19.1 mg/L 13. DISPOSAL CONSIDERATIONS Waste Disposal: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate 13 1 disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. Special Considerations: NΑ 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED IATA (AIR): 14.2 NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): NOT REGULATED 14.5 ADR/RID (EU): NOT REGULATED 14.6 SCT (MEXICO): NOT REGULATED ADGR (AUS): 14.7 **NOT REGULATED** 15. REGULATORY INFORMATION 15.1 SARA Reporting This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Requirements: Planning and Community Right-to-know Act of 1986 and of CFR 372; 68649-42-3 Zinc Alkyldithiophosphate SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics) 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state 15.7 State Regulatory Information: criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).



Page 5 of 6 SDS-E-L260AP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.0 SDS Revision Date: 2/3/2015

		15. REGULATORY INFORMATION			
15.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC:  Harmful (XN)  Risk Phrases: (R) 20/21/22 36 – Harmful by inhalation, in contact with skin and if swallowed. Safety  Phrases: (S) 2-36-45 – Keep out of reach of children. Wear suitable protective clothing. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).			
		16. OTHER INFORMATION			
16.1	Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Use only as directed. Keep out of reach children. Wear suitable protective clothing. In case of accident or if you feel unwell seek medical advice immediate (show the label where possible). If skin irritation occurs: get medical advice/attention. KEEP LOCKED UP AND OF REACH OF CHILDREN.	tely		
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.			
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Ot government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CA Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; howev accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, a provided. The information contained herein relates only to the specific product(s). If this product(s) is combined wother materials, all component properties must be considered. Data may be changed from time to time. Be sure consult the latest edition.	AIG ver, are with		
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/			
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com			



Page 6 of 6 SDS-E-L260AP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/3/2015

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**


CAS No.	Chemical Abstract Service Number
<b>EXPOSURE</b>	LIMITS IN AIR:
ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body


#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D		THE STATE OF THE S	
Е			
F		THE SECOND	





Splash Goggle







Synthetic Apre











Airline Hood/Mask or SCBA

#### OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition	Minimum temperature required to initiate combustion in air with no other			
Temperature	source of ignition			
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will			
	explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will			
	explode or ignite in the presence of an ignition source			

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive
•	-



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>Io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>lo</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS						
DOT	T U.S. Department of Transportation					
TC	TC Transport Canada					
EPA U.S. Environmental Protection Agency						
DSL Canadian Domestic Substance List						
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL Canadian Non-Domestic Substance List						
PSL Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(2)</b>	<b>(2)</b>		$\odot$	<b>®</b>		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

(	(***********************************								
T.		N. C.	*		<b>%</b>	X	X		
С	E	F	N	0	Т	Xi	Xn		
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful		

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$	A Park		<b>\limits</b>		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment