

DeoxIT® PROPRIETARY MIX

TRADE SECRET

GRAPHITE

Page 1 of 6

FUME

	GAIG LABORATORIES, INC.		SAFE	ETY D	ATA	S	HE	ĒΈ	Γ				_	e 1 of 6 S-E-L260GP
Prepa	ared to OSHA, ACC, ANSI, NO	DHSC, WHMIS, 2	001/58 & 1272/2	2008/EC Standar	rds		SDS	Revisio	n: 3.0		SDS	Revision	n Date:	2/3/2015
		1.	PRODUC	T & COM	<u>IPANY</u>	IDE	NTIF	-ICA	TIO	<u> </u>				
.1	Product Name:	DEOXIT ®	GREAS	E, TYPE	L260G	P (G	RAF	PHIT	E P	ART	ICLE	ES)		
.2	Chemical Name:	NA		•		•								
.3	Synonyms:	DeoxIT® Grea	se Type L260	GP, (Part No.	L260GP)									
.4	Trade Names:	DeoxIT® Grea	xIT [®] Grease Type L260GP; P/N L260-G2G (2 g); P/N L260-G1 (28 g); P/N L260-G50G (50 g); P/N L260-G8TP (226 P/N L260-G8 (226 g); P/N L260-G35 (15.9 Kg)											
.5	Product Uses & Restrictions:	Lubricating Gr	ease											
.6	Distributor's Name:	CAIG Laborate												
.7	Distributor's Address:	12200 Thatch	er Court, Pow	ay, CA 92064-	6876 USA									
.8	Emergency Phone:	CHEMTRE	C: +1 (703)	527-3887	+1 (800) 424	-9300	O (CC	X N	(XXX	()			
.9	Business Phone / Fax:	+1 (800) 224-4	4123		•			•						
			2 ⊔	AZARDS	IDENT	IEIC	ΛΤΙĆ	N						
		Precautionary IF ON SKIN - call a POISON section 4 of continuously v continue rinsir treatment, sto	ned mineral o AY BE FATAL nents (H): H3 Statements (I - Wash with p N CENTER or this Safety E with water for ng. P405 – Si rage or dispos	il contains < 3° LIF SWALLOV 04 – May be fa P): P280 – We lenty of soap a doctor/physici Data Sheet (F several minute tore locked up	% (w/w%) WED AND atal if swall ar protecti and water. ian. P331 irst Aid). es. Remov.	DMSO ENTE lowed a live glov P301 Do P305 Ve confi	extrace RS AII and en yes an +P310 NOT ir i+P351 cact ler e of co	et, according to the control of the	ording S. rways. protec: WALL vomitii 3 – IF prese contai	tion. FOWEEng. PCF IN Ent and	46. P302 + D: Imm 321 - EYES I easy rough	nediatel Refer t - Rins to do	y o e - d	
						AC	GIH		NOHSC			OSHA	, ,	
						pp	m		ppm			ppm		
JEM	ICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
	UM GREASE LUBRICATING	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	OTHER
ORI	OIL CONTAINING ONE OR E OF THE FOLLOWING EDIENTS:		•		100000									
	LLATES (PETROLEUM),	64742-65-0	SE7500000	265-169-7	NA	5	10	NF	NF	NF	100	10	NA	RESP MIST
	ENT-DEWAXED HEAVY FFINIC	Carc. 1B; H35	0											
ESII	DUAL OILS (PETROLIUM)	64742-01-4	NA	265-101-6	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
OLV	ENT-REFINED	Carc. 1B; H35	0											
	LLATES (PETROLEUM),	64741-88-4	PY8040500	265-090-8	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
	ENT-DEWAXED HEAVY FFINIC	Carc. 1B; H35	0											
NC	ALKYLDITHIOPHOSPHATE	68649-42-3	NA	272-028-3	NA	NA	NA	NF	NF	NF	NA	NA	NA	
INC	ALKILDIITIOPHOSPHATE		•		•	•								

EIDST AID MEASIIDES

NA

7782-42-5 MD9659600 231-955-3 <50.30 0.2 NA NF NF NF 0.1 NA 100

NA NA NF NF NF NA NA NA

L			4. FIRST AID MEASURES
	4.1 First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.
		Skin:	Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.
		Inhalation:	Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
Γ	•		



Page 2 of 6 SDS-E-L260GP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/3/2015 4. FIRST AID MEASURES 42 Effects of Exposure: If product is swallowed, may cause nausea, temporary gastrointestinal irritation. vomiting and/or diarrhea. Ingestion: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: None expected. 4.3 Nausea, intestinal discomfort, vomiting and/or diarrhea. Symptoms of Overexposure: Ingestion: Eyes: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high 4.4 Acute Health Effects: concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 None reported by the manufacturer. 46 Target Organs: Eyes, Skin Medical Conditions Aggravated by Exposure: 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 target organs (eyes). **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO,CO_x). 52 Extinguishing Methods: Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink, or smoke while handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk covered. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Container is not designed to contain pressure. Don not use pressure to empty container or it may rupture with explosive force. Normal shelf-life: 2-3 years. 7.3 Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. Empty containers may contain product residues. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.



Page 3 of 6 SDS-E-L260GP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/3/2015

8.1	Exposure Limits:	8. EXPOSURE CON		GIH		NOHSC			OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	OTHER
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	100	10	NA	RESP MIST
		RESIDUAL OILS (PETROLIUM) SOLVENT-REFINED	5	10	NF	NF	NF	5	10	NA	RESP MIST
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	5	10	NA	RESP MIST
		GRAPHITE	0.2	NA	NF	NF	NF	0.1	NA	100	FUME
8.2	Ventilation & Engineering Controls:	When working with large quantithat an eyewash station, sink or							al exhau	ıst vent	ilation, fans). Ensui
8.3	Respiratory Protection:	No special respiratory protection necessary, use only respirator §1910.134, or applicable U.S. provinces, E.C. member states,	proted state	ction au regulation	thorized p	er U.S. C	SHA's req	uireme	ent in 2	9 CFR	
8.4	Eye Protection:	product. Always use protective	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.								
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber or impervious plastic gloves.									
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									
		O BUIVOLOAL	۰ ،								
		9. PHYSICAI	_ & L	HEM	IICAL F	PROPE	ERTIES				
9.1	Appearance:	9. PHYSICAl	_ & C	HEM	IICAL I	PROPE	RTIES				
	Appearance: Odor:	Amber / black	_ & C	HEIN	IICAL I	PROPE	RTIES				
9.2		1	<u> </u>	HEIN	IICAL I	PROPE	RTIES				
9.2	Odor:	Amber / black Ethereal / hydrocarbon odor	_ & C	HEIVI	IICAL I	PROPE	RTIES				
9.2 9.3 9.4	Odor: Odor Threshold:	Amber / black Ethereal / hydrocarbon odor NA	_ & C	HEIV	IICAL I	PROPE	RTIES				
9.2 9.3 9.4 9.5	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling	Amber / black Ethereal / hydrocarbon odor NA NA	_ & C	HEM	IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold: pH: Melting Point/Freezing Point:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F)			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits:	Amber / black Ethereal / hydrocarbon odor NA NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F)			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.9 9.10 9.11	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble			IICAL I	PROPE	ERTIES				
3.2 3.3 3.3 3.4 3.5 3.6 3.7 3.8 3.9 3.10 3.11 3.12 3.13	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow):	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA			IICAL I	PROPE	ERTIES				
3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 3.9 3.10 3.11 3.11 3.12 3.13 3.14	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA			IICAL I	PROPE	ERTIES				
3.2 3.3 3.4 3.4 3.5 3.6 3.8 3.9 3.9 3.10 3.11 3.1	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.7 9.9 9.10 9.11 9.12 9.13 9.15	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA S.4 - 7.5 cSt @ 104 °F			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.10 9.11 9.12 9.14 9.15 9.16	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.15	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA S.4 - 7.5 cSt @ 104 °F	and Ope	en Cup)							
9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.14 9.15 9.17	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA	and Ope	en Cup)							
9.2 9.3 9.3 9.4 9.5 9.6 9.7 9.7 9.10 9.11 9.12 9.13 9.14 9.15 9.17 10.1	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition Products:	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA This product is stable. Oxides of carbon (CO, CO ₂) and	and Ope	en Cup)	& REAC	CTIVIT	Y	ngerou	as press	ure.	
9.2 9.3 9.3 9.4 9.5 9.6 9.7 9.9 9.9 9.10 9.11 9.12 9.15 9.17	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition	Amber / black Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA S.4 - 7.5 cSt @ 104 °F NA 10. ST	ABIL	ITY 8	& REAC	CTIVIT	Y	ngerou	is press	ure.	



Page 4 of 6 SDS-E-L260GP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/3/2015 11. TOXICOLOGICAL INFORMATION Inhalation: YES Ingestion: YES 11.1 Routes of Entry: Absorption: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis). Suspected Carcinogen: 11.5 Reproductive Toxicity: 11.6 This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. This product contains alkyl dithiophosphates Mutagenicity: (ZDDPs). Several ZDDPs have been reported to have weak mutagenic activity in cultured mammalian cells but only at concentrations that were toxic. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Biological Exposure Indices: 11.8 NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: 12.1 There is no specific data available for this product. Effects on Plants & Animals: 12.2 There are no specific data available for this product. 12.3 Effects on Aquatic Life Ethanol: EC₅₀ (Daphnia magna (water flea), 48h): 7.7 - 11.2 mg/L; LC₅₀ (Pimephales promelas (fathead minnow), 96h) > 100 mg/L; Alkyl Dimethyl Benzyl Ammonium Chloride: LC₅₀ (Morone saxatilis (Striped bass, 96h): 10.4 - 19.1 mg/L 13. DISPOSAL CONSIDERATIONS Waste Disposal Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate 13.1 disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. Special Considerations: NA 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED IATA (AIR): 14.2 NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): **NOT REGULATED** ADR/RID (EU): 14.5 NOT REGULATED 14.6 SCT (MEXICO): NOT REGULATED ADGR (AUS): 14.7 **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Requirements: Planning and Community Right-to-know Act of 1986 and of CFR 372; 68649-42-3 Zinc Alkyldithiophosphate SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics) 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.



Page 5 of 6 SDS-E-L260GP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/3/2015

		01100; 11111110; 2001/00 & 1212/2000/20 Citandardo	
		15. REGULATORY INFO	RMATION – cont'd
15.7	State Regulatory Information:	Substance List (PA), Wisconsin Hazardous Su Jersey Right to Know List (NJ), new York Right Toxic Substances List (FL). No other ingredients in this product, present in a criteria lists: California Proposition 65 (CA65), List (FL), Massachusetts Hazardous Substant Hazardous Substances List (MN), New Jersey	st(s): Massachusetts Right to Know List (MA), Pennsylvania Hazardous bstance List (WI), Minnesota Hazardous Substance List (MN), New to Know List (NY), Michigan Critical Substances List (MI), and Florida concentration of 1.0% or greater, are listed on any of the following state Delaware Air Quality Management List (DE), Florida Toxic Substances ces List (MA), Michigan Critical Substances List (MI), Minnesota Right-to-Know List (NJ), New York Hazardous Substances List (NY), on Permissible Exposures List (WA), Wisconsin Hazardous Substances
15.8	Other Requirements:	The primary components of this product are not list Harmful (XN) Risk Phrases: (R) 20/21/22 36 – Harmful by inhal Phrases: (S) 2-36-45 – Keep out of reach of child accident or if you feel unwell seek medical advice	lation, in contact with skin and if swallowed. Safety dren. Wear suitable protective clothing. In case of
		16. OTHER INFO	DRMATION
16.1	Other Information:	children. Wear suitable protective clothing. In c	AND ENTERS AIRWAYS. Use only as directed. Keep out of reach of case of accident or if you feel unwell seek medical advice immediately n occurs: get medical advice/attention. KEEP LOCKED UP AND OUT
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	government regulations must be reviewed for Laboratories, Inc.'s knowledge, the information accuracy, suitability or completeness is not guara provided. The information contained herein rela	SHA's Hazard Communication Standard, 29 CFR §1910.1200. Other applicability to this product. To the best of ShipMate's & CAIG contained herein is reliable and accurate as of this date; however, anteed and no warranties of any type, either expressed or implied, are ites only to the specific product(s). If this product(s) is combined with be considered. Data may be changed from time to time. Be sure to
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/	CAIG LABORATORIES, INC.
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate Dangerous Goods Training & Consulting



Page 6 of 6 SDS-E-L260GP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.0

SDS Revision Date: 2/3/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:


CAS No.	Chemical Abstract Service Number				
EXPOSURE	LIMITS IN AIR:				
ACGIH	American Conference on Governmental Industrial Hygienists				
С	Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH	Immediately Dangerous to Life and Health				
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV	Threshold Limit Value				
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D		THE STATE OF THE S	
Е			
F		THE SECOND	

G				
Н				
I				
J			9	
K	F		M	
Х	Consult special h	your supe	ervisor or directions	SOPs for























Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature	source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	Extreme Hazard				
ACD	Acidic				
ALK	Alkaline				
COR	Corrosive				
₩	Use No Water				
OX	Oxidizer				
TREFOIL	Radioactive				



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals				
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{Io}	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{lo} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS	HMIS Canadian Workplace Hazardous Material Information System					
DOT	DOT U.S. Department of Transportation					
TC	Transport Canada					
EPA U.S. Environmental Protection Agency						
DSL Canadian Domestic Substance List						
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL Canadian Non-Domestic Substance List						
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	③	(2)		\odot	®		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

1.***		*	*		® X	X	×	
С	E	F	N	0	Т	Xi	Xn	
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful	

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\ODE		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment