

1.1

1.2

1.3

1.4

1.5

1.6

1.7 1.8

19

21

S100L

4.1

4.2

Page 1 of 6 SDS-E-SN5MS-15

IDLH

NA

NA

NA

May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in

Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination,

drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping,"

apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.

OTHER

SAFETY DATA SHEET Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 1/26/2015 SDS Revision: 5.0 1. PRODUCT & COMPANY IDENTIFICATION Product Name: DEOXIT® Shield S-SERIES, 5% MINI-SPRAY, (P/N SN5MS-15), 14 grams, VOC Compliant Chemical Name: NA DeoxIT® Shield S-Series 5% Spray; PN SN5MS-15 Synonyms: Trade Names: DeoxIT® Shield S-Series 5% Spray; PN SN5MS-15 Product Uses & Restrictions: Lubricant and Protectant for electronic contacts & connectors Distributor's Name: CAIG Laboratories, Inc. Distributor's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX) Business Phone / Fax: +1 (800) 224-4123 2. HAZARDS IDENTIFICATION This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS Hazard Identification: according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. EXT EXTREMELY FLAMMABLE GAS. Classification: Aerosols 1, Flam. Gas 1 Hazard Statements (H): H229 - Pressurized container; may burst if heated. Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P410P412 -Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F P332+P313 - If skin irritation occurs: get medical advice/attention. P377 - Leaking gas fire: Don not extinguish, unless leak can be stopped safely. P381 - In case of leakage, eliminate all ignition sources. P403 - Store in a well-ventilated place. P405 - Store locked up. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF). 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-STEL STEL CAS No. RTECS No. EINECS No. TLV TWA STEL PEAK PEL CHEMICAL NAME(S) % 60-100 460-73-1 NA 419-170-6 300 NA NF NF NF NA NA 1,1,1,3-3-PENTAFLUORPROPANE 75-28-5 TZ4300000 200-857-2 10-30 600 750 NF NF NF NA NA ISOBUTANE Press. Gas, Flam. Gas 1; H229, H220 DEOXIT® SHIELD S-SERIES. PROPRIETARY – TRADE SECRET 3-7 NA NA NF NF NF NA NA 4. FIRST AID MEASURES If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk First Aid: Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Splashes are not likely; however, mist may cause irritation. If product gets in the eyes may cause irritation; Eyes: flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention. Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. If breathing difficult, administer oxygen. Gross overexposure may Inhalation: cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, lightheadedness, weakness, fainting, loss of consciousness, and death. Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea, Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eves:

watering.

some sensitive individuals.

Skin:

Inhalation:



7.3

Special Precautions:

Clean all spills promptly.

SAFETY DATA SHEET

Page 2 of 6 SDS-E-SN5MS-15

Prep	ared to OSHA, ACC, ANSI,	NOHSC, WHMIS	, 2001/58 & 1272/2008/EC Standards	SDS Revis	ion: 5.0	SDS Rev	ision Date: 1/2	26/2015	
			4. FIRST AID MEASU	RES – conť	d				
4.3	Symptoms of Overexposure:	Ingestion: Eyes: Skin:	Nausea, intestinal discomfort, vomiting Overexposure in eyes may cause redr Symptoms of skin overexposure may like symptoms. The product can ca individuals.	hess, itching and w include redness, use allergic skin r	itching, and reactions ((e.g., rashes,	welts, derma	atitis) i	in some
		Inhalation:	Gross overexposure may cause central drowsiness, irregular heartbeat acc apprehension, light-headedness, weak	ompanied by a concernent of a	strange fe	eeling in the iousness, and	chest, "head death.	art thu	umping,"
4.4	Acute Health Effects:	drowsiness,	ritation to eyes and skin near affecte dizziness, headaches and nausea. Fros	tbite like effect to	skin.		•		
4.5	Chronic Health Effects:		re may trigger asthma-like symptoms ir hypersensitivity. Possible allergic derma		ndividuals.	May also inc	luce skin se	nsitizat	tion and
4.6	Target Organs:	Eyes, Skin,	Respiratory System.						
4.7	Medical Conditions Aggravated by Exposure:		dermatitis, other skin conditions, and s (eyes, skin, and respiratory system).	disorders of the	FLAMN	FLAMMABILITY 1			
						CAL HAZAR			0
					PROTE	CTIVE EQU	IPMENT		В
					EYES	SKIN			
5.1	Fire & Explosion Hazards:		5. FIREFIGHTING N psol (NFPA 30B). Aerosols may burst a						
5.2	Extinguishing Methods:	containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Hydrogen Fluoride).							
5.3	Firefighting Procedures:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to cool unopened containers. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.						0	
	1	-1	6. ACCIDENTAL RELEA						
6.1	Spills:	Equipment. Small Spills material suc water or a in plastic broo Large Spills or release.	ning any spill or leak, individuals invo Plastic or rubber gloves, respirator, eye : Wear appropriate protective equipmer ch as vermiculite or sand to soak up th material such as "speedy dry" to soak u ms, shovels, dustpans) and place into a : Keep incompatible materials (e.g., or Isolate immediate hazard area and keep inimal risk. Wear appropriate protective	e protection and ap nt including gloves e product and pla up material. Swee plastic container o ganics such as oil) o unauthorized per	oron may b and protece into a cop or plastic lir away fror sonnel out	be required for active eyewea container for la erial using no her within anot n spill. Stay u t of area. Stop	clean-up of r. Use a no ater disposa n-sparking n ther containe upwind and a o spill or rele	large s n-coml l. Do n naterial er. away fr ase if it	spills. bustible not use ls (e.g., rom spill t can be
		7	. HANDLING & STORAG	E INFORMA	TION				
7.1	Work & Hygiene Practices:	Do not eat, container(s)	drink or smoke when handling this p. . When used as intended, no addition ossible. Wash unintentional residues wit	roduct. Contents al protective equip	under pre ment is n				
7.2	Storage & Handling:	Use and sto sunlight. Av	ore in a cool, dry, well-ventilated location oid temperatures above 120 °F. Keep a provid unintentional spraying keep cap is	on (e.g., local exh way from incompa	aust venti atible subs				
7.3	Special Precautions:	Clean all sn	, , , , , , ,						



Page 3 of 6 SDS-E-SN5MS-15

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.0 SDS

SDS Revision Date: 1/26/2015

		8. EXPOSURE C	CONTROLS	& PER	SONA	L PRO	TECI	FION		
8.1	Exposure Limits:		ACGIH		NOHSC			OSHA		OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOBUTANE	600 750	NF	NF	NF	NA	NA	NA	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g. exhaust ventilation to eff product. Ensure appropria	ectively remove a	nd preven	t buildup	of vapors	or mist	genera	ted from	the handling of thi
8.3	Respiratory Protection:	No special respiratory pro- instances where dusts of protection authorized by CAS Standard Z94.4-93 a	otection is require this product are ge 29 CFR §1910.13	d under ty enerated, a 4, applica	vpical circo ind respira ble U.S. S	umstances itory protec State regula	of use tion is r ations,	or hand needed, or the C	lling. In use only Canadian	
8.4	Eye Protection:	Australia. Avoid eye contact. None when handling or using la				ise. Safety	glasse	es could	be used	
8.5	Hand Protection:	None required under no sensitive individuals. Whe impervious plastic gloves.	en handling large q							
8.6	Body Protection:	No apron required when I eye wash stations and do involving large quantities of	handling small qua eluge showers sho	ould be av	ailable. I	Jpon comp	letion o	of work	activities	
		·					_			
		9. PHYS	ICAL & CHE	MICAL	. PROI	PERTIE	S			
9.1	Appearance:	Light blue aerosol spray/n	nist							
9.2	Odor:	Ethereal / hydrocarbon oc								
9.3	Odor Threshold:	NA								
9.4	pH:	NA								
9.5	Melting Point/Freezing Point:									
	° °	NA								
9.6	Initial Boiling Point/Boiling Range:	15 °C (59 °F) - 1,1,1,3,3-F	Pentafluoropropane	Э						
9.7	Flashpoint:	NA								
9.8	Upper/Lower Flammability									
	Limits:	NA								
9.9	Vapor Pressure:	50 +/-5 PSIG @ 20 °C								
9.10	Vapor Density:	NA								
9.11	Relative Density:	0.8								
9.12	Solubility:	Not soluble in water								
9.13	Partition Coefficient (log Pow):	NA								
9.14	Autoignition Temperature:	412 °C (774 °F) – 1,1,1,3,	3-Pentafluoroprop	ane						
9.15	Decomposition Temperature:	NA	· · ·							
9.16	Viscosity:	NA								
9.17	Other Information:	VOC content 268 g/L								
		100 contont 200 g/2								
	1		STABILITY							
10.1	Stability:	Stable under normal cond	· ·							
10.2	Hazardous Decomposition Products: Hazardous Polymerization:	Change in color signifies of Discard solution.	exposure to ultravi	olet light o	r exceedin	g shelf life.	Will no	ot degrad	de to uns	table products.
10.3	•	Will not occur.								
10.4	Conditions to Avoid:	Open flames, sparks, high	· · ·			U	nt.			
10.5	Incompatible Substances:	Avoid extreme heat and ig	gnition sources. St	ore away fi	rom oxidiz	ers.				
		44 70								
			XICOLOGI							
11.1	Routes of Entry:		/ES			YES			Ingestic	120
11.2	Toxicity Data:	This product has NOT be available for some of the of 1,1,1,3,3-Pentafluoroprop noted at 35,000 ppm, the ppm. Acute Inhalation (r effect. Acute Inhalation (r activity during exposure	components of the ane: Acute Derm threshold for induc at): 4-hr. LC ₅₀ > 2	product: al (rabbit) ction of car 00,000 ppi	– LD₅₀ > rdiac arrhy m. No let	2,000 mg/k thmias in tl hality at 20	kg; Card he pres 00,000	diac Ser ence of opm. Ev	nsitizatior injected a idence o	i (dogs) – No effect adrenalin was 44,00 f transient anestheti
11.3	Acute Toxicity:	Moderate irritation to ey	activity during exposure. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.							
				ou.						
11.4	Chronic Toxicity:	This material may aggrava			dition (e.a.	, dermatitis).			



Page 4 of 6 SDS-E-SN5MS-15

	LABORATORIES, INC.	
repa	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 5.0 SDS Revision Date: 1/26/2015
		11. TOXICOLOGICAL INFORMATION – cont'd
.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.
7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
8	Biological Exposure Indices:	NE
.9	Physician Recommendations:	Treat symptomatically.
		12. ECOLOGICAL INFORMATION
.1	Environmental Stability:	There is no specific data available for this product.
2.2	Effects on Plants & Animals:	There are no specific data available for this product.
2.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fail to overexposed aquatic life.
.1	Waste Disposal:	13. DISPOSAL CONSIDERATIONS Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous was
		according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and fede
		regulations. Dispose of in accordance with federal, state and local regulations.
3.2	Special Considerations:	California Waste Code: 331
		14. TRANSPORTATION INFORMATION
he esc	basic description (ID Nur	nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Addition e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.
.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L); or
		CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020
.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or
		ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)
.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)
1.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L);
		or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ
1.5	ADR/RID (EU):	
i.5	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L)
1.7	ADGR (AUS):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL \leq 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L)
	1	15. REGULATORY INFORMATION
5.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.
5.2	SARA Threshold Planning	There are no specific Threshold Planning Quantities for the components of this product.
5.3	Quantity: TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
5.4	CERCLA Reportable Quantity	
	(RQ):	NA
.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).
5.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products
		Regulations (CPR) and the SDS contains all of the information required by the CPR. The
		components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.
		15. REGULATORY INFORMATION – cont'd
.7	State Regulatory Information:	1,1,1,2-Tetrafluorethane can be found on the following state criteria lists: Minnesota Hazardous Substances List (MN)
		No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following sta
		criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (MA) Michigan Critical Substances List (MA) Michigan Critical Substances List (MA)
		List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardou Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylva
		Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
5.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC:
		Isobutene: Flammable (F)
		Risk Phrases: (R) 12 – Extremely flammable. Safety Phrases: (S) 2-9-16 – Keep out of reach of
		children. Keep container in a well-ventilated place. Keep away from sources of ignition - No
		smoking.

smoking.



Page 5 of 6 SDS-E-SN5MS-15

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.0

SDS Revision Date: 1/26/2015

		16. OTHER INFO	RMATION					
16.1	Other Information:	DANGER! PRESSURIZED CONATINER; MAY BURST IF HEATED. EXTREMELY FLAMMABLE GAS. Use only as directed. Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.						
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.						
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/	BALLABORATORIES, INC.					
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate Dangerous Goods Training & Consulting					



Page 6 of 6 SDS-E-SN5MS-15

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 5.0

SDS Revision Date: 1/26/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists				
C	C Ceiling Limit				
ES	Exposure Standard (Australia)				
IDLH Immediately Dangerous to Life and Health					
OSHA U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit				
STEL	Short-Term Exposure Limit				
TLV Threshold Limit Value					
TWA	Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:

Α			G				
в	0		Н	0		H H H	
С	0		I				
D	B		J			Î	
Е			K	E			
F	8		X	Consult y special ha			
Sa	afety Glasse	es Splash Goggles		e Shield & tive Eyewe	ar	Glove	s
	Boots	Synthetic Apron		tive Clothiı Full Suit	ng E	Oust Resp	pirator
						1	
Full I	Face Respi	rator Dust & Vapor Half- Mask Respirator	-	ull Face espirator	Ai	rline Hoo or SCI	
OTH	ER STAN	DARD ABBREVIATION	S:				
	ML	Maximum Limit					
	mg/m3	milligrams per cubic meter					
NA Not Available							
ND Not Determined							
	NE	Not Established					
	NF NR	Not Found No Results					
	ppm	parts per million					
-	SCBA	Self-Contained Breathing A	oparatus				
1							

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition	Autoignition Minimum temperature required to initiate combustion in air with no other					
Temperature	source of ignition					
LEL						
	explode or ignite in the presence of an ignition source					
UEL	UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
OX	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

Lethal Dose (solids & liquids) which kills 50% of the exposed animals
Lethal concentration (gases) which kills 50% of the exposed animal
Concentration expressed in parts of material per million parts
Lowest dose to cause a symptom
Lowest concentration to cause a symptom
Lowest dose (or concentration) to cause lethal or toxic effects
International Agency for Research on Cancer
National Toxicology Program
Registry of Toxic Effects of Chemical Substances
Bioconcentration Factor
Median threshold limit
Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

\bigcirc	۲	۲		Ð	۲		Ŕ		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F		
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive		

EC (67/548/EEC) INFORMATION:

		×	¥	8	® X	×	×		
С	Е	F	Ν	0	т	Xi	Xn		
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful		

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\:		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment