| | | MSDS #3004 |
|--|---|--|
| SECTION 1: CHEMICAL PRODUCT AND COMPANY | INFORMATION | |
| Company Address: | | |
| 125 Cobb Center Drive | | |
| Kennesaw, GA 30152 Product Information: 800-TECH-401 | Emorgonov | (Chemtrec) 800-424-9300 |
| Customer Service: 800-645-5244 | Emergency: Revision Date: | February 10, 2007 |
| roduct Identification | | |
| 0 | CIRCUITWORKS® HEAT SIN | K GREASE |
| roduct Code: CT40-5, CT405B | | |
| ECTION 2: COMPOSITION/INFORMATION ON ING | REDIENTS | |
| Chemical Name | CAS# | Wt. % Range |
| Polymethyldisiloxane Fluid | 63148-62-9 | 25.0-30.0 |
| Cinc Oxide Fumed Silica | 1314-13-2 112945-52-5 | 70.0-75.0 1.0-5.0 |
| ECTION 3: HAZARD IDENTIFICATION | 112)+3 52 5 | 1.0 5.0 |
| | oduct is nonflammable. Paste v | ill cause acute but mild irritation of the eyes and skin under repeated of |
| rolonged exposure. | | |
| Potential Health Effects: | antan and dan tan 199 | |
| Eyes: Product is irritating and can cause acute but mild te Skin: Contact with product can cause acute but mild skin | | a stinging sensation. |
| ngestion: Irritating to mouth, throat and stomach. May cause | | and diarrhea |
| nhalation: No known health effects from inhalation. | | |
| re-Existing Medical Conditions Aggravated by Exposure: SI | kin, eye. | |
| ECTION 4: FIRST AID MEASURES | | |
| | | enses and continue flushing for at least 15 minutes. Have eyes examine |
| nd tested by medical personnel if irritation develops persists. | | |
| | th soap and water. Remove cont | aminated clothing. Get medical attention if irritation develops or persists |
| Vash clothing separately before reuse. ngestion: Do not induce vomiting, but give one or two glasse | as of water to dilute material and | get immediate medical attention |
| nhalation: Remove to fresh air. If not breathing, give artifici | | |
| ECTION 5: FIRE FIGHTING MEASURES | | |
| | | |
| | LEL/UEL: Not established | (% by volume in air) |
| 'l <u>ash Point:</u> >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, wate | <u>LEL/UEL</u> : Not established er spray, or dry chemical when fi | ghting fires involving this material. |
| <u>'lash Point:</u> >500 F (260C) (TCC) <u>Extinguishing media:</u> Use alcohol foam, carbon dioxide, wate <u>'ire Fighting Instructions:</u> As in any fire, wear self-contained | er spray, or dry chemical when fi | |
| Plash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, wate | er spray, or dry chemical when fi | ghting fires involving this material. |
| <u>ash Point:</u> >500 F (260C) (TCC) <u>ixtinguishing media:</u> Use alcohol foam, carbon dioxide, wate <u>ire Fighting Instructions:</u> As in any fire, wear self-contained Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES | er spray, or dry chemical when fi d breathing apparatus (pressure-o | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea |
| Plash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Pire Fighting Instructions: As in any fire, wear self-contained Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Large Spills: Shut off leak if possible and safe to do so. | er spray, or dry chemical when fi d breathing apparatus (pressure-o ear self-contained breathing app | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit |
| lash Point: >500 F (260C) (TCC) <u>axtinguishing media:</u> Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. weat material (e.g. dry sand or earth), then place in a chemica | er spray, or dry chemical when fi d breathing apparatus (pressure-o ear self-contained breathing app | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, wate ire Fighting Instructions: As in any fire, wear self-contained tool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. Weart material (e.g. dry sand or earth), then place in a chemica which lead to waterways. | er spray, or dry chemical when fi d breathing apparatus (pressure-o ear self-contained breathing app l waste container for proper disp | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche |
| lash Point: >500 F (260C) (TCC) extinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or | er spray, or dry chemical when fi d breathing apparatus (pressure-o ear self-contained breathing app l waste container for proper disp | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche |
| lash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water the Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES targe Spills: Shut off leak if possible and safe to do so. whert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. |
| lash Point: >500 F (260C) (TCC) <u>axtinguishing media:</u> Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE word prolonged or repeated contact of product with eyes, ski | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, wate ire Fighting Instructions: As in any fire, wear self-contained tool fire-exposed containers with water. Section 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W tert material (e.g. dry sand or earth), then place in a chemica thich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE void prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gear aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried produc |
| lash Point: >500 F (260C) (TCC) ixtinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica /hich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE woid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. EXPLOSE | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands befor vay from heat, sparks and flame. | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gear aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried produc |
| lash Point: >500 F (260C) (TCC) <u>axtinguishing media:</u> Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI axposure Guidelines: | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gear aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried produc Keep container closed when not in use. Do not store in direct sunlight. |
| lash Point: >500 F (260C) (TCC) axtinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI axposure Guidelines: CHEMICAL NAME ACG | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef yay from heat, sparks and flame. ROTECTION IH TLV OSE | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained tool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W tert material (e.g. dry sand or earth), then place in a chemica thich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE void prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI xposure Guidelines: CHEMICAL NAME ACGI olymethyldisiloxane NA | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef yay from heat, sparks and flame. ROTECTION IH TLV OSH NA | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained ool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W tert material (e.g. dry sand or earth), then place in a chemica hich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE void prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI xposure Guidelines: 'HEMICAL NAME ACGI olymethyldisiloxane NA inc Oxide 2 mg. | er spray, or dry chemical when fi d breathing apparatus (pressure-of- lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSH NA /m3 (dust) 15 m | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditched waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA g/m3 (dust) 10 mg/m3 (dust) STEL |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, water ire Fighting Instructions: As in any fire, wear self-contained ool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W tert material (e.g. dry sand or earth), then place in a chemica hich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE void prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI xposure Guidelines: HEMICAL NAME ACGI olymethyldisiloxane NA inc Oxide 2 mg umed Silica 10 mg | er spray, or dry chemical when fi d breathing apparatus (pressure-o lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef yay from heat, sparks and flame. ROTECTION IH TLV OSH NA | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA |
| lash Point: >500 F (260C) (TCC) xtinguishing media: Use alcohol foam, carbon dioxide, wate ire Fighting Instructions: As in any fire, wear self-contained tool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES arge Spills: Shut off leak if possible and safe to do so. W tert material (e.g. dry sand or earth), then place in a chemica thich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE .void prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI xposure Guidelines: 'HEMICAL NAME ACGI olymethyldisiloxane NA inc Oxide 2 mg umed Silica 10 mg VA = not available 10 mg | er spray, or dry chemical when fi d breathing apparatus (pressure-of- lear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSH NA /m3 (dust) 15 m | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill with osal. Do not flush to sewer. Avoid runoff into storm sewers and ditched waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA g/m3 (dust) 10 mg/m3 (dust) STEL |
| lash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica /hich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE woid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw CEP OUT OF REACH OF CHILDREN. EXPOSURE CONTROLS/PERSONNEL PI Exposure Guidelines: CHEMICAL NAME ACGI 'olymethyldisiloxane NA 'Ginc Oxide 2 mg, 'umed Silica 10 mg VA = not available PNOC = Particles not otherwise classified Vork/Hygienic Practices: Good general ventilation should | er spray, or dry chemical when fi d breathing apparatus (pressure-o l'ear self-contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSH NA /m3 (dust) 15 m z/m3 (PNOC dust) NA | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA g/m3 (dust) 10 mg/m3 (dust) STEL 6 mg/m3 OEL • levels. Local exhaust ventilation may be necessary to control any at |
| Plash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Pire Fighting Instructions: As in any fire, wear self-contained Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. imall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE Avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw ECETION 8: EXPOSURE CONTROLS/PERSONNEL PI Exposure Guidelines: "HemitCAL NAME ACGI volumed Silica 10 mg VA = not available PNOC = Particles not otherwise classified VOR/Hygienic Practices: Good general ventilation should ontaminants to within their TLVs during the use of this prod | er spray, or dry chemical when fi d breathing apparatus (pressure-o l waste contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSE NA /m3 (dust) 15 m z/m3 (PNOC dust) NA be sufficient to control airborne luct. If vapor concentration exce | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER g/m3 (dust) 10 mg/m3 (dust) STEL 6 mg/m3 OEL elevels. Local exhaust ventilation may be necessary to control any ai eds TLV, use NIOSH approved organic vapor cartridge respirator. Wea |
| Plash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Pire Fighting Instructions: As in any fire, wear self-contained Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. imall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE Avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw ECETION 8: EXPOSURE CONTROLS/PERSONNEL PI Exposure Guidelines: "Delymethyldisiloxane NA "Our of a contained be NA "Our on tavailable 10 mg PNOC = Particles not otherwise classified Vork/Hygienic Practices: Work/Hygienic Practices: Good general ventilation should ontaminants to within their TLVs during the use of this produation aftery glasses with side shields (or goggles) and rubber or otherwork of the store store of the store of the store of the stor | er spray, or dry chemical when fi d breathing apparatus (pressure-of l waste contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSE NA /m3 (dust) 15 m g/m3 (PNOC dust) NA be sufficient to control airborned luct. If vapor concentration exce er chemically resistant gloves wh | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER g/m3 (dust) 10 mg/m3 (dust) STEL 6 mg/m3 OEL elevels. Local exhaust ventilation may be necessary to control any ai eds TLV, use NIOSH approved organic vapor cartridge respirator. Wea en handling this material. |
| lash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica /hich lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE woid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI Exposure Guidelines: 'HEMICAL NAME ACGI 'o'ymethyldisiloxane NA 'and Silica 10 mg 'A = not available ?POC = Particles not otherwise classified Vork/Hygienic Practices: Good general ventilation should ontaminants to within their TLVs during the use of this prod afety glasses with side shields (or goggles) and rubber or othe | er spray, or dry chemical when fi d breathing apparatus (pressure-of l waste contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSE MA /m3 (dust) 15 m g/m3 (PNOC dust) NA be sufficient to control airborned luct. If vapor concentration exce er chemically resistant gloves wh NFPA | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA 10 mg/m3 (dust) STEL g/m3 (dust) 10 mg/m3 OEL elevels. Local exhaust ventilation may be necessary to control any ai eds TLV, use NIOSH approved organic vapor cartridge respirator. Weaten handling this material. HMIS |
| lash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W hert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE Avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw EEP OUT OF REACH OF CHILDREN. ECTION 8: EXPOSURE CONTROLS/PERSONNEL PI Exposure Guidelines: CHEMICAL NAME ACGI Vomed Silica 10 mg VA = not available 2 mg, PNOC = Particles not otherwise classified Vork/Hygienic Practices: Vork/Hygienic Practices: Good general ventilation should ontaminants to within their TLVs during the use of this prod aftery glasses with side shields (or goggles) and rubber or othe UFPA and HMIS Codes: | er spray, or dry chemical when fi d breathing apparatus (pressure-of l waste contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSE MA /m3 (dust) 15 m g/m3 (PNOC dust) NA be sufficient to control airborned luct. If vapor concentration exce er chemically resistant gloves wh NFPA 1 | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA g/m3 (dust) 10 mg/m3 (dust) STEL 6 mg/m3 OEL elevels. Local exhaust ventilation may be necessary to control any at eds TLV, use NIOSH approved organic vapor cartridge respirator. Weaten handling this material. HMIS 1 |
| Plash Point: >500 F (260C) (TCC) Extinguishing media: Use alcohol foam, carbon dioxide, water Pire Fighting Instructions: As in any fire, wear self-contained Cool fire-exposed containers with water. ECTION 6: ACCIDENTAL RELEASE MEASURES Earge Spills: Shut off leak if possible and safe to do so. W nert material (e.g. dry sand or earth), then place in a chemica which lead to waterways. mall Spills: Absorb spill with inert material (e.g. dry sand or ECTION 7: HANDLING AND STORAGE Avoid prolonged or repeated contact of product with eyes, ski ust. Do not reuse this container. Store in a cool dry place aw KEEP OUT OF REACH OF CHILDREN. EXERCISE ACGI Supsoure Guidelines: NA 'olymethyldisiloxane NA 'olymethyldisiloxane NA 'Chic Oxide 2 mg, 'A = not available 10 mg PNOC = Particles not otherwise classified Vork/Hygienic Practices: | er spray, or dry chemical when fi d breathing apparatus (pressure-of l waste contained breathing app l waste container for proper disp earth), then place in a chemical n, and clothing. Wash hands bef vay from heat, sparks and flame. ROTECTION IH TLV OSE MA /m3 (dust) 15 m g/m3 (PNOC dust) NA be sufficient to control airborned luct. If vapor concentration exce er chemically resistant gloves wh NFPA | ghting fires involving this material. lemand, OSHA/NIOSH approved or equivalent) and full protective gea aratus and appropriate personal protective equipment. Absorb spill wit osal. Do not flush to sewer. Avoid runoff into storm sewers and ditche waste container for proper disposal. ore eating. Use with adequate ventilation. Avoid breathing dried product Keep container closed when not in use. Do not store in direct sunlight. A PEL OTHER NA 10 mg/m3 (dust) STEL g/m3 (dust) 10 mg/m3 OEL elevels. Local exhaust ventilation may be necessary to control any ai eds TLV, use NIOSH approved organic vapor cartridge respirator. Weaten handling this material. HMIS |

| ITW CHEMTRONICS | MSDS #3004 |
|--|---------------------------------|
| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIESPhysical State:White, opaque pasteSolubility in Water: NegligibleOdor:NoneSpecific Gravity:2.60 (Water =1)pH:NAEvaporation Rate: <<1Vapor Pressure:NA(Butyl acetate=1)Vapor Density:NAViscosity: > 1 (water=1)Boiling Point:>300 F (149C)Percent Volatile: <1 %Melting Point:N/AN/A | |
| SECTION 10: STABILITY AND REACTIVITY Stability: This product is stable. Conditions to Avoid: None Incompatibility: Do not mix with amines, strong bases or strong oxidizing agents. Products of Decomposition: Thermal decomposition at temperatures above 575 0F may release silicon dioxide and carbon dioxide. Hazardous Polymerization: Not likely to occur. Conditions to Avoid: Exposure to amines, bases or strong oxidizing agents. | |
| $\begin{array}{c c c c c c } \textbf{SECTION 11: TOXICOLOGICAL INFORMATION} \\ \hline \\ $ | |
| Environmental Impact Information Avoid runoff into storm sewers and ditches, which lead to waterways. Water runoff can cause environmental damage. REPORTING US regulations require reporting spills of this material that could reach any surface waters. The toll-free number for the US Coast Gua 1-800-424-8802 | rd National Response Center is: |
| SECTION 13: DISPOSAL CONSIDERATIONS Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage. SECTION 14: TRANSPORTATION INFORMATION Air and Ground Shipments: Proper Shipping Name Adhesives, sealants Not Regulated | |
| SECTION 15: REGULATORY INFORMATION SECTION 313 SUPPLIER NOTIFICATION This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Commune (40 CFR 372). This information should be included on all MSDSs copied and distributed for this material. <u>TOXIC SUBSTANCES CONTROL ACT (TSCA).</u> All ingredients of this product are listed on the TSCA Inventory. <u>WHMIS:</u> Not hazardous. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the CPR. | |
| SECTION 16: OTHER INFORMATION Normal ventilation for standard manufacturing practices is usually adequate. To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and particular, improper use of our products and their inappropriate combination with other products and substances may produce h anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are uncontract that these are the only bagedes that mou origin | armful results which cannot be |

guarantee that these are the only hazards that may exist.