CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Phone: 978-373-1600 | Website: http://www.circuitmedic.com

Revision Date: May 20, 2015 Page 1 of 5 Pages

CircuitMedic disclaims all liability associated with the use of this information.

Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Plating Solution, Electroclean
Product Number: 1 oz: 115-3841, 4 oz: 115-3844

Distributor: CircuitMedic

22 Parkridge Road, Haverhill, MA 01835 USA PHONE: 978-373-1600, FAX: 978-372-5700

Emergency Response: For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 CCN4877

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)



Section 2. HAZARD IDENTIFICATION

Classifications: Classification according to Regulation(EC)No1272/2008

Classifications applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200)

Emergency Overview:

Potential Health Effects:

Intritating to the eyes, nose, throat and lungs. May cause sneezing, watering of eyes, nasal discharge and coughing.

Eyes: Corrosive to the eyes and may cause severe eye damage.

Skin: Causes skin irritation. May cause skin burns.

Ingestion: May cause severe and permanent damage to mouth, throat and stomach.

Section 3. COMPOSITION, INFORMATION OR INGREDIENTS

Chemical Name	RTECS #	C.A.S. Number	Weight %	OSHA PEL	ACGIH TLV	ACGIH Ceiling	NIOSH REL	NIOSH IDLH
Sodium Hydroxide	WB4900000	1310-73-2	1-5	2mg/M3	N/A	2mg/M3	2mg/M3	10mg/M3
Water	ZC0110000	7732-18-5	95-99	N/A	N/A	N/A	N/A	N/A

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200): Exposure Limits 8 Hours TWA (PPM)

Section 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. Lay victim down, legs raised. Loosen tight clothing, cover with a blanket, If not breathing, give

artificial respiration. If breating is difficult, give oxygen.

Eye Contact: Hold eyelids apart and flush with plenty of water for at least 15 minutes.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Thoroughly decontaminate (or discard) clothing and shoes.

Ingestion: DO NOT induce vomiting, unless advised by EMS. Give victim large quantities of water or milk with 1-2 fresh eggs.

Give a glass of 1/3 vinegar with 2/3 water. Never give anything by mouth to an unconscious person.

Revision Date: May 20, 2015

Page 2 of 5 Pages

Safety Data Sheet 115-3841/115-3844

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA

Phone: 978-373-1600 | Website: http://www.circuitmedic.com

CircuitMedic disclaims all liability associated with the use of this information.

Section 5. FIRE-FIGHTING MEASURES

Flash Point & Method: 230°F (C.O.C.).
Flammable Limits: LEL: 1.1 UEL: 6.0

Autoignition Temperature: N/A

General Hazard: Containers can build up pressure and burst if exposed to heat (fire). Water runoff can cause

environmental damage. Dike area for later disposal.

Fire Fighting Instructions: NIOSH/MSHA approved positive-pressure self-contained breathing apparatus. Structural fire fighters'

protective clothing may not provide adequate protection.

Hazardous Combustion Prod. N/A

Flammable Properties: Material will not burn.

Extinguishing Media: All.

Section 6. ACCIDENTAL RELEASE MEASURES

Land Spill: Do not touch or walk through spilled material. Isolate hazard area and keep people away. Notify your facility

emergency coordinator. Eliminate all sources of ignition. Provide maximum ventilation. Do not release into soil, sewers or natural bodies of water. Wear proper personal protective equipment (PPE). Carefully mop up or vacuum spill and triple rinse with water into suitable plastic container. Release of a reportable quantity (RQ) require notification of proper authorities. Dispose of according to local, state, and federal regulations.

Neutralizing Agent: Dilute Hydrochloric Acid (6M)

Section 7. HANDLING AND STORAGE

Storage Temperature: 60-90 degrees F
Storage Pressure: Atmospheric

Shelf Life: Unlimited when properly stored away from light in room temperature (60 C / 140F).

General: Use "buddy system" when working with chemicals. Do not get in eyes, on skin or on clothing. Do not breathe

vapor, mist of gas. Use with adequate ventilation. Wash thoroughly after handling. Triple rinse container clean before discarding. Put nothing else in this container. Keep container tightly closed in upright position. Store at 60-90 degrees F away from incompatible materials and physical hazards. Do not remove or deface container

labels.

Section 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Local Exhaust ventilation is required. See section 2 for component exposure guidelines.

Personal Protection:

Respirator: If engineering controls are not feasible, the respiratory protection program must comply with OSHA's 29 CFR

1910.34, 30 CFR 11 and ANSI Z88.2 requirements.

Hand Protection: Protective Gloves Recommended (Nitrile, Neoprene, Vinyl, Latex).

Eye Protection: Use one of the following: Face Shield and Safety Glasses with Side Shields or Chemical Goggles (splash-

proof).

Other Recommended: Use one of the following: Eye Bath, Safety Shower, Washing Station Nearby, Impervious Boots, Apron,

Appropriate Protective Clothing.

Note 1: In accordance with good industrial hygiene, wash hands with soap and water after working with material.

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Phone: 978-373-1600 | Website: http://www.circuitmedic.com

CircuitMedic disclaims all liability associated with the use of this information.

Revision Date: May 20, 2015 Page 3 of 5 Pages/b>

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Density: 1.044-1.054g/ml

pH: 12-14

Boiling Point: >100 degrees C, >212 degrees F
Freezing Point: <0 degrees C, <32 degrees F

Vapor Density (Air = 1): N/A
% Volatile By Weight: N/A
% Solids: N/A
Evaporation Rate (Butyl Acetate = 1: <1

Solubility in Water:

Viscosity:

N/A

Molecular Weight:

N/A

Physical State:

Liquid

Molecular Weight:

N/A

Appearance: Colorless liquid

Vapor Pressure(mmHg): N/A

Section 10. STABILITY AND REACTIVITY

General: Stable under normal ambient conditions

Incompatible materials and Conditions to Avoid: Avoid contact with amphoteric metals, strong acids, anhydrides and aldehydes.

Hazardous Decomposition or Byproducts: NA2O (Sodium oxide)

Hazardous Polmerization: Will not occur.

Section 11. TOXICOLOGICAL INFORMATION

Results of Component Toxicity Test Performed: Information not available.

Human Experience: Information not available.

Section 12. ECOLOGICAL INFORMATION

Further Information: Information not available.

Section 13. DISPOSAL CONSIDERATIONS

RCRA 40 CFR 261 Classification: Federal, State, and Local laws governing disposal of materials can differ. Ensure proper disposal

compliance with proper authorities before disposal.

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Phone: 978-373-1600 | Website: http://www.circuitmedic.com CircuitMedic disclaims all liability associated with the use of this information.

Revision Date: May 20, 2015 Page 4 of 5 Pages

Section 14. TRANSPORT INFORMATION

This product is always shipped in very small quantities, less than 1 liter. Limited quantity exceptions are applicable for this product if requirements in 49 CFR 173.154 (b), are met. Under these exceptions, inner packaging must not be over 1.0 liters (0.3 gallon), net capacity for liquids, packed in strong outer packaging. Each package must not exceed 30 kg (66 lb) gross weight. In addition, shipments of these limited quantities are not subject to Subpart F (Placarding) of Part 172. Packages must comply with Subpart B of Part 172.

DOT, IATA, ICAO, and IMO Description:

Basic Description: Electrocleaning Solution

Proper Shipping Name: Sodium Hydroxide Solution

Hazard Class: 8
Packaging Group: II
UN Number: UN 1824

Label Requirements: 8 - Corrosive

Max. Shippable Qty.:

1 liter by Air, no Ground limitations

Packaging: Meets Performance Oriented Packaging Requirements

Reportable Quantity (RQ): N/A
1996 NAERG Guide#: 154
Limitations: N/A

Do not transfer to unmarked containers. Non-Regulated under D.O.T.

Section 15. REGULATORY INFORMATION

United States Federal Regulations:

MSDS complies with OSHA's Hazard Communication Rule, 29 CFR 1910.1200.

CERCLA/SUPERFUND,40 CFR 117, 302: None of the chemicals are Superfund hazards

SARA SUPERFUND AND REAUTHORIZATION ACT OF 1986 TITLE III Sections 302, 311, 312 and 313: Section 302 Extremely hazardous substances (40 CFR 355): None of the chemicals are Section 302 hazards.

Section 311/312 - Material Safety Data Sheet Requirements (40 CFR 370): By our hazard evaluation, this product is non-hazardous.

TOXIC SUBSTANCE CONTROL ACT (TSCA): All substances are TSCA Listed.

Section 311/312 - Material Safety Data Sheet Requirements (40 CFR 370): By our hazard evaluation, this product is non-hazardous. TOXIC SUBSTANCE CONTROL ACT (TSCA): All substances are TSCA Listed.

International Regulations:

Canada Whims: NA

Europe EINECS Numbers: NA

Canadian Substance Inventory: One or more of the components of this product do not appear in the Canadian Substance Inventory.

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Phone: 978-373-1600 | Website: http://www.circuitmedic.com

CircuitMedic disclaims all liability associated with the use of this information.

Revision Date: May 20, 2015 Page 5 of 5 Pages

Section 16. OTHER INFORMATION

Label Information:

European risk and Safety Phrases: N/A
European Symbols Needed: N/A
Canadian WHIMS Symbols: N/A

NFPA Hazard Rating: (1) Flammability (1) Health (0) Reactivity

Abbreviations Used in this Document: NE - Not Established, NA - Not Applicable/Not Available, NIF - No Information Found

References: Code of Federal Regulations (CFR)

The Sigma-Aldrich Library of Regulatory and Safety Data Chemical Guide and OSHA Hazard Communication Standard

Various Federal, State & Local Regulations

To the best of our knowledge, the information contained herein is accurate. However, neither Circuit Technology Center, Inc., nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.