

J.P. Nissen Co. 2544 Fairhill Avenue P.O. Box 339 Glenside, PA 19038 Phone: 215-886-2025 Fax: 215-886-0707

Emergency: 1-800-424-9300

Material Safety Data Sheet January 5, 2011 Product Identification NISSEN FELTIP PAINT MARKER – WHITE MARKER

HMIS Ratings- Health 2 Flammability 3 Reactivity 0
NFPA Ratings- Health 2 Flammability 3 Reactivity 0

Hazardous ingredients – The paint is contained in a valve action reservoir and will not leak under normal conditions.

<u>Ingredients</u>	CAS#	<u>%</u>	Exposure Limits
Mineral Spirits	64742-88-7	30 -35	100 ppm/8 hrs pel
VM& P Naptha	64742-89-8	10-15	300 ppm/8 hrs pel
Xylol (Xylene)	1330-20-7	1-5	100 ppm/8 hrs pel
Titanium Dioxide Pigment	13463-67-7	20-25	10 mg/cu.m Respirable dust
Aliphatic Hydrocarbon	64742-47-8	1-5	100 ppm/8hrs pel

Physical Data

Boiling point:246-404 F **Vapor density**: Heavier than air. **Volatile** %: 66.7% by volume **Specific gravity**: Less than 1.

Evaporation rate: Slower than Ethyl Ether Vapor Pressure: 6.2 mm hg @ 20 deg. C

Appearance: White viscous liquid with an aromatic odor.

Volatile Organic Compound data not required because product only produced in quantities of less than 1 liter

Fire and Explosion Data

Flammability Class: IC Flashpoint: 75 deg..F LEL:1% UEL 7%

Extinguishing Media: Foam, Carbon dioxide, or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

Health Hazard Data

Listed as possible carcinogen: NTP - No IARC - OSHA - No

Symptoms of over exposure: Headache, Dizziness, Nausea, Coughing, Eye, Throat and Skin Irritation.

Effects of overexposure: Slight to severe irritation to eyes and mucous membranes. Dermatitis.

Affects central nervous system.

Emergency first aid: Inhalation; seek fresh air. Give artificial respiration if not breathing.

Skin contact; Wash with soap and water. Ingestion; Call Physician. Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs

Reactivity Data

Stability: Stable, hazardous polymerization: Will not occur.

Conditions to avoid: Heat, open flames and sparks. **Incompatibility**: Do not expose to strong oxidizers.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

Environmental Protection Procedures

Remove all sources of ignition, ventilate area, and use absorbent material to clean spills. Disposal method: Dispose of waste in accordance with all local, state and federal regulations.

Control Measures

Respiratory protection: None required under normal use.

Ventilation: Normal-working conditions.

Protective Equipment: Safety glasses and gloves. No special clothing required under normal

conditions of use.

Transportation

Shipping Class ORM-D

UN Number 1263 Package Group III

Toxic Substances Control Act TSCA States:

All components of this product are listed in the EPA's Inventory of Chemical Substances as required under the Toxic Substances Control Act (TSCA)

For more information visit: http://www.nissenmarkers.com/