



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Type: Coating
 Product Name: Red Insulating Varnish
 Part Number(s): 10-9002-A
 10-9008-A

Emergency Contact: Chemtrec
 Phone: (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3
 Acute toxicity (Inhalation) : Category 4
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Skin sensitisation : Category 1
 Carcinogenicity : Category 2
 Reproductive toxicity : Category 2
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
 Specific target organ toxicity - repeated exposure : Category 2 (Kidney, Liver)

GHS Label element

Hazard pictograms :   

Signal word : Warning



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 2. HAZARDS IDENTIFICATION

- Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 2. HAZARDS IDENTIFICATION (CONTINUED)

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Alkyd Resin Solution

Hazardous components

Component	CAS-No.	Concentration (%)
Xylene	1330-20-7	>= 42 - < 43
Ethylbenzene	100-41-4	>= 5 - < 6
Iron(III) oxide	1317-61-9	>= 1 - < 2
2-Butanone oxime	96-29-7	>= 0 - < 1



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 4. FIRST AID MEASURES

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|--------------------------------------|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 5. FIREFIGHTING MEASURES (CONTINUED)

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Absorb with inert absorbent material and dispose of in accordance with applicable regulations.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm	OSHA P0
			545 mg/m3	
Triirontetraoxide	1317-61-9	TWA	10 mg/m3	
		TWA	15 mg/m3	
2-Butanone oxime	96-29-7	TWA	10 ppm	US WEEL

Engineering measures : Use with adequate ventilation.
All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.
Repeated inhalation of such dust may cause lung injury.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid	Thermal decomposition	: No data available
Odour Threshold	: No data available	Viscosity	
pH	: No data available	Viscosity, dynamic	: No data available
Melting point/freezing point	: No data available	Viscosity, kinematic	: Greater than 22 mm ² /s (104 °F (40 °C))
Initial boiling point and boiling range	: No data available		
Flash point	: 75.2 °F (24.0 °C) Method: ASTM D 93		
Evaporation rate	: No data available		
Upper explosion limit	: No data available		
Lower explosion limit	: No data available		
Vapour pressure	: No data available		
Relative vapour density	: No data available		
Relative Density/Specific Gravity	: No data available		
Density	: 1.06 g/cm ³ (68 °F (20 °C))		
Solubility(ies)			
Water solubility	: No data available		
Solubility in other solvents	: No data available		
Partition coefficient: n-octanol/water	: No data available		
Auto-ignition temperature	: No data available		



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
 Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 10325 ppm
 Exposure time: 4 h
 Test atmosphere: gas
 Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,036 mg/kg
 Method: Calculation method

Components:

1330-20-7 Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
 Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

100-41-4 Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

96-29-7 2-Butanone oxime:

Acute oral toxicity : LD50 (Rat): 2,500 mg/kg
Acute inhalation toxicity : LC50 (Rat): 1350 ppm
Acute dermal toxicity : LD50 (Rabbit): 920 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

1330-20-7 Xylene:

Species: Rabbit
Result: Moderate skin irritation

100-41-4 Ethylbenzene:

Species: Rabbit
Result: Moderate skin irritation

96-29-7 2-Butanone oxime:

Species: Rabbit
Result: Moderate skin irritation

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

1330-20-7 Xylene:

Species: Rabbit
Result: Eye irritation

100-41-4 Ethylbenzene:

Species: Rabbit
Result: Moderate eye irritation



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 307
Revision Date: 6/11/2015
Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

96-29-7 2-Butanone oxime:

Species: Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Carcinogenicity

IARC	Group 2B: Possibly carcinogenic to humans	
	Ethylbenzene	100-41-4
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Persistence and degradability

No data available

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Bioaccumulative potential

No data available

Mobility in soil

No data available

Additional ecological information : No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. : UN 1263
 Proper shipping name : Paint
 Class : 3
 Packing group : II
 Labels : Flammable liquid
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1263
 Proper shipping name : PAINT
 Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

National Regulations

49 CFR

UN/ID/NA number : UN 1263
 Proper shipping name : Paint
 Class : 3
 Packing group : II
 Labels : Flammable liquid
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	237

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a SARA 302 RQ.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 15. REGULATORY INFORMATION (CONTINUED)

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard
 Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	42.1 %
Ethylbenzene	100-41-4	5.6 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Xylene	1330-20-7	42.1 %
Ethylbenzene	100-41-4	5.6 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	42.1 %
Ethylbenzene	100-41-4	5.6 %

Non-volatile (Wt) : 51.5 %
 Refer to the product technical data sheet for VOC information.

US State Regulations

Massachusetts Right To Know

Xylene	1330-20-7
Ethylbenzene	100-41-4
Crystalline silica	14808-60-7

Pennsylvania Right To Know



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 15. REGULATORY INFORMATION (CONTINUED)

Xylene	1330-20-7
Modified Alkyd Resin	Not Assigned
Iron oxide	1332-37-2
Ethylbenzene	100-41-4
Toluene	108-88-3

New Jersey Right To Know

Xylene	1330-20-7
Modified Alkyd Resin	Not Assigned
Iron oxide	1332-37-2
Ethylbenzene	100-41-4
Iron(III) oxide	1317-61-9

New Jersey Trade Secret : NOT APPLICABLE
Registry Number for the product (NJ TSNR)

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Ethylbenzene	100-41-4
Crystalline silica	14808-60-7

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene	108-88-3
---------	----------

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

DSL : We certify that all of the components of this product are listed on the DSL.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 307
 Revision Date: 6/11/2015
 Supersedes Date: 2/13/2013

SAFETY DATA SHEET


Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: RED INSULATING VARNISH

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.