

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name: 275 Flux-Cored Lead Free Solder

Relevant identified uses of the substance or mixture and uses advised against

Solder

Professional use of solder

1.3 Details of the supplier of the safety data sheet

This Safety Data Sheet has been updated in accordance with the Globally Harmonized System (GHS).

Manufacturer/Supplier:

Kester Inc.

800 West Thorndale Avenue

Itasca, IL 60143

Tel 00+1 + 630 616 4000

ITW Specialty Materials (Suzhou) Co., Ltd.

Hengqiao Road, Wujiang Economic Development Zone

Suzhou, Jiangsu Province, China 215200

Tel +86 512 82060807

Further information obtainable from: Product Compliance: EHS_Kester@kester.com

1.4 Emergency telephone number:

TRANSPORT EMERGENCY Phone: CHEMTREC (800) 424-9300 (Outside US & Canada): 00+1 +703 527 3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

Signal word Warning

Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P402 Store in a dry place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

For use in industrial installations only.

Restricted to professional users.

Trade name: **275 Flux-Cored Lead Free Solder**

(Continued from page 1)

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Chemical components:

CAS: 7440-31-5 EINECS: 231-141-8	TIN (Sn)		>65%
CAS: 65997-06-0	Rosin	⚠ Skin Sens. 1, H317	3.0-5.0%
CAS: 7440-22-4 EINECS: 231-131-3	SILVER (Ag)		^^
CAS: 7440-50-8 EINECS: 231-159-6	COPPER (Cu)		^^
CAS: 7440-36-0 EINECS: 231-146-5	ANTIMONY (Sb)		^^
CAS: 7440-69-9 EINECS: 231-177-4	BISMUTH (Bi)		^^

Additional information:

^^ See Product Alloy Table

This solder product does not contain any Substance of Very High Concern (SVHC) on the European Chemicals Agency (ECHA) candidate list.

Composition and weight percent of solder alloys varies widely and can be determined by product label.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Follow general first aid procedures.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Seek immediate medical advice.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents:** CO₂. Do not use water.**For safety reasons unsuitable extinguishing agents:** Water**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)Carbon dioxide (CO₂)**5.3 Advice for firefighters****Protective equipment:** Wear self-contained respiratory protective device.

GB

(Continued on page 3)

Trade name: **275 Flux-Cored Lead Free Solder**

(Continued from page 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

7440-31-5 TIN (Sn)

PEL Long-term value 2 mg/m³ metal

REL Long-term value 2 mg/m³

TLV Long-term value 2 mg/m³ metal

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Protection of hands:



Protective gloves

Material of gloves

Nitrile rubber, NBR

(Continued on page 4)

Trade name: **275 Flux-Cored Lead Free Solder**

Natural rubber, NR

(Continued from page 3)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety Glasses with Side Shields Required

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Solid material
Colour: Silver grey
Odour: Odourless

pH-value: Not applicable.

Change in condition

Melting point/Melting range: 221-245 °C

Flash point: Undetermined.

Flammability (solid, gaseous): Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Vapour pressure: Not applicable.

Density at 20 °C: 7.31-7.42 g/cm³

Vapour density: Not applicable.

Solubility in / Miscibility with water: Insoluble.

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: Strong acids, strong oxidizers.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Primary irritant effect:

Skin corrosion/irritation: Irritant to skin and mucous membranes.

Serious eye damage/irritation: Smoke during soldering can cause eye irritation.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

(Continued on page 5)

Trade name: 275 Flux-Cored Lead Free Solder

Irritant

(Continued from page 4)

SECTION 12: Ecological information
12.1 Toxicity
Aquatic toxicity: No further relevant information available.

Additional ecological information:
General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number	Not regulated
14.2 UN proper shipping name	Not regulated
IMDG, IATA	Not regulated
14.3 Transport hazard class(es)	Not regulated

ADR, IMDG, IATA

Class	Not regulated.
--------------	----------------

14.4 Packing group	Not regulated
---------------------------	---------------

14.5 Environmental hazards:	Not applicable.
------------------------------------	-----------------

Marine pollutant:	No
--------------------------	----

14.6 Special precautions for user	Not applicable.
--	-----------------

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
---	-----------------

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

China:	Inventory of Existing Chemical Substances in China (IECSC)
Korea:	Korea Existing Chemicals List (ECL)
Europe:	European Inventory of Existing Commercial Chemical Substances (EINECS)
Japan:	Inventory of Existing and New Chemical Substances (ENCS)
Philippines:	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
USA:	TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Continued on page 6)

Trade name: **275 Flux-Cored Lead Free Solder**

(Continued from page 5)

Hazard pictograms

GHS07

Signal word Warning**Hazard statements**

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P402 Store in a dry place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Safety Data Sheet (SDS) relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet (SDS) as a source for hazard information.

Department issuing MSDS: Product Compliance / EHS Department**Contact:** EHS_Kester@kester.com**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

*** Data compared to the previous version altered.**

275 Flux-Cored Lead-Free Products included in this SDS

Alloy	Diameter	Core	Description	Part #
K100LD	0.01	66	K100LD #66/275 .010 1 LB SPL	2495747631
K100LD	0.015	66	K100LD #66/275 .015 1 LB SPL	2495747609
K100LD	0.02	66	K100LD #66/275 .020 1 LB SPL	2495747610
K100LD	0.025	66	K100LD #66/275 .025 1 LB SPL	2495747619
K100LD	0.031	58	K100LD #58/275 .031 1 LB SPL	2495747601
K100LD	0.031	66	K100LD #66/275 .031 1 LB SPL	2495747618
K100LD	0.05	66	K100LD #66/275 .050 1 LB SPL	2495747613
K100LD	0.05	66	K100LD #66/275 .050 4 LB SPL	2595747613
K100LD	0.062	66	K100LD #66/275 .062 1 LB SPL	2495747615
K100LD	0.093	66	K100LD #66/275 .093 4 LB SPL	2595747634
K100LD	0.25mm	66	275 66 K100LD 0.25mm 1 lb spool	40500985
K100LD	0.4mm	66	275 66 K100LD 0.4mm 1/4 kg Spl	40510445
K100LD	0.6mm	58	275 K100 58 060M 050 125	WI3107
K100LD	0.6mm	66	275 66 K100LD 0.6mm 450g Spl	40510447
K100LD	0.8mm	66	275 K100LD 66 080M 050 125	WI3221
K100LD	0.8mm	66	275 66 K100LD 0.8mm 450g Spl	40510448
K100LD	1.0mm	66	275 66 K100LD 1.0mm 450g Spl	40510449
K100LD	1.2mm	58	275 K100 58 120M 050 125	WI3582
K100LD	1.2mm	66	275 66 K100LD 1.2mm 450g Spl	40510450
K100LD	1.5mm	66	275 66 K100LD 1.5mm 1kg Spl	40510452
SAC305	0.01	58	SN96.5AG03CU.5 #58/275 .010 1 LB SPL	2470687623
SAC305	0.015	58	SN96.5AG03CU.5 #58/275 .015 1 LB SPL	2470687608
SAC305	0.015	66	SN96.5AG03CU.5 #66/275 .015 1 LB SPL	2470687609
SAC305	0.02	50	SN96.5AG03CU.5 #50/275 .020 1 LB SPL	2470687602
SAC305	0.02	58	SN96.5AG03CU.5 #58/275 .020 1 LB SPL	2470687603
SAC305	0.02	66	SN96.5AG03CU.5 #66/275 .020 1 LB SPL	2470687610
SAC305	0.025	58	SN96.5AG03CU.5 #58/275 .025 1 LB SPL	2470687617
SAC305	0.025	66	SN96.5AG03CU.5 #66/275 .025 1 LB SPL	2470687619
SAC305	0.031	50	SN96.5AG03CU.5 #50/275 .031 1 LB SPL	2470687600
SAC305	0.031	58	SN96.5AG03CU.5 #58/275 .031 1 LB SPL	2470687601
SAC305	0.031	66	SN96.5AG03CU.5 #66/275 .031 1 LB SPL	2470687618
SAC305	0.04	58	SN96.5AG03CU.5 #58/275 .040 1 LB SPL	2470687605
SAC305	0.04	66	SN96.5AG03CU.5 #66/275 .040 1 LB SPL	2470687611
SAC305	0.05	58	SN96.5AG03CU.5 #58/275 .050 1 LB SPL	2470687606
SAC305	0.05	66	SN96.5AG03CU.5 #66/275 .050 4 LB SPL	2570687613
SAC305	0.062	50	SN96.5AG03CU.5 #50/275 .062 1 LB SPL	2470687614
SAC305	0.062	58	SN96.5AG03CU.5 #58/275 .062 1 LB SPL	2470687607
SAC305	0.062	66	SN96.5AG03CU.5 #66/275 .062 1 LB SPL	2470687615
SAC305	0.093	58	SN96.5AG03CU.5 #58/275 .093 1 LB SPL	2470687632
SAC305	0.093	58	SN96.5AG03CU.5 #58/275 .093 4 LB SPL	2570687632
SAC305	0.25mm	58	275 58 Sn96.5Ag3Cu0.5 0.25mm 1/4kg Spl	40500755
SAC305	0.25mm	58	275 58 Sn96.5Ag3Cu0.5 0.25mm 1/2kg Spl	40500944
SAC305	0.4mm	58	275 58 Sn96.5Ag3Cu0.5 0.4mm 1/4kg Spl (D)	40510756
SAC305	0.4mm	58	275 965A3C05 58 040M 025 125	WI2663
SAC305	0.4mm	58	275 965A3C05 58 040M 025 125 W	WI2844
SAC305	0.4mm	66	275 965A3C05 66 040M 025 125	WI2664
SAC305	0.5mm	58	275 965A3C05 58 050M 025 125	WI2720
SAC305	0.5mm	58	275 965A3C05 58 050M 025 125 W	WI2843
SAC305	0.6mm	58	275 58 Sn96.5Ag3Cu0.5 0.6mm 1/2kg Spl (D)	40510763
SAC305	0.6mm	58	275 965A3C05 58 060M 050 125	WI2728
SAC305	0.8mm	58	275 58 Sn96.5Ag3Cu0.5 0.8mm 1/2kg Spl (D)	40510758
SAC305	0.8mm	58	275 965A3C05 58 080M 050 125	WI2788
SAC305	1.0mm	58	275 58 Sn96.5Ag3Cu0.5 1.0mm 1/2kg Spl (D)	40510759
SAC305	1.0mm	58	275 965A3C05 58 100M 050 125	WI2789
SAC305	1.2mm	58	275 58 Sn96.5Ag3Cu0.5 1.2mm 1/2kg Spl (D)	40510760
SAC305	1.5mm	58	275 58 Sn96.5Ag3Cu0.5 1.5mm 1/2kg Spl (D)	40510761
SAC305	2.0mm	58	275 58 Sn96.5Ag3Cu0.5 2.0mm 1/2kg Spl (D)	40510927
SAC305	2.5mm	58	275 58 Sn96.5Ag3Cu0.5 2.5mm 1/2kg Spl (D)	40510762
SAC305	3.0mm	58	275 58 Sn96.5Ag3Cu0.5 3.0mm 2.5kg Spl (D)	40510940
SAC357	0.6mm	66	275 965A3C05 66 060M 050 125	WI2853
SAC357	0.8mm	58	275 965A3C05 58 080M 050 125W	WI2898
SAC357	1.0mm	58	275 965A3C05 58 100M 050 125W	WI2897
SN96.5AG3.5	0.031	58	SN96.5AG03.5 #58/275 .031 1 LB SPL	2470407601
SN96.5AG3.5	0.062	58	SN96.5AG03.5 #58/275 .062 4 LB SPL	2570407607
SN96.5AG3.5	0.062	58	SN96.5AG03.5 #58/275 .062 1 LB SPL	2470407607