

## 1: PRODUCT AND COMPANY IDENTIFICATION

**Trade name:** 2224-25 Soldering Flux

**Article number:** C6-00-2224-25

**Application of the substance / the preparation:**

Soldering flux  
Soldering flux

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Kester Inc.  
800 West Thorndale Avenue  
Itasca, IL 60143  
Tel (630) 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd.  
Heng Qiao Road  
Wujiang Economic Development Zone  
Suzhou, Jiangsu 215200 China  
Tel +86 512 82060808

**Information department:** Product Compliance: EHS\_Kester@kester.com

**1.4 Emergency telephone number:**

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300  
CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

## 2: HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labeled according to the CLP regulation.

(Contd. on page 2)

US

Trade name: 2224-25 Soldering Flux

(Contd. of page 1)

**Hazard pictograms**

GHS02 GHS05 GHS07

**Signal word** Danger**Hazard-determining components of labeling:**

Isopropanol

**Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves / eye protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard description:****WHMIS Symbols****Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**3: COMPOSITION OF MIXTURE**

**Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Trade name: 2224-25 Soldering Flux

(Contd. of page 2)

CAS No.	Description	% Range
CAS: 67-63-0 EINECS: 200-661-7	Isopropanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	70-85%
CAS: 79-14-1 EINECS: 201-180-5	Glycolic Acid ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302	3.0-5.0%
CAS: 50-01-1 EINECS: 200-002-3	guanidinium chloride ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	3.0-5.0%
CAS: 56-81-5 EINECS: 200-289-5	glycerol	3.0-5.0%
CAS: 7732-18-5 EINECS: 231-791-2	Water	5-10%

#### 4: FIRST AID MEASURES

##### 4.1 Description of first aid measures

**General information:** Follow general first aid procedures.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5: FIREFIGHTING MEASURES

##### 5.1 Extinguishing media

**Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:

##### 5.3 Advice for firefighters

**Protective equipment:** Wear self-contained respiratory protective device.

#### 6: ACCIDENTAL RELEASE MEASURES

##### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

##### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

##### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Absorb with clay, dry sand, or other inert material. Do not use combustible materials such as sawdust. Place in a chemical waste container.

##### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



**SAFETY DATA SHEET (SDS)**  
According to 1907/2006/EC, Article 31

Version number 3

Reviewed on 11/24/2015

**Trade name: 2224-25 Soldering Flux**

See Section 13 for disposal information.

(Contd. of page 3)

**7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store in a cool location.  
**Information about storage in one common storage facility:** Store away from oxidizing agents.

**Further information about storage conditions:**

Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)** No further relevant information available.

**8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical systems:** No further data; see item 7.

**8.1 Control parameters**

**Components with limit values that require monitoring at the workplace:**

**67-63-0 Isopropanol**

PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI

**56-81-5 glycerol**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> mist; *total dust **respirable fraction
TLV	TLV withdrawn-insufficient data human occup. exp.

**Additional information:**

PEL = Permissible Exposure Limit (OSHA)  
TLV= Threshold Limit Value (ACGIH)  
OSHA= Occupational Safety and Health Administration  
ACGIH= American Conference of Governmental Industrial Hygienists

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

**Breathing equipment:**

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

(Contd. on page 5)

**Trade name: 2224-25 Soldering Flux**

Not necessary if room is well-ventilated.

(Contd. of page 4)

**Protection of hands:**



Protective gloves

**Material of gloves:**

Nitrile rubber, NBR

Natural rubber, NR

**Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Safety glasses



Face Shield with Safety Glasses when refilling.

**9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

**Form:** Liquid  
**Color:** Light yellow  
**Odor:** Mild

**pH-value at 20 °C (68 °F):** 2.5

**Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 82 °C (180 °F)

**Flash point:** 18 °C (64 °F)

**Ignition temperature:** 399 °C (750 °F)

**Auto igniting:** Product is not selfigniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**Explosion limits:**

**Lower:** 2.0 Vol %  
**Upper:** 12.0 Vol %

**Vapor pressure at 20 °C (68 °F):** 43 hPa (32 mm Hg)

**Density:** 1.40 g/cm<sup>3</sup>

**Solubility in / Miscibility with**

**Water at 20 °C (68 °F):** 100 %

**Solvent content:**

**Organic solvents:** 73.4 %  
**Water:** 6.1 %

(Contd. on page 6)

US



**SAFETY DATA SHEET (SDS)**  
According to 1907/2006/EC, Article 31

Version number 3

Reviewed on 11/24/2015

Trade name: 2224-25 Soldering Flux

(Contd. of page 5)

Solids content: 20.4 %

**10: STABILITY AND REACTIVITY**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability  
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Strong acids, strong oxidizers.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

**11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity:**  
Harmful if swallowed, in contact with skin or if inhaled.

**LD/LC50 values that are relevant for classification:**

**67-63-0 Isopropanol**

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

**Primary irritant effect:**

**on the skin:** Possible local irritation by contact with flux or fumes.

**on the eye:**  
Smoke during soldering can cause eye irritation.  
Causes serious eye damage.

**through inhalation:**  
Vapors during use may irritate mucous membranes and respiratory system. High concentrations can cause headache, dizziness, and nausea.

**through ingestion:** May cause gastrointestinal irritation.

**Sensitization:** Based on available data, the classification criteria are not met.

**Additional toxicological information:**

**Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

67-63-0	Isopropanol	3
---------	-------------	---

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12: ECOLOGICAL INFORMATION**

**12.1 Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Additional ecological information:**

**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

(Contd. on page 7)

**Trade name: 2224-25 Soldering Flux**

vPvB: Not applicable.

(Contd. of page 6)

**13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Recommendation:**

Disposal must be made according to official regulations.  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packagings:**

**Recommendation:** Disposal must be made according to official regulations.

**14: TRANSPORT INFORMATION**

**14.1 UN-Number**  
DOT, IMDG, IATA  
ADR

UN1219  
UN1219  
Not regulated

**14.2 UN proper shipping name**  
DOT  
ADR  
IMDG, IATA

Isopropanol  
1219 Isopropanol  
Not regulated  
ISOPROPANOL (ISOPROPYL ALCOHOL)

**14.3 Transport hazard class(es)**  
DOT



**Class**  
**Label**

3 Flammable liquids  
Not regulated.  
3

ADR, IMDG, IATA



**Class**  
**Label**

3 Flammable liquids  
3

**14.4 Packing group**

DOT, IMDG, IATA

II

**Marine pollutant:**

No

**14.6 Special precautions for user**

Not applicable.

**Danger code (Kemler):**

33

**EMS Number:**

F-E,S-D

**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 8)



**SAFETY DATA SHEET (SDS)**  
According to 1907/2006/EC, Article 31

Version number 3

Reviewed on 11/24/2015

Trade name: 2224-25 Soldering Flux

(Contd. of page 7)

**Transport/Additional information:**

**DOT**

**Quantity limitations**

On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

**ADR**

**Excepted quantities (EQ)**

Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

**IMDG**

**Limited quantities (LQ)  
Excepted quantities (EQ)**

1L  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

**UN "Model Regulation":**

UN 1219 ISOPROPANOL, 3, II

**15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA** The following information relates to product regulation specific to the USA.

**SARA (Superfund Amendments and Reauthorization Act)**

**Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

**Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):** Kester certifies that all components listed below for the subject finished product are on the TSCA Inventory of Chemical Substances and are not subject to any chemical specific regulation under TSCA Section 12(b) export notification requirements delineated at 40 CFR part 707, subpart D.

All ingredients are listed or exempt from listing.

**California Proposition 65**

**Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

**Carcinogenic categories**

**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**CANADA:**

Not classified.

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labeled according to the CLP regulation.

(Contd. on page 9)



Trade name: 2224-25 Soldering Flux

(Contd. of page 8)

### Hazard pictograms



GHS02 GHS05 GHS07

### Signal word Danger

#### Hazard-determining components of labeling:

Isopropanol

#### Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves / eye protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16: OTHER INFORMATION

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

**Department issuing Safety Data Sheet (SDS):** Product Compliance / EHS Department

**Contact:** EHS\_Kester@kester.com

**Date of preparation / last revision** 11/24/2015 / 2

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

(Contd. on page 10)



**SAFETY DATA SHEET (SDS)**  
According to 1907/2006/EC, Article 31

Version number 3

Reviewed on 11/24/2015

**Trade name: 2224-25 Soldering Flux**

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
**\* Data compared to the previous version altered.**

(Contd. of page 9)

us