

## Safety Data Sheet



Revision Number: 005.0

Issue date: 08/07/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>Tak Pak® 712 Accelerator Metered Mist</b>	<b>IDH number:</b>	229783
<b>Product type:</b>	Accelerator	<b>Item number:</b>	18636
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

## 2. HAZARDS IDENTIFICATION

## EMERGENCY OVERVIEW

**DANGER:** CONTENTS UNDER PRESSURE.  
EXTREMELY FLAMMABLE AEROSOL.  
CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.  
HARMFUL IF INHALED.  
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
ACUTE TOXICITY INHALATION	4
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

## PICTOGRAM(S)



## Precautionary Statements

## Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves.

## Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get

<b>Storage:</b>	medical attention. Take off contaminated clothing.
	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
2-Propanol	67-63-0	60 - 100
Butane	106-97-8	10 - 30
Propane	74-98-6	10 - 30
N,N-Dimethyl-p-toluidine	99-97-8	1 - 5

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention. Never give anything by mouth to an unconscious person.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	Aspiration may cause pulmonary edema or aspiration pneumonia.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.
<b>Unusual fire or explosion hazards:</b>	Contents under pressure. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Exposure to temperatures above 49°C (120°F) may cause container to burst. Do not puncture or incinerate pressurized containers.

**Hazardous combustion products:** Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Rinse spill area with water. Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Wear suitable protective clothing, gloves and eye/face protection. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not puncture or incinerate pressurized containers. Refer to Section 8.

**Storage:** For safe storage, store at or below 49 °C (120.2 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m <sup>3</sup> ) PEL	None	None
Butane	1,000 ppm STEL	None	None	None
Propane	Included in the regulation but with no data values. See regulation for further details	1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None
N,N-Dimethyl-p-toluidine	None	None	0.5 ppm TWA	None

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Aerosol
<b>Color:</b>	Clear, Colorless
<b>Odor:</b>	Alcoholic
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	33 mm hg (21 °C (69.8 °F))
<b>Boiling point/range:</b>	82 °C (179.6 °F)
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.79
<b>Vapor density:</b>	2.1
<b>Flash point:</b>	> -109 °C (> -164.2 °F) Open cup; (value for propellant).
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Evaporation rate:</b>	7.7 (Ether = 1)
<b>Solubility in water:</b>	Partially soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	99.9 %; 789 g/l EPA Method 24
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.
<b>Incompatible materials:</b>	Strong oxidizing agents. Strong acids and strong bases. Aluminum. Aldehydes.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F). Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

**Potential Health Effects/Symptoms**

<b>Inhalation:</b>	Harmful if inhaled. May cause dizziness, incoordination, headache, nausea, and vomiting.
<b>Skin contact:</b>	Causes skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation. Tearing. Redness.
<b>Ingestion:</b>	Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Propanol	Oral LD50 (RAT) = 5,045 mg/kg Oral LD50 (RABBIT) = 6,410 mg/kg Oral LD50 (RAT) = 4.7 g/kg Oral LD50 (RABBIT) = 8.0 g/kg Oral LD50 (RABBIT) = 5.03 g/kg Dermal LD50 (RABBIT) = 12,800 mg/kg	Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen
Butane	Inhalation LC50 (RAT, 4 h) = 658 mg/l	Cardiac, Central nervous system, Irritant
Propane	Inhalation LC50 (RAT, 15 min) = > 1,442.847 mg/l Inhalation LC50 (RAT, 15 min) = > 1,464 mg/l	Cardiac, Central nervous system, Irritant
N,N-Dimethyl-p-toluidine	None	Mutagen, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	No	No
Butane	No	No	No
Propane	No	No	No
N,N-Dimethyl-p-toluidine	No	No	No

**12. ECOLOGICAL INFORMATION**

**Ecological information:** Not available.

**13. DISPOSAL CONSIDERATIONS**

**Information provided is for unused product only.**

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

**14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

**U.S. Department of Transportation Ground (49 CFR)**

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None  
**Exceptions:** May Qualify as Consumer Commodity, (Not more than 500 ml), ID8000

**Water Transportation (IMO/IMDG)**

<b>Proper shipping name:</b>	AEROSOLS
<b>Hazard class or division:</b>	2.1
<b>Identification number:</b>	UN 1950
<b>Packing group:</b>	None
<b>Exceptions:</b>	Limited quantity (Not more than 1 L).

## 15. REGULATORY INFORMATION

**United States Regulatory Information**

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 311/312:</b>	Immediate Health, Delayed Health, Fire
<b>CERCLA/SARA Section 313:</b>	None above reporting de minimis
<b>CERCLA Reportable quantity:</b>	2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg) Butane (CAS# 106-97-8) 100 lbs. (45.4 kg) Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)
<b>California Proposition 65:</b>	No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information**

<b>CEPA DSL/NDL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Sheila Gines, Regulatory Affairs Specialist

**Issue date:** 08/07/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.