

SAFETY DATA SHEET PROW - ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

PROW - ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Product number MCC-PROW,MCC-PROWR,MCC-PROWY,MCC-PROWYR

Synonyms; trade names "PROW-ProClean Solvent Presaturated Wipes"; "PROWR-Stencil Wipes with ProClean

Presaturated Wipes/Refill"

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MicroCare Corporation

Manufacturer MICROCARE CORPORATION

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 860-827-0626 Fax: +1 860-827-8105 techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC (800) 424-9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2A - H319 Repr. 2 - H361 STOT SE 1 - H370 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

Physicochemical The product is highly flammable. Vapors may form explosive mixtures with air. Vapors are

heavier than air and may travel along the floor and accumulate in the bottom of containers.

Label elements

Pictogram







Signal word

Danger

Hazard statements H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapor/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

Safety data sheet available on request. For use in industrial installations only.

information

PROPAN-2-OL, ETHANOL, METHANOL

Other hazards

Contains

This substance is not classified as PBT or vPvB according to current EU criteria.

3. Composition/information on ingredients

Mixtures

PROPAN-2-OL	30-60%
CAS number: 67-63-0	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	

ETHANOL		30-60%

CAS number: 64-17-5

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H335

METHANOL 1-5%

CAS number: 67-56-1

Classification

Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

The Full Text for all Hazard Statements are Displayed in Section 16.

Composition comments The Data Shown is in accordance with the latest EC Directives.

4. First-aid measures

Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur. Do not

induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give

anything by mouth to an unconscious person. Consult a physician for specific advice.

Skin Contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause drowsiness and dizziness. Headache. Irritation of nose, throat and

airway.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur. Ingestion of

large amounts may cause unconsciousness. May cause nausea, headache, dizziness and

intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May

cause skin irritation/eczema.

Eye contact May cause temporary eye irritation. Irritating to eyes. Symptoms following overexposure may

include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor
No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Considering the size of the packaging, the risk is regarded as minimal. The product is highly

flammable. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof

containers with tight-fitting, self-closing lids.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapors. Oxides of carbon.

Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation.

Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the

ground. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Warn everybody of potential hazards and evacuate if necessary. If leakage cannot be

stopped, evacuate area. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain and absorb spillage with sand, earth or other non-combustible material.

Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards.

7. Handling and storage

Precautions for safe handling

Usage precautionsDo not eat, drink or smoke when using the product. Keep away from heat, sparks and open

flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable

level.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep

container tightly closed. Keep away from heat, sparks and open flame.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³ A4

ETHANOL

Long-term exposure limit (8-hour TWA): ACGIH

Short-term exposure limit (15-minute): ACGIH 1000 ppm

METHANOL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m³ Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m³ Sk

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 260 mg/m³

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

Sk = Danger of cutaneous absorption.

A4 = Not Classifiable as a Human Carcinogen.

Ingredient comments WEL = Workplace Exposure Limits

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Avoid heat, flames and other sources of ignition.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Not considered to be a significant hazard due to the small quantities used.

Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Revision date: 2/9/2016 Revision: 17 Supersedes date: 2/8/2016

PROW - ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Appearance Clear liquid.

Color Colorless.

Odor Alcoholic.

Odor threshold No information available.

pH No information available.

Initial boiling point and range 77.6°C @ 760 mm Hg

Flash point 12°C TCC (Tag closed cup).

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 2.0 Upper flammable/explosive limit: 12.7

Vapor pressure 39 mm Hg @ 20°C

Vapor density 1.82

Soluble in water.

Oxidising properties There are no chemical groups present in the product that are associated with oxidizing

properties.

Comments Information given is applicable to the major ingredient.

Volatility 100%

Flammability The product is flammable.

10. Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidizing agents. Strong alkalis. Strong mineral acids.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Fire creates: Vapors/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Inhalation May cause respiratory system irritation. Vapors may cause headache, fatigue, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Not considered to be a significant hazard due to the small quantities used.

Skin Contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes. Liquid, aerosols and vapors of this product are irritating and can cause pain,

tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that

of fine dust in the eyes.

Acute and chronic health

hazards

Keep out of the reach of children.

Toxicological information on ingredients.

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

5,800.0

Species

Rat

ATE oral (mg/kg)

5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 13,000.0

mg/kg)

Rabbit **Species**

13,000.0 ATE dermal (mg/kg)

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

16,000.0

Species

Rat

ATE inhalation (vapours

mg/l)

16,000.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

METHANOL

Acute toxicity - oral

Acute toxicity oral (LD₅o

7,300.0

mg/kg) **Species**

Mouse

ATE oral (mg/kg)

100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 15,800.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 300.0 Revision date: 2/9/2016 Revision: 17 Supersedes date: 2/8/2016

PROW - ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Acute toxicity - inhalation

Acute toxicity inhalation

64,000.0

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

ma/l)

3.0

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Toxicity

Ecological information on ingredients.

PROPAN-2-OL

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >2,000 mg/l, Algae

ETHANOL

Acute toxicity - fish LC₅₀, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 7,800 mg/l, Daphnia magna

METHANOL

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >10000 mg/l, Daphnia magna

Persistence and degradability

Persistence and degradability The product contains mainly inorganic substances which are not biodegradable. The other

substances in the product are expected to be readily biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility The product is soluble in water.

Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

13. Disposal considerations

Waste treatment methods

General information Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids

may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. Waste packaging should be collected for reuse or recycling. Reuse or

recycle products wherever possible.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (DOT) 3175 UN No. (TDG) 3175

UN No. (IMDG) 3175

UN No. (ICAO) 3175

UN proper shipping name

Proper shipping name (DOT) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)

Proper shipping name (TDG) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)

Proper shipping name

(IMDG)

SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ICAO) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.

Transport hazard class(es)

TDG class 4.1

TDG label 4.1

IMDG Class 4.1

ICAO class/division 4.1

Transport labels



Packing group

DOT pack group

TDG Packing Group II

IMDG packing group

ICAO packing group

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-A, S-I

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA (311/312) Hazard Categories

Fire

Acute

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

METHANOL

Known to the State of California to cause developmental and reproductive toxicity.

California Air Toxics "Hot Spots" (A-I)

PROPAN-2-OL

Present.

METHANOL

Present.

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

PROPAN-2-OL

Present.

Massachusetts "Right To Know" List

Not listed.

ETHANOL

Yes.

PROPAN-2-OL

Present.

METHANOL

Present.

Rhode Island "Right To Know" List

ETHANOL

Yes.

PROPAN-2-OL

Present.

METHANOL

Present.

Minnesota "Right To Know" List

ETHANOL

Yes.

PROPAN-2-OL

Present.

METHANOL

Present.

New Jersey "Right To Know" List

ETHANOL

Yes.

PROPAN-2-OL

Present.

METHANOL

Present.

Pennsylvania "Right To Know" List

ETHANOL

Yes.

PROPAN-2-OL

Present.

METHANOL

Present.

16. Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 2/9/2016

Revision 17

Supersedes date 2/8/2016

SDS No. PRESAT - PRO

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed. H311 Toxic in contact with skin. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs .

H373 May cause damage to organs through prolonged or repeated exposure.

NFPA - health hazard Irritation, minor residual injury. (1)

NFPA - flammability hazard Ignites easily. (3)

NFPA - instability hazard Unstable if heated. (1)

NFPA - special hazard N/A

ACA HMIS Health rating. Slight Hazard. (1)

ACA HMIS Flammability

rating.

Ignites easily. (3)

ACA HMIS Physical hazard

rating.

Unstable if heated. (1)

ACA HMIS Personal protection rating.

В

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.