

SAFETY DATA SHEET

1. Identification

Product identifier Di-Electric Grease

Other means of identification

Product code 02085

Recommended use Lubricates, protects and insulates electrical connections

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc. Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Do not puncture or incinerate container. Do not expose to heat or store at temperatures above

49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Observe good industrial hygiene

practices.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause

can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Polydimethylsiloxane		63148-62-9	70 - 80
Amorphous silica		7631-86-9	5 - 10

Material name: Di-Electric Grease sps us

1/8

Chemical name	Common name and synonyms	CAS number	%
Propylene glycol		57-55-6	5 - 10
Nitrogen		7727-37-9	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion If swallowed, do NOT induce vomiting. Get medical attention if symptoms occur.

Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

media

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water spray. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

General fire hazards

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Wipe up with absorbent material (e.g. cloth, fleece, vermiculite). Sweep up or vacuum up spillage and collect in suitable container for disposal. The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Material name: Di-Electric Grease

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed original container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components **Type** Value Amorphous silica (CAS TWA 0.8 mg/m3

7631-86-9)

20 mppcf

US. NIOSH: Pocket Guide to Chemical Hazards

Components Value Type

Amorphous silica (CAS **TWA** 6 mg/m3

7631-86-9)

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components Value **Form** Type Propvlene alvcol (CAS **TWA** 10 ma/m3 Aerosol.

57-55-6)

Biological limit values No biological exposure limits noted for the ingredient(s).

Occupational Exposure Limits are not relevant to the current physical form of the product. **Exposure guidelines**

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Gel. **Form** Color Off-white. Mild. Odor

Not available. Odor threshold Neutral.

-74.2 °F (-59 °C) estimated Melting point/freezing point Initial boiling point and boiling

600 °F (315.6 °C) estimated

range

> 500 °F (> 260 °C) Tag Closed Cup Flash point

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Material name: Di-Electric Grease

SDS US

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.6 % estimated

Flammability limit - upper

(%)

12.6 % estimated

Vapor pressure 55354.1 hPa estimated

Vapor density> 5 (air = 1)Relative density1.01 estimatedSolubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature

600 °F (315.6 °C) estimated

Decomposition temperatureNot available.Viscosity (kinematic)Not available.Percent volatileNot available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the decomposition temperature. Contact

with incompatible materials.

Incompatible materials

Hazardous decomposition

products

Product

irritation

Carbon oxides. Silicone oxides.

Strong oxidizing agents. Strong acids.

11. Toxicological information

Information on likely routes of exposure

InhalationViscous nature may block breathing passages if inhaled.Skin contactProlonged skin contact may cause temporary irritation.Eye contactDirect contact with eyes may cause temporary irritation.

Ingestion May cause gastrointestinal irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Di-Electric Grease		
<u>Acute</u>		
Dermal		
LD50	Rabbit	2632 mg/kg estimated
Oral		
LD50	Rat	12699 mg/kg estimated

Test Results

Species

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

^{*} Estimates for product may be based on additional component data not shown.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not expected to be an aspiration hazard.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

Di-Electric Grease

Aquatic

Fish LC50 Fish 18.8349 mg/l, 96 hours estimated

Components Species Test Results

Polydimethylsiloxane (CAS 63148-62-9)

Aquatic

Fish LC50 Channel catfish (Ictalurus punctatus) 2.36 - 4.15 mg/l, 96 hours

Propylene glycol (CAS 57-55-6)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Nitrogen 0.67 Propylene glycol -0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in

accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, non-flammable, Limited Quantity

Transport hazard class(es)

Class 2.2 Subsidiary risk -Label(s) 2.2

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Di-Electric Grease

02085 Version #: 01 Issue date: 06-02-2015

SDS US

^{*} Estimates for product may be based on additional component data not shown.

Not available. Special provisions

Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, non-flammable, Limited Quantity

Transport hazard class(es)

2.2 **Class** Subsidiary risk

Not applicable. Packing group

Environmental hazards No. **ERG Code** 2L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

IMDG

UN1950 **UN** number

UN proper shipping name AEROSOLS, LIMITED QUANTITY

Transport hazard class(es) Class 2

Subsidiary risk

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

Not available. **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

Material name: Di-Electric Grease

SDS US

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - No
Hazard categories Delayed Hazard - No
Fire Hazard - No
Processor Hazard Voc

Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Nο

Nitrogen (CAS 7727-37-9) Propylene glycol (CAS 57-55-6)

US. Massachusetts RTK - Substance List

Amorphous silica (CAS 7631-86-9)

Nitrogen (CAS 7727-37-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous silica (CAS 7631-86-9) Nitrogen (CAS 7727-37-9) Propylene glycol (CAS 57-55-6)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

0 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products

Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-02-2015	

Material name: Di-Electric Grease sps us 02085 Version #: 01 Issue date: 06-02-2015 7 / 8

Prepared by Allison Cho

Version # 01

CRC # 113 **Further information HMIS®** ratings Health: 0 Flammability: 1

Physical hazard: 0 Personal protection: B

Health: 0 **NFPA** ratings

Flammability: 1 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.