SAFETY DATA SHEET CH775_CH797_ I.P.A. SOLVENT

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name CH775_CH797_ I.P.A. SOLVENT

Product number 758CH775, 758CH797

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Manufacturer Techni-Tool, Inc.

1547 North Trooper Road Worcester, PA 19490-1117

610-941-2400 610-940-5485 www.techni-tool.com

Emergency telephone number

Emergency telephone CHEMTREC (800) 424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2A - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Physicochemical The product is highly flammable. Vapors may form explosive mixtures with air.

Label elements

Pictogram





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

CH775_CH797_ I.P.A. SOLVENT

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P240 Ground/ bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapor/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P302+P352 If on skin: Wash with plenty of water. P314 Get medical advice/ attention if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

Safety data sheet available on request. For use in industrial installations only.

Contains PROPAN-2-OL

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

PROPAN-2-OL 60-100%

CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage

(concentration) of composition has been withheld as a trade secret in accordance with

paragraph (i) of CFR 1900.1200

Composition

4. First-aid measures

Description of first aid measures

General information The product is flammable. CAUTION! First aid personnel must be aware of own risk during

rescue! Move affected person to fresh air at once. Place unconscious person on the side in the recovery position and ensure breathing can take place. Get medical attention if any

discomfort continues.

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

CH775_CH797_ I.P.A. SOLVENT

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Never give anything by mouth to an unconscious person. Consult a physician for specific

advice.

Skin Contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause drowsiness and dizziness. Headache. Irritation of nose, throat and

airway.

Ingestion Ingestion of large amounts may cause unconsciousness. May cause nausea, headache,

dizziness and intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May

cause skin irritation/eczema.

Eye contact May cause temporary eye irritation. Irritating to eyes. Symptoms following overexposure may

include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapors. Vapors are heavier than

air and may spread near ground and travel a considerable distance to a source of ignition and

flash back. Vapors are heavier than air and may spread near ground and travel a

considerable distance to a source of ignition and flash back.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapors. Oxides of carbon.

Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapors.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

CH775_CH797_ I.P.A. SOLVENT

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation.

Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the

ground. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Warn everybody of potential hazards and evacuate if necessary. If leakage cannot be

stopped, evacuate area. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate

ventilation. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards.

7. Handling and storage

Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and

eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Storage tanks and other containers must be grounded. Static electricity and formation of sparks must be prevented. Ground and bond

containers when transferring material.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container. Keep container dry. Ground container and transfer

equipment to eliminate sparks from static electricity. Do not store near heat sources or expose

to high temperatures.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Cleaning agent.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Additional Occupational

Exposure Limits

Ingredient comments WEL = Workplace Exposure Limits

CH775_CH797_ I.P.A. SOLVENT

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

> eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety

glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

> a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body

protection

Not considered to be a significant hazard due to the small quantities used. Wear apron or

protective clothing in case of contact.

Hygiene measures Do not smoke in work area. Wash hands at the end of each work shift and before eating,

smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

When using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Clear liquid. Color Colorless

Odor Characteristic. Alcoholic.

Odor threshold 22 ppm 6.5 - 7.2pН

Not relevant. Melting point

Initial boiling point and range 82 - 83°C/179 - 182°F @ 101.3 kPa

Flash point 12°C/54°F TCC (Tag closed cup).

Evaporation rate No information available. No information available. **Evaporation factor**

Flammability (solid, gas) No information available.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 12.0 Lower flammable/explosive limit: 2.0

Other flammability No information available.

41 hPa @ 20°C Vapor pressure

Vapor density 1.82

CH775_CH797_ I.P.A. SOLVENT

Relative density 0.785 g/cm3 @ 20°C

Bulk density No information available.

Solubility(ies) Completely soluble in water.

Partition coefficient Pow: 0.05

Auto-ignition temperature 399°C/750°F

Viscosity 2.43 mPa s @ 20°C

Refractive index No information available.

Particle size Not applicable.

Molecular weight No information available.

Volatility 100%

Saturation concentration No information available.

Critical temperature No information available.

Volatile organic compound This product contains a maximum VOC content of 785 g/litre.

10. Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidizing agents. Strong alkalis. Strong mineral acids.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Fire creates: Vapors/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Inhalation May cause respiratory system irritation. Vapors may cause headache, fatigue, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Substance may be harmful if swallowed. May cause nausea, headache, dizziness and

intoxication. May cause irritation. Symptoms following overexposure may include the

following: Stomach pain. Nausea, vomiting. Diarrhea.

Skin Contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes. Liquid, aerosols and vapors of this product are irritating and can cause pain,

tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that

of fine dust in the eyes.

CH775_CH797_ I.P.A. SOLVENT

Acute and chronic health

Keep out of the reach of children.

hazards

Toxicological information on ingredients.

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 5,800.0

mg/kg)

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 13,000.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 13,000.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 vapours mg/l)

16,000.0

Species Rat

ATE inhalation (vapours

mg/l)

16,000.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Toxicity

Ecological information on ingredients.

PROPAN-2-OL

Acute toxicity - fish LC50, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The product is readily biodegradable.

Bioaccumulative potential

CH775_CH797_ I.P.A. SOLVENT

Bio-Accumulative Potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Pow: 0.05

Mobility in soil

Mobility The product is soluble in water.

Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

13. Disposal considerations

Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority. Waste is suitable for incineration. When handling waste, the safety precautions applying to handling of the product

should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

General As supplied, this product is consigned under the Limited Quantities provisions.

49 CFR 173.150 (b)

UN Number

UN No. (TDG) LIMITED QUANTITY

UN No. (IMDG) UN1219

UN No. (ICAO) UN1219

UN No. (DOT) LIMITED QUANTITY

UN proper shipping name

Proper shipping name (TDG) ISOPROPANOL

Proper shipping name (IMDG) ISOPROPANOL

Proper shipping name (ICAO) ISOPROPANOL

Transport hazard class(es)

TDG class 3

IMDG Class 3

ICAO class/division 3

Transport labels



CH775_CH797_ I.P.A. SOLVENT

Packing group

TDG Packing Group II

IMDG packing group

ICAO packing group

DOT packing group

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-E, S-D

Transport in bulk according to Not relevant. No information required.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Acute Chronic Fire

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-I)

PROPAN-2-OL

Present.

CH775_CH797_ I.P.A. SOLVENT

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

PROPAN-2-OL

Present.

Massachusetts "Right To Know" List

PROPAN-2-OL

Present.

Rhode Island "Right To Know" List

PROPAN-2-OL

Present.

Minnesota "Right To Know" List

PROPAN-2-OL

Present.

New Jersey "Right To Know" List

PROPAN-2-OL

Present.

Pennsylvania "Right To Know" List

PROPAN-2-OL

Present.

Inventories

Canada - DSL/NDSL

Yes

US - TSCA

All the ingredients are listed.

16. Other information

NFPA - health hazard

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 8/5/2016

Revision 14

Supersedes date 7/18/2016

SDS No. BULK - CH775_CH797_ IPA

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Irritation, minor residual injury. (1)

NFPA - flammability hazard Ignites easily. (3)

CH775_CH797_ I.P.A. SOLVENT

NFPA - instability hazard Normally stable. (0)

NFPA - special hazard N/A

ACA HMIS Health rating. Slight Hazard. (1)

ACA HMIS Flammability

rating.

Ignites easily. (3)

ACA HMIS Physical hazard

rating.

Normally stable. (0)

ACA HMIS Personal protection rating.

Α

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.