# Material Safety Data Sheet One Step (No Clean)

# 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING. Page 1 of 4

1.1	Identification of subs	tance (as per label):	One Step Desoldering Braid.
	Other means of Ident	ification:	
1.2	Company Name:	Easy Braid Co.	Part Numbers: OS-A-5, OS-A-5AS, OS-A-10, OS-A-10AS, OS-A-25,
	Contact Name:	Jim Strempke	OS-A-50, OS-A-100, OS-A-500, OS-B-5, OS-B-5AS, OS-B-10, OS-B-
	Full Address:	11543 K-tel Drive	10AS, OS-B-25, OS-B-50, OS-B-100, OS-B-500, OS-C-5, OS-C-5AS,
		Minneapolis, MN 55343 USA	OS-C-10, OS-C-10AS, OS-C-25, OS-C-50, OS-C-100, OS-C-500, OS-
	Telephone Number:	952-929-3040	D-5, OS-D-5AS, OS-D-10, OS-D-10AS, OS-D-25, OS-D-50, OS-D-100,
	Fax Number:	952-929-2765	OS-D-100AS, OS-D-500, OS-E-5, OS-E-5AS, OS-E-10, OS-E-10AS,
	Emergency Number:		OS-E-25, OS-E-50, OS-E-100, OS-E-100AS, OS-E-500

#### 2. COMPOSITION / IDENTIFICATION ON INGREDIENTS

CAS NUMBER	INGREDIENTS	%	SYMBOLS	RISK PHASE
7440-50-8	Pure Copper Metal	99.9		
8050-09-7	Modified Rosin	0.1		

2.1	Substances presenting a health hazard:	The 0.1% Rosin may caus	se allergic reactions: does not contain hazardous
		ingredients.	
2.2	Exposure Limit Values:	Copper -	ACGIH
			TLV
2.3	Is substance is confidential - indicate chemical nature to ensure	-fume	0.1 mg/m3
	safe handling	-dust	1.0mg/m3

#### 3. HAZARDS IDENTIFICATION

3.1	Critical Hazards:	HMIS Hazard Rating:	0 = insignificant
3.1	Critical Hazards.	Third Hazard Rating.	S
			1 = slight
			2 = moderate
			3 = high
			4 = extreme
3.2	Critical Hazards to Man & Environment:	Health = 1	
		Flammability = 0	
		Reactivity $= 0$	
	Adverse Human Health Effects and Symptoms:	Rosin flux may cause an	allergic reaction, resulting in a skin rash. Clean
		hands after use.	

### 4. FIRST AID MEASURE

4. FIK	ST AID MEASURE	
4.1	Skin Contact:	Flush skin with copious amounts of water.
	-First Aid:	
	-Symptoms:	Rash.
	-Effects:	
	-Delayed Effects:	
	-Medical Attention Needed:	
	Eye Contact:	Remove metal fragments and flush eyes with water.
	-First Aid:	
	-Symptoms:	
	-Effects:	
	-Delayed Effects:	
	-Professional Attention Needed:	
	Inhalation:	
	-First Aid:	Remove to fresh air. If breathing has stopped, administer CPR.
	-Symptoms:	
	-Effects:	
	-Delayed Effects:	
	-Professional Attention Needed:	
	Ingestion:	
	-First Aid:	Induce vomiting.
	-Symptoms:	
	-Effects:	
	-Delayed Effects:	Wire strands could cause internal digestive tract bleeding.
	-Professional Attention Needed:	Induce vomiting.

 $<sup>\</sup>hbox{\Large \ifmmode {\Bbb C}\ensuremath{\Bbb C}\ensuremath$ 

## 5. FIRE FIGHTING MEASURES

5.1	Suitable Extinguishing Media:	Powder Dolomite, Sodium Chloride or Graphite.
5.2	Unsuitable Extinguishing Media:	Do not use water.
5.3	Exposure Hazards:	Copper reacts violently with C2H2, NH4N03, Bromates, Chlorates,
		Iodates, C12, C1F2, Ethylene Oxide, F2, H2O2, Hydrazine monoitrate,
		Hydrazoic acid, H2S, K202, NaN3, Na202, CUN03, S.
5.4	Combustion Products: -Resulting Gases:	Carbon Monoxide, Aliphatic Aldehydes, and Acids
5.5	Protective Equipment For Firefighters:	Not Needed

#### 6. ACCIDENTAL RELEASE MEASURES

6.1	Personal Precautions:	
	-Ignition sources?	When subjected to temperatures over 180° F, flux fumes should be vented.
	-Provision for sufficient ventilation?	See Section 8.1.
	-Control of dust?	Vacuum or sweep up and dispose of as a non-cumbustable metal.
	-Prevention of skin contact?	Gloves not normally required. When clipping short lengths, protective
	-Prevention of eye contact?	eyewear is recommended.
6.2	Environmental Precautions:	
6.3	Methods for Cleaning Up:	Vacuum or sweep up and dispose of as a noncombustible solid.
6.4	Materials not to be Used for Cleaning Up:	See above. See section 5, of this document.

## 7. HANDLING & STORAGE

7.1	Handling	
	-General Rules	Store in cool, dry environment for functional purposes.
	-Technical Precautions for Safe Handling	None required.
	-Measures necessary to prevent airborne levels of chemical	If product is exposed to temperatures are above 180° F, use local
	being generated as a result of handling.	ventilation.
7.2	Recommended Storage Conditions	
	-List incompatible materials	
	-Quantity Limits for storage	See sections 5 & 2 of this document.
	-Special Requirements for proper	
	storage of chemical	

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1	System Design	General mechanical or local hood. Ventilation is recommended for
	(e.g. Fume Hoods, Ventilated	applications where the product will exceed 180° F.
	Cabinets, Enclosure)	
8.2	Control Parameters	
	-Limit values or biological standards:	
8.3	Recommended Monitoring Procedures:	See Section 5, of this document.
8.4	Personal Protection	Use local or general ventilation away from the operator if the product
	-Respiratory Protection:	temperature is exposed to 180° F+.
	-Hand Protection:	Gloves may be used if resin is a skin irritant.
	-Eye Protection:	Eye protection should be worn when clipping short lengths.
	-Skin Protection:	See hand protection.
8.5	CEN standards	Carcinogens < 0.1%

## 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1	Appearance:	Copper metallic braid with fine crystalline resin layer.
9.2	Odor:	None.
9.3	pH:	N/A
9.4	Boiling Point:	1981 degrees F
9.5	Melting Point:	1949 degrees F
9.6	Flash Point:	No flash
9.7	Flammability (solid gas):	None
9.8	Autoflammability:	None
9.9	Explosive Properties:	None
9.10	Oxidizing Properties:	Copper can oxidize if prolonged exposure in moist conditions.
9.11	Vapor Pressure:	N/A
9.12	Relative Density:	N/A
9.13	Solubility:	
	-Water Solubility	Negligible
	-Fat Solubility	Unknown
9.14	Partition coefficient, n-octanol/water:	
9.15	Other Data:	
	-Safety Parameters	N/A
	-Vapor Density	N/A
	-Miscibility	N/A
	-Evaporation rate	N/A
	-Conductivity	Copper is very conductive.
	-Viscosity	A solid

#### 10. STABILITY AND REACTIVITY

101 0111	V. STADIETT AND REACTIVITY			
10.1	Stability	Stable		
10.2	Conditions to avoid			
	-Effects			
10.3	Materials to Avoid			
	-Effects			
10.4	Hazardous Decomposition products			
	-the need for and the presence of			
	stabilizers:	Hazardous environment can occur in the presence of excessive heat		
	-hazardous exothermic reaction:	and/or chemicals as listed in Section 5, this document.		
	-change in appearance in the substance:			
	-hazardous products formed upon			
	contact with water:			
	-possible degradation to unstable			
	products:			

## 11. TOXICOLOGICAL INFORMATION

11.1	Skin Exposure:	
	-Symptoms:	Possible allergic rash reaction. See Section 4, this document.
	-Immediate Effects:	
	-Delayed Effects:	
	-Chronic Effects:	
	-Special Health Effects:	
11.2	Eye Contact:	
	-Symptoms:	Possible danger of metal fragments. See Section 4, this document.
	-Immediate Effects:	
	-Delayed Effects:	
	-Chronic Effects:	
	-Special Health Effects:	
11.3	Inhalation:	
	-Symptoms:	
	-Immediate Effects:	If product is exposed to temperatures in excess of 180° F, local
	-Delayed Effects:	ventilation must be used.
	-Chronic Effects:	
	-Special Health Effects:	
11.4	Ingestion:	
	-Symptoms:	
	-Immediate Effects:	May be moderately irritating to stomach lining. Induce vomiting if
	-Delayed Effects:	conscious.
	-Chronic Effects:	
	-Special Health Effects:	

 $<sup>\</sup>bigodot$  1998, EASY BRAID CO., PROD-4014, Revision D, 31 July 2000

Page 4 of 4

12. ECOLOGICAL INFORMATION			
	12.1	Mobility -distribution to environmental compartments -surface tension -absorption / desorption -physical & chemical properties	Not applicable.
	12.2	Degradability -biotic and abiotic degradation -acrobic and anaerobic degradation -persistence	Not applicable.
	12.3	Accumulation -bioaccumulation potential -biomagnification	Not applicable.
	12.4	Short and Long Term Effects on:  -Ecotoxity  -aquatic organisms -soil organisms -plants and terrestrial animals  -Other Adverse Effects -ozone depletion potential -photochemical ozone creation potential  -effects on waste water treatment plants	Not applicable.
13. DISPOSAL CONSIDERATIONS			
	13.1	Safe Handling	Consult with local regulatory bodies to metallic solid waste disposal
	13.2	Methods of Disposal	
14. TRANSPORT INFORMATION			
Ť	14.1	UN Number:	Harmonized Tariff Code:
			#7413.00.1000
	14.2	Road & Sea Freight Classification:	Copper wire coated with resin flux
	14.3	Substance Classification Number:	
	14.4	Class:	Malidada I ilaana # / Camara I ilaana arankala
	14.5 14.6	Packing Group: Proper Shipping Name:	Validated license # / General license symbol: "NLR"
	14.0	PGR (if applicable)	
	14.7	ADR/RID CLASSIFICATION: Class: Item Number:	
	14.8	ICAO/IATA CLASSIFICATION: Class: Sub-Risk: Packing Group: Proper Shipping Name:	
15 DECHI ATODY INFORMATION			
15. REGULATORY INFORMATION  15.1 Precautionary Label Information:  This product does not require warning labels due to Hazard			This product does not require warning labels due to Hazards
	15.1 15.2	Symbols:	Classification as designated in Section 3.
	15.2	Symbols: Risk Phrases:	Risk Phrases: R36/37/38
	15.3	Risk Phrases: Safety Phrases:	Safety Phrases: S14 (per section 5), S22/39, S43 (per section 5)
		,	12, 2
16. OTHER INFORMATION  16.1 Regulatory Information:			
	10.1	Regulatory Illiorniation.	

<sup>© 1998,</sup> EASY BRAID CO., PROD-4014, Revision D, 31 July 2000