

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH INDIUM 10.1 FLUX

SDS Number: SDS-5795 Revised Date: 7 MARCH 2016

Product Use: Industrial Use (mixture) - solder paste consisting of a flux vehicle blended with 88-89 weight

percent pre-alloyed metal powder.

MANUFACTURER:

In America:

The Indium Corporation of America **CHEMTREC 24 hrs.** 1676 Lincoln Ave., Utica NY 13502 USA: 1 (800) 424-9300

Information: (315) 853-4900

nswarts@indium.com

In Europe:

Indium Corporation of Europe

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Carcinogen listed in

⊕Skin NTP **IARC OSHA** ⊕Eve ⊕Inhalation ⊕Ingestion ⊕Not Listed

GHS:







for lead containing products

Signal Word: Warning Hazard statement(s)

H303 May be harmful if swallowed (lead) H317 May cause an allergic skin reaction H319 Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled H334

H351 Suspected of causing cancer (lead)

H361 Suspected of damaging fertility or the unborn child (applicable to lead containing product)

H373 May cause damage to organs through prolonged or repeated exposure (applicable to lead containing

product)

H410 Very toxic to aquatic life with long lasting effects (lead containing product)

EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 +P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + P351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures

over 100°C may cause serious eye irritation.

Ingestion: This product contains metal alloy powders and organic chemicals. May be harmful if swallowed.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local

irritation to the respiratory system. May be harmful if inhaled. Inhalation of rosin fume may cause

occupational asthma.

Skin Contact: May cause skin irritation. Rosin may cause dermatitis and skin sensitization.

Chronic: SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition

known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

<u>COPPER:</u> Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory

irritation and systematic lead poisoning.

This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system.

Keep out of the reach of children.

WARNING:

Warning: State of California Only: This product contains a chemical known to the State of California to

cause cancer and/or birth defects (or other reproductive harm). (lead)

Safe Drinking Water Standard – California Prop 65.

Note: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

. COMPOSITION / INFORMATION ON INGREDIENTS						
Components	% wt	CAS Registry #/ EINECS#	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³	
TIN	*	7440-31-5/231-141-8				
		(US)	2	2	-	
		(EU)	-	2	4	
		(Canada)	-	2	4	
		(Singapore)	2	-	<u>-</u>	
SILVER	*	7440-22-4/231-131-3				
		(US)	0.01	0.1	-	
		(EU)	-	0.1	-	
		(Canada)	-	0.1	0.3	
		(Mexico)	-	0.1	-	
		(Singapore)	0.1	-	<u>-</u>	
COPPER	*	7440-50-8/231-159-6				
		(US)	0.1 (fume)	0.2 (fume)	-	
		(EU)	-	0.2 (fume)	-	
		(Canada)	-	0.2 (fume)	0.6 (fume)	
		(Mexico)	-	0.2(fume)	2	

SDS - 5795		INDALLOY WITH INDIUM 10.1					
		(Singapore)	0.2	-	-		
		(China)	-	1(dust)	2.5		
				0.2(fume)	0.6		
LEAD	*	7439-92-1/231-100-4 (US)	0.05	0.05	_		
			0.03				
		(EU)	-	0.15	-		
		(Canada)	0.05	0.05	-		
		(Singapore)	0.15	-	-		
		(Mexico)	N.E.	0.15	-		
		(China)	-	0.05(dust) 0.03(fume)	<u>.</u>		
ANTIMONY	*	7440-36-0/231-146-5					
		(US)	0.5	0.5	-		
		(EU)	0.5	-	-		
		(Canada)	-	0.5	1.5		
		(Mexico)	N.E.	0.5	-		
		(Singapore)	0.5	-	-		
		(China)	-	0.5	-		
ROSIN	5.0 - 6.0	65997-05-9	N.E.	N.E.	N.E.		
		(EU)	0.05	N.E.	0.15 (sensitiser)		
POLYGLYCOL ETHER	3.0 – 5.0	9038-95-3	N.E.	N.E.	N.E.		
PROPRIETARY ACTIVATORS	1.0 – 3.0	-	N.E.	N.E.	N.E <u>.</u>		
N.E. = Not established							
"* See Alloy table							
•							

SDS - 5795

ALLOY TABLE 88-89% metal load

INDALLOY	%TIN	%SILVER	%COPPER	%ANTIMONY	%LEAD	RoHS 2
Metal Mix	Sn	Ag	Cu	Sb	Pb	Compliance
121	85-85.9	3.08-3.1				Yes
(96.5Sn/3.5Ag)	00-00.9	3.00-3.1	-	-	-	162
133	83.6-84.6	-	-	0.44-0.445	-	Yes
95Sn/5Sb						
233	4.4-4.45	-	-	8.8-8.9	74.8-75.7	Yes*
(85Pb/10Sb/5Sn)						
241	84-85	3.3-3.4	0.62-0.623	-	-	Yes
(SAC387)						
95.5Sn/3.8Ag/0.7Cu)						
256	85-85.9	2.6-2.67	0.44-0.445	-	-	Yes
(SAC305)						
96.5Sn/3Ag/0.5Cu)						
268	86.7-87.7	0.44-0.445	0.88-0.89	-	-	Yes
(SACM0510)						
(98.5Sn/0.5Ag/1Cu/0.05Mn)						

RoHS 2 = (2011/65/EU) * Complies with high melting lead exemption

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly

cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste

Regulations.

7. HANDLING AND STORAGE

HandlingKeep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate

production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are

washed.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with production equipment (such as stencil printers and re-flow furnaces) with

adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that any permissible

exposure limits are not exceeded.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or

exceed exposure limits.

Skin: Compatible chemical resistant gloves. Latex gloves not recommended.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good

paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area. When working

with lead containing products use standard lead work procedures.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Grey colored paste.Boiling Point:Not applicable.Odor:Mild characteristic odor.Melting Point:Not applicableSpecific Gravity:1 g/cc (flux)pH:4-8 (flux)

Vapor Pressure: Not applicable. Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Harmful organic fumes and toxic oxide fumes may form at elevated

Combustion: temperatures.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

LD50: Not established. **LC50:** Not established.

Other: Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational

asthma.

Product not tested.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation.

Non - hazardous under shipping requirements. (USDOT/IATA/IMDG)

UN - none

North American Emergency Guide Book - Not Classified

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS:

D2B - Materials Causing Other Toxic Effects - irritation/sensitization

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2000 and NOM-010-STPS-2014.

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2002.

California PROP 65 (Safe Drinking Water Standard):

This product contains a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm. (trace levels of lead)

SARA 313 Listing - 40 CFR 372.65 Silver Copper Lead Antimony

All ingredients are listed on the EPA TSCA Inventory.

Most of the ingredients are listed on the Canadian Domestic Substance List.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

16. OTHER INFORMATION

HMIS Hazard Rating:

Health:

1

Fire: 1

Reactivity: 0

Revised Date: 7 MARCH 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Note: This MSDS may be translated into an international language. If there is any misinterpretation or misunderstanding of any words or phrases that may occur within any translation the <u>ENGLISH</u> language shall always prevail.