

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

Some of the regulatory information contained within may not be applicable to the customer's individual state or country. Unless otherwise stated the health and safety information provided within is applicable to all products.

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH INDIUM 6.4R FLUX VEHICLE

SDS Number: SDS-6006SC Revised Date: 7 MARCH 2016

Product Use: Industrial use - solder paste consisting of a flux vehicle blended with an 70-90% pre-

alloyed metal powder. Review product metal alloy table mixtures with the same flux.

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900

nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou), Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

CARCINOGEN LISTED IN:

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP IARC OSHA ⊕Not Listed

See Section 11

GHS:







Signal Word: Warning Hazard statement(s)

H303 May be harmful if swallowed (lead)
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 Suspected of causing cancer (lead containing product)

H361 Suspected of damaging fertility or the unborn child (applicable to lead containing product)

H373 May cause damage to organs through prolonged or repeated exposure (applicable to lead containing

product)

H410 Very toxic to aquatic life with long lasting harmful effects (lead)

EUH201A Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell.

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Eye Irritant (Category 2)

Acute toxicity, Oral (Category 4) (lead)
Carcinogenicity (Category 2) (lead)
Reproductive toxicity (Category 2) (lead)
Acute aquatic toxicity (Category 1) (lead)
Chronic aquatic toxicity (Category 1) (lead)

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures

over 100°C may cause eye irritation.

Ingestion: This product contains alloy powder and organic chemicals. May be harmful if swallowed.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local

irritation to the respiratory system.

Skin Contact: May cause skin irritation or dermatitis.

Chronic: LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory

irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and

kidneys.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

COPPER: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

INDIUM: May cause damage to respiratory system if inhaled over long exposure.

WARNING: This product contains a chemical (s) known to the State of California to cause cancer and/or

birth defects (or other reproductive harm). (lead) Applicable in the State of California.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits

the use of leaded solders in making joints and fittings in any private or public water supply

system. Keep out of the reach of children.

3. COMPOSITION / INFO	ORMA ⁻	TION ON INGREDIENTS	3			
Components	% wt	% wt CAS Registry #/EINECS#		TLV-TWA mg/m³	TLV-STEL mg/m³	
TIN	*	7440-31-5/231-141-8				
		(US)	2	2	-	
		(EU)	-	2	4	
		(Canada)	-	2	4	
		(Singapore)	2	-	-	
LEAD	*	7439-92-1/231-100-4				
		(US)	0.05	0.05	-	
		(EU)	-	0.15	-	
		(Canada)	0.05	0.05	-	
		(Singapore)	0.15	-	-	

SDS - 6006SC				INDALLOY V	VITH INDIUM 6.4R		
		(Mexico)	0.15	-	-		
		(China)	-	0.05(dust)	-		
				0.03(fume)	-		
SILVER	*	7440-22-4/231-131-3					
5-2-1		(US)	0.01	0.1	-		
		(EU)	-	0.1	-		
		(Canada)	-	0.1	0.3		
		(Mexico)	-	0.1	-		
		(Singapore)	0.1	-	-		
COPPER	*	7440-50-8/231-159-6					
		(US)	0.1	0.2	-		
		(EU)	-	0.2 (fume)	2(dust)		
		(Canada)	-	0.2	0.6		
		(Singapore)	0.2(fume)	1(dust)	-		
		(Mexico)	0.2	-	2		
		(China)	-	0.2(fume)	0.6(fume)		
BISMUTH	*	7440-69-9/231-177-4	N.E.	N.E.	N.E.		
INDIUM	*	7440-74-6/231-180-0					
		(US)	0.1	0.1	-		
		(EU)	-	0.1	0.3		
		(Canada)	-	0.1	0.3		
		(Singapore)	0.1	-	-		
		(Mexico)	-	0.1	0.3		
		(China)	-	0.1	0.3		
ROSIN AMINES	1.5 -4.5	61790-47-4/263-139-8	N.E.	N.E.	N.E.		
		(EU)	0.05	N.E.	0.15 (sensitiser)		
		(- /			, ,		
PROPRIETARY	6.50 – 12.5	<u>-</u>	N.E.	N.E.	N.E.		
OTHER NON-HAZARDOUS INGREDIENTS							
N.E. = Not established * See Alloy Table.							
		-					

ALLOY TABLE

% Metal mix with flux

			70 11101	ai iiiix witii iia			
INDALLOY (METAL MIX)	%TIN Sn	%SILVER Ag	%LEAD Pb	%COPPER Cu	%BISMUTH Bi	%INDIUM In	^RoHS 2 Compliance
19 (51ln/32.5Bi/16.5Sn)	11.6-14.9	-	-	-	22.8-29.3	35.7-46	Yes
100 (62.6Sn/37Pb/0.4Ag)	43.8-56	0.28-0.36	25.9-33	-	-	-	No
104 (62Sn/36Pb/2Ag)	43-56	1.4-1.8	25-32	-	-	-	No
106 (63Sn/37Pb)	44-56.7	-	25.9-33	-	-	-	No
109 (60Sn/40Pb)	42-54	-	28-36	-	-	-	No
256 (SAC305) (96.5Sn/3Ag/0.5Cu)	67.6-86.9	2.1-2.7	-	0.35-0.45	-	-	Yes
Sn 992 (99.2Sn/0.5Cu/0.3Bi/ 0.05Co)	69-89	-	-	0.35-0.45	0.21-0.27	-	Yes

RoHS 2- (2011/65/EU)

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly

cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste

Regulations.

7. HANDLING AND STORAGE

HandlingKeep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate

production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are

washed.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with adequate ventilation and other safety features specifically designed for use

with solder paste. Control concentration of all components so that the permissible

exposure levels are not exceeded. Use exhaust ventilation.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or

exceed exposure limits.

Skin: Compatible chemical resistant gloves. Latex gloves not recommended for chemical handling.

Other: Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Goo

paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area. When working

with lead containing products follow standard lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Grey colored paste. **Boiling Point:** Not applicable. Appearance: Odor: Mild characteristic odor. **Melting Point:** Not applicable **Specific Gravity:** Not applicable. pH: Not applicable **Vapor Pressure:** Not applicable. Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Harmful organic fumes and toxic oxide fumes may form at elevated

Combustion: temperatures.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

LD50: Not established. **LC50:** Not established.

Other: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the rules for hazard assessment of wastes.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated (US Department of Transportation).

Non - hazardous under shipping regulations (UN regulations).

Non-hazardous under IATA.

UN - none

Marine pollutant: No

North American Emergency Guide Book - Not applicable

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic).



D2B Materials Causing Other Toxic Effects - irritant

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-2014.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

California PROP 65: WARNING:

This product contains a chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (lead)

SARA 313 Listing - 40 CFR 372.65 Lead CAS# 7439-92-1

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

All ingredients are listed on the Canadian Domestic Substance List.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 1 Reactivity: 0

Revised Date: 7 MARCH 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health,

safety and other necessary information is included on the container. The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.