



**INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®  
INDIUM CORPORATION (SUZHOU)®  
SAFETY DATA SHEET**

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** INDALLOY WITH FLUXCAKE-201 (CW-201)

**SDS Number:** SDS-CW 4541

**Revised Date:** 9 APRIL 2015

**Product Use:** Industrial Use - Flux cored wire (soldering applications). Review alloy table for metal mixtures with the same core flux.

#### MANUFACTURER:

##### In America:

The Indium Corporation of America  
34 Robinson Rd., Clinton NY 13323  
Information: (315) 853-4900  
nswarts@indium.com

##### EMERGENCY PHONE:

**CHEMTREC 24 hrs.**  
**USA: 1 (800) 424-9300**  
**Outside USA: +1 (703) 527-3887**

Indium Corporation of America  
Chicago Materials Division  
80 Scott Street  
Elk Grove Village, Illinois 60007

##### In Europe:

Indium Corporation of Europe  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

##### In China:

Indium Corporation (Suzhou), Co., Ltd.  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

##### In Asia:

Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

**2. HAZARDS IDENTIFICATION**

**PRIMARY ROUTES OF ENTRY:**

⊕Eye    ⊕Inhalation    ⊕Skin    ⊕Ingestion    NTP

**Carcinogen listed in**

IARC    OSHA    ⊕Not Listed  
 \*\*\*See Section 11

**GHS:**



for products containing lead

Signal Word: Warning

**Hazard statement(s)**

- H303      May be harmful if swallowed (lead)
- H317      May cause an allergic skin reaction
- H334      May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H351      Suspected of causing cancer (lead)
- H361      Suspected of damaging fertility or the unborn child (applicable to lead containing product)
- H373      May cause damage to organs through prolonged or repeated exposure (applicable to lead containing product)
- H410      Very toxic to aquatic life with long lasting effects (lead containing product)
- EUH201A    Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.
- EUH208      Contains rosin. May produce an allergic reaction

**Precautionary statement(s)**

- P233      Keep container tightly closed
- P261      Avoid breathing dust/fume/gas/mist/vapours/spray
- P270      Do not eat, drink or smoke when using this product
- P273      Avoid release to the environment
- P280      Wear protective gloves/protective clothing/eye protection/face protection
- P362      Take off contaminated clothing and wash before reuse
- P301 + P314    IF SWALLOWED: Get Medical advice/attention if you feel unwell
- P302 +P352    IF ON SKIN: Wash with plenty of soap and water
- P304 + 341    IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + 351    IF IN EYES: Rinse continuously with water for several minutes (15mins)

**POTENTIAL HEALTH EFFECTS:**

- Eye Contact:**    Irritating to the eyes and if not removed, may result in serious injury. Contact with fume from molten metal may cause irritation.
- Ingestion:**      This product contains metal and organic chemicals. May be harmful if swallowed.
- Inhalation:**     Inhalation of fume or dust may cause local irritation to the respiratory system. Rosin may cause occupational asthma.
- Skin Contact:**    May cause skin irritation. Rosin may cause dermatitis.
- Chronic:**         SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition

known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Prolonged inhalation of fume may result in lung complications.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning.

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (lead)

**WARNING:** This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Components    | % wt | CAS Registry #/EINECS# | PEL<br>mg/m <sup>3</sup> | TLV-TWA<br>mg/m <sup>3</sup> | TLV-STEL<br>mg/m <sup>3</sup> |
|---------------|------|------------------------|--------------------------|------------------------------|-------------------------------|
| <b>TIN</b>    | *    | 7440-31-5/231-141-8    |                          |                              |                               |
|               |      | (US)                   | 2                        | 2                            | -                             |
|               |      | (EU)                   | -                        | 2                            | 4                             |
|               |      | (Canada)               | -                        | 2                            | 4                             |
|               |      | (Singapore)            | 2                        | -                            | -                             |
| <b>SILVER</b> | *    | 7440-22-4/231-131-3    |                          |                              |                               |
|               |      | (US)                   | 0.01                     | 0.1                          | -                             |
|               |      | (EU)                   | -                        | 0.1                          | -                             |
|               |      | (Canada)               | -                        | 0.1                          | 0.3                           |
|               |      | (Singapore)            | 0.1                      | -                            | -                             |
| (Mexico)      | -    | 0.1                    | -                        |                              |                               |
| <b>COPPER</b> | *    | 7440-50-8/231-159-6    |                          |                              |                               |
|               |      | (US)                   | 0.1 (fume)               | 0.2 (fume)                   | -                             |
|               |      | (EU)                   | -                        | 0.2 (fume)                   | -                             |
|               |      | (Canada)               | -                        | 0.2 (fume)                   | 0.6 (fume)                    |
|               |      | (Singapore)            | 0.2(fume)                | -                            | -                             |
| (Mexico)      | -    | 0.2(fume)              | 2                        |                              |                               |

|                        |         |                     |  |      |                          |                  |
|------------------------|---------|---------------------|--|------|--------------------------|------------------|
|                        |         |                     | (China)  | -    | 0.2(fume)                | 0.6              |
| <b>LEAD</b>            | *       | 7439-92-1/231-100-4 |  |      |                          |                  |
|                        |         |                     | (US)   | 0.05 | 0.05                     | -                |
|                        |         |                     | (EU)   | -    | 0.15                     | -                |
|                        |         |                     | (Canada)   | 0.05 | 0.05                     | -                |
|                        |         |                     | (Singapore)  | 0.15 | -                        | -                |
|                        |         |                     | (Mexico)   | N.E. | 0.15                     | -                |
|                        |         |                     | (China)  | -    | 0.05(dust)<br>0.03(fume) | -                |
| <b>BISMUTH</b>         | *       | 7440-69-9           |  | N.E. | N.E.                     | N.E.             |
| <b>ANTIMONY</b>        | *       | 7440-36-0/231-146-5 |  |      |                          |                  |
|                        |         |                     | (US)   | 0.5  | 0.5                      | -                |
|                        |         |                     | (EU)   | 0.5  | -                        | -                |
|                        |         |                     | (Canada)   | -    | 0.5                      | 1.5              |
|                        |         |                     | (Mexico)   | -    | 0.5                      | -                |
|                        |         |                     | (Singapore)  | 0.5  | -                        | -                |
|                        |         |                     | (China)  | -    | 0.5                      | -                |
| <b>ROSIN MIX</b>       | 1.0-6.0 | 65997-05-9 (US)     |  | N.E. | N.E.                     | N.E.             |
|                        |         |                     | (EU)   | 0.05 | N.E.                     | 0.15(sensitiser) |
| Symbol: X              |         |                     | Risk Phrases: R20/21/22, R36/37/38,R42/43 (see section 15) |      |                          |                  |
| N.E. = Not established |         |                     |  |      |                          |                  |
| * See alloy table      |         |                     |  |      |                          |                  |

#### 4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

**Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

## 5. FIRE FIGHTING MEASURES

**Flash Point:** Not established. **Method:** Not established.

**Auto-ignition Temperature:** Not established.

**Flammable Limits:** Limits not established.

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.

**Special Fire Fighting Procedures:** Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

**Spill or Leak Procedures:** Pick up solids and put in container for reuse or recycling. Do not sweep powder or small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations. If applicable follow standard lead work practices.

## 7. HANDLING AND STORAGE

**Handling** Keep containers tightly closed when not in use. Use care to avoid spills. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

**Storage Precautions:** Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Local exhaust ventilation is recommended to keep exposures below established limits and protect operators. Use proper ventilation when working with leaded products.

### Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield was splash hazards.

**Respirator:** An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.

**Skin:** Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed for melting applications.

**Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas. Follow standard lead work practices when working with lead containing products.

**Work/Hygienic** Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow applicable lead work practices.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                          |                         |                             |                 |
|--------------------------|-------------------------|-----------------------------|-----------------|
| <b>Appearance:</b>       | Solid metal             | <b>Boiling Point:</b>       | Not applicable. |
| <b>Odor:</b>             | Odorless                | <b>Melting Point:</b>       | See table       |
| <b>Specific Gravity:</b> | See table               | <b>pH:</b>                  | Not applicable  |
| <b>Vapor Pressure:</b>   | Not established         | <b>Solubility in Water:</b> | Insoluble       |
| <b>Vapor Density:</b>    | (air=1) Not applicable. |                             |                 |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>General:</b>                              | Stable.  |
| <b>Conditions to Avoid:</b>                  | Not established.   |
| <b>Incompatible Materials:</b>               | Avoid contact with acids, bases or oxidizing agents.                           |
| <b>Hazardous Decomposition / Combustion:</b> | Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. |
| <b>Hazardous Polymerization:</b>             | Will not occur.  |

## 11. TOXICOLOGICAL INFORMATION

|                         |                  |   |                  |
|-------------------------|------------------|---|------------------|
| <b>Carcinogenicity:</b> | <b>NTP:</b> No   |   |                  |
|                         | <b>OSHA:</b> No  |   |                  |
|                         | <b>IARC:</b> Yes | Lead and lead compounds are listed as possible carcinogens. |                  |
| <b>LD50:</b>            | Not established. | <b>LC50:</b>  | Not established. |

Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead can cause potential harm to the developing fetus.

## 12. ECOLOGICAL INFORMATION

Avoid the entrance of metals into the environment, especially lead.  
Product not tested.

## 13. DISPOSAL CONSIDERATION

**Waste Disposal Method:** Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation). Not hazardous under shipping regulations.

UN- None

Not regulated – IATA.

## 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead)

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65  
Silver Copper Lead Antimony

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1

California Prop 65 Safe Drinking Water Standard: Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (listed metals)

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X

### Risk Phrases:

- |           |  |
|-----------|--|
| R20/22    | Harmful by inhalation and if swallowed (lead)  |
| R36/37/38 | Irritating to eyes, respiratory system and skin  |
| R33       | Danger of cumulative effects (lead)  |
| R40       | Limited evidence of carcinogenic effect (lead)   |
| R48       | Danger of serious damage to health by prolonged exposure (lead)  |
| R50/53    | Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment (lead) |
| R61       | May cause harm to the unborn child (lead)  |

### Safety Phrases:

- |        |                                       |
|--------|---------------------------------------|
| S20/21 | When using do not eat, drink or smoke |
| S23    | Do not breathe fumes                  |

|           |  |
|-----------|--|
| S24/25    | Avoid contact with skin and eyes   |
| S28       | After contact with skin wash immediately with plenty of soap and water                           |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection                                |
| S62       | If swallowed, do not induce vomiting seek medical advice immediately and show container or label |
| S7        | Keep container tightly closed  |

## 16. OTHER INFORMATION

**HMIS Hazard Rating:**

|                    |   |
|--------------------|---|
| <b>Health:</b>     | 2 |
| <b>Fire:</b>       | 1 |
| <b>Reactivity:</b> | 0 |

**Revised Date:** 9 APRIL 2015

**Prepared by:** Nancy Swarts, Indium Corporation of America

**Approved by:** Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.



**ALLOY TABLE****Metal Alloy Mix with Flux Core (1-6%)**

| <b>INDALLOY</b>                             | <b>Lead<br/>Pb</b> | <b>Tin<br/>Sn</b> | <b>Copper<br/>Cu</b> | <b>Bismuth<br/>Bi</b> | <b>Silver<br/>Ag</b> | <b>Antimony<br/>Sb</b> | <b>Specific<br/>Gravity</b> | <b>RoHS 2<br/>Compliance</b> |
|---|--------------------|-------------------|----------------------|-----------------------|----------------------|------------------------|-----------------------------|------------------------------|
| 97<br>(43Sn/43Pb/14Bi)                      | 40.4-42.6          | 40.4-42.6         | -                    | 13.2-13.9             | -                    | -                      | 9.02                        | No**                         |
| 106<br>(Sn63/Pb37)                          | 34.8-36.6          | 59-62.4           | -                    |                       | -                    | -                      | 8.40                        | No**                         |
| 109<br>(Sn60/40Pb)                          | 37.6-39.6          | 56.4-59.4         | -                    |                       | -                    | -                      | 8.50                        | No**                         |
| 121<br>(96.5Sn/3.5Ag)                       | -                  | 90.7-95.5         | -                    | -                     | 3.3-3.47             | -                      | 7.50                        | Yes                          |
| 133<br>(95Sn/5Sb)                           | -                  | 89.3-94           | -                    | -                     | -                    | 4.7-4.95               | 7.25                        | Yes                          |
| 241(SAC387)<br>(95.5Sn/3.8Ag/0.7Cu)         | -                  | 89.7-94.5         | 0.66-0.69            |                       | 3.57-3.76            | -                      | 7.40                        | Yes                          |
| 256(SAC 305)<br>(96.5Sn/3Ag/0.5Cu)          | -                  | 90.7-95.5         | 0.47-0.495           |                       | 2.82-2.97            | -                      | 7.40                        | Yes                          |
| Non Standard Mix<br>(Pb62<br>Sn25/Bi10/Ag3) | 58.3 - 61.4        | 23.5 – 24.8       | -                    | 9.4-9.9               | 2.8-2.97             | -                      | 9.80                        | No                           |

RoHS = Restriction of Hazardous Substances \*\*Review any exemptions that may apply. (2011/65/EU)