



**INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®
INDIUM CORPORATION (SUZHOU)®
SAFETY DATA SHEET**

This safety data sheet represents a family grouping of all metal mixes that are blended with the same fluxcake to make a flux cored wire for soldering applications. A table is provided that lists all metal groupings. Please review for the product that is being used.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH FLUXCAKE-807 (CW-807)

SDS Number: SDS-CW 4832

Revised Date: 6 FEBRUARY 2015

Product Use: Industrial Use - Flux cored wire for soldering applications. (See alloy table for metal alloy mix)
Flux varies between 1-5%.

MANUFACTURER:

In America:

The Indium Corporation of America
1676 Lincoln Ave., Utica NY 13502
Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

Indium Corporation of America
Chicago Materials Division
80 Scott Street
Elk Grove Village, Illinois 60007

In Europe:

Indium Corporation of Europe
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou), Co., Ltd.
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP

Carcinogen listed in

IARC OSHA ⊕Not Listed

GHS



for products containing lead

Signal Word: Warning

Hazard statement(s)

- H303 May be harmful if swallowed (lead)
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H351 Suspected of causing cancer (lead)
- H361 Suspected of damaging fertility or the unborn child (lead containing product)
- H373 May cause damage to organs through prolonged or repeated exposure (applicable to lead containing product)
- H410 Very toxic to aquatic life with long lasting harmful effects (lead containing product)
- EUH201A Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.
- EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

- P233 Keep container tightly closed
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P362 Take off contaminated clothing and wash before reuse
- P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
- P302 +P352 IF ON SKIN: Wash with plenty of soap and water
- P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)
- P501 Dispose of contents by recycling or thru an approved chemical waste hauler.

Classification:

- Carcinogenicity (Category 2) (lead)
- Reproductive toxicity (Category 2) (lead)
- Acute aquatic toxicity – Category 1 for lead containing products
- Chronic aquatic toxicity – Category 1 for lead containing products
- For product containing both lead and antimony the Acute and Chronic Classification is (Category 2)

POTENTIAL HEALTH EFFECTS:

- Eye Contact:** Irritating to the eyes and if not removed, may result in serious injury. Contact with fume from molten metal may cause irritation.

- Ingestion:** This product contains metal and organic chemicals. May cause irritation or harm.

- Inhalation:** Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of lead fume may be harmful. Rosin may cause occupational asthma.

- Skin Contact:** May cause skin irritation. Rosin may cause dermatitis or sensitization. Antimony may cause irritation.

- Chronic:**
 - SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

 - TIN: Prolonged inhalation of fume may result in lung complications.

 - COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

 - LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning.

 - INDIUM: May cause damage to respiratory or kidney system. May be harmful if inhaled.

- NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

- WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (lead).

- WARNING:** This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS#	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-

SILVER	*	7440-22-4/231-131-3	(US)	0.01	0.1	-
			(EU)	-	0.1	-
			(Canada)	-	0.1	0.3
			(Singapore)	0.1	-	-
			(Mexico)	-	0.1	-
COPPER	*	7440-50-8/231-159-6	(US)	0.1 (fume)	0.2 (fume)	-
			(EU)	-	0.2 (fume)	-
			(Canada)	-	0.2 (fume)	0.6 (fume)
			(Singapore)	0.2(fume)	-	-
			(Mexico)	-	0.2(fume)	2
			(China)	-	0.2(fume)	0.6
LEAD	*	7439-92-1/231-100-4	(US)	0.05	0.05	-
			(EU)	-	0.15	-
			(Canada)	0.05	0.05	-
			(Singapore)	0.15	-	-
			(Mexico)	N.E.	0.15	-
			(China)	-	0.05(dust) 0.03(fume)	-
ANTIMONY	*	7440-36-0/231-146-5	(US)	0.5	0.5	-
			(EU)	0.5	-	-
			(Canada)	N.E.	0.5	1.5
			(Singapore)	0.5	-	-
			(Mexico)	0.5	-	-
			(China)	-	0.5	-

INDIUM	*	7440-74-6/231-180-0			
		(US)	0.1	0.1	-
		(EU)	-	0.1	0.3
		(Canada)	-	0.1	0.3
		(Singapore)	0.1	-	-
		(Mexico)	-	0.1	0.3
		(China)	-	0.1	0.3
MANGANESE	doped	7439-96-5	N.E.	N.E.	N.E.
ROSIN MIX	1 - 5.0	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
Symbol: Xn N.E. = Not established * See alloy table			Risk Phrases: R20/22, R36/37/38, R42/43 See Section 15.		
PRODUCT DOES NOT CONTAIN ANY EU LISTED SUBSTANCES OF VERY HIGH CONCERN (SVHC)					

ALLOY TABLE**Metal alloy mixed with rosin (1-5%)**

INDALLOY	Lead Pb	Tin Sn	Copper Cu	Silver Ag	Antimony Sb	Indium In	Specific Gravity (metal mix)	RoHS Compliance
106 (Sn63/Pb37)	34.2-36.7	60- 62.4	-	-	-	-	8.40	No
109 (Sn60/Pb40)	38 - 39.6	57 - 59.4	--	-	-	-	8.50	No
121 (96.5Sn/3.5Ag)	-	91.7 -95.5	-	3.3 - 3.47	-	-	7.50	Yes
132 (95Sn/5Ag)	-	90 - 94	-	4.75 - 4.95	-	-	7.39	Yes
133 (95Sn/5Sb)	-	90-94	-	-	4.75-4.95	-	7.25	Yes
165 (97.5Pb/1.5Ag/1Sn)	92.6 - 96.5	0.95 - 0.99	-	1.43 - 1.48	-	-	11.28	Yes*
171 (95Pb/5Sn)	90-94	4.75-4.95	-	-	-	-	11.04	Yes*
227 (77.2Sn/20In/2.8Ag)	-	73-77.4	-	2.66-2.77	-	19-19.8	7.25	Yes
228 (88Pb/10Sn/2Ag)	83.6 – 87	9.5 - 9.9	-	1.9 - 1.98	-	-	10.75	Yes*
241 (SAC387) (95.5Sn/3.8Ag/0.7)	-	79-87.9	0.58-0.64	3.15-3.5	-	-	7.40	Yes
256 (SAC 305) (96.5Sn/3Ag/0.5Cu)	-	91.6 - 95.5	0.475-0.495	2.85 - 2.97	-	-	7.40	Yes
268 (SACM0510) (98.5Sn/0.5Ag/1Cu) Doped 0.05Mn	-	93.6-97.5	0.95-.099	0.475-0.495	-	-	7.32	Yes
Sn995 (Co995) (99.5Sn/0.5Cu/<500 ppm Co)	-	94.5 - 98.5	0.475-0.495	-	-	-	7.29	Yes
Non standard (Sn50/Pb48.5/Cu1.5)	46 – 48	47.5 - 49.5	1.43 - 1.48	-	-	-	8.84	No
Non standard (93.5Pb/5Sn/1.5Ag)	88.8 - 92.6	4.75 - 4.95	-	1.43 - 1.49	-	-	11.03	Yes*

* Review applicable exemptions that may apply, otherwise not compliant.

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point:	Not established.	Method:	Not established.
Auto-ignition Temperature:	Not established.		
Flammable Limits:	Limits not established.		
Extinguishing Media:	Use extinguishers appropriate for the surrounding fire conditions.		
Special Fire Fighting Procedures:	Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.		

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:	Pick up solids and put in container for reuse or recycling. Do not sweep powder or small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations.
----------------------------------	--

7. HANDLING AND STORAGE

Handling	Keep containers tightly closed when not in use. Use care to avoid spills. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.
Storage Precautions:	Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Exhaust ventilation is recommended to keep exposures below established limits and protect operators. Use proper ventilation when working with leaded products.
Personal protection:	
Eyes:	Chemical safety glasses/goggles. Face shield for splash hazards.
Respirator:	An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.
Skin:	Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed for melting applications.
Other:	Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas. Follow standard lead work practices when working with lead containing products.
Work/Hygienic	Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow applicable lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Solid metal - wire	Boiling Point:	Not applicable.
Odor:	Odorless	Melting Point:	See table
Specific Gravity:	See table	pH:	Not applicable
Vapor Pressure:	Not established	Solubility in Water:	Insoluble
Vapor Density:	(air=1) Not applicable.		

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition / Combustion:	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No		
	OSHA: 1910.1025 (lead)		
	IARC: Yes	Lead and lead compounds are listed as possible carcinogens.	
LD50:	Not established.	LC50:	Not established.

Chronic Toxicity: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Protect not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method:	Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.
-------------------------------	---

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Not hazardous under shipping regulations. UN – none

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead)
D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65
Silver Copper Lead

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1

California Prop 65 Safe Drinking Water Standard: Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (LEAD)

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X

Risk Phrases:

- R20/22 Harmful by inhalation and if swallowed (lead)
- R36/37/38 Irritating to eyes, respiratory system and skin
- R42/43 May cause sensitization by inhalation and skin contact
- R33 Danger of cumulative effects (lead)
- R40 Limited evidence of carcinogenic effect. (lead)
- R48 Danger of serious damage to health by prolonged exposure (lead)
- R50/53 Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment (lead)
- R61 May cause harm to the unborn child (lead)

Safety Phrases:

- S20/21 When using do not eat, drink or smoke
- S23 Do not breathe fumes
- S24/25 Avoid contact with skin and eyes
- S28 After contact with skin wash immediately with plenty of soap and water
- S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S62	If swallowed, do not induce vomiting seek medical advice immediately and show container or label
S7	Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating:

Health:	2
Fire:	1
Reactivity:	0

Revised Date: 6 FEBRUARY 2015

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.