

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ® SAFETY DATA SHEET

This safety data sheet represents a family grouping of all metal mixes that are blended with the same fluxcake to make a flux cored wire for soldering applications. A table is provided that lists all metal groupings. Please review for the product that is being used.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH FLUXCAKE-807 (CW-807)

SDS Number: SDS-CW 4832

Revised Date: 6 FEBRUARY 2015

Product Use:Industrial Use - Flux cored wire for soldering applications. (See alloy table for metal alloy mix)
Flux varies between 1-5%.

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900 nswarts@indium.com EMERGENCY PHONE: CHEMTREC 24 hrs. USA: 1 (800) 424-9300 Outside USA: +1 (703) 527-3887

Indium Corporation of America Chicago Materials Division 80 Scott Street Elk Grove Village, Illinois 60007

In Europe:

Indium Corporation of Europe 7 Newmarket Ct. Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore 29 Kian Teck Avenue Singapore 628908 Information: +65 6268-8678

In China:

Indium Corporation (Suzhou), Co., Ltd. No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square Unit No. 14-C Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS		ION					
		ITRY:			Carcino	gen listed	in
⊕Eye	⊕Inhalation ⊕Skin ⊕Ingestion NTP IARC OSHA ⊕Not Listed						
₩Eye		USKIII	Ungestion		IANC	USHA	
GHS							
	•						
				Sty.			
					for products	containing l	ead
	•			•		oontaining i	
Signal Word: W	arning						
Hazard stateme	ent(s)						
H303	May be harmf						
H317	May cause an						
H319	Causes seriou			امیر مدام	: ff :	holod	
H334			ma symptoms or	breathing d	ifficulties if ir	naled	
H351	Suspected of			ro obild (loo	deentoining	n reduct)	
H361	Suspected of damaging fertility or the unborn child (lead containing product)						
H373	May cause damage to organs through prolonged or repeated exposure (applicable to lead containing product)						
H410	. ,	iquatic life w	ith long lasting ha	armful effect	ts (lead cont	aining produ	uct)
EUH201A			pplicable only to				
EUH208			ice an allergic rea				, terter nemigi
Precautionary			j				
P233	Keep containe	er tightly clos	sed				
P261			e/gas/mist/vapors/	/spray			
P270			e when using this				
P273	Avoid release	to the envir	onment	-			
P280	Wear protectiv	/e gloves/pr	otective clothing/e	eye protection	on/face prote	ection	
P362	Wear protective gloves/protective clothing/eye protection/face protection Take off contaminated clothing and wash before reuse						
P301 + P314	•						
P302 +P352	+P352 IF ON SKIN: Wash with plenty of soap and water						
P304 + 341	341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable						
	for breathing						
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)						
P501	Dispose of co	ntents by re	cycling or thru an	approved c	hemical was	ste hauler.	
Classification:							
	(Category 2) (lea						
	xicity (Category 2	, , ,					
	xicity - Category						
	toxicity - Catego						
For product con	taining both lead	and antimor	ny the Acute and (Unronic Cla	ssification is	(Category 2	<u>2)</u>

POTENTIAL HEA	LTH EFFECTS:
Eye Contact:	Irritating to the eyes and if not removed, may result in serious injury. Contact with fume from molten metal may cause irritation.
Ingestion:	This product contains metal and organic chemicals. May cause irritation or harm.
Inhalation:	Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of lead fume may be harmful. Rosin may cause occupational asthma.
Skin Contact:	May cause skin irritation. Rosin may cause dermatitis or sensitization. Antimony may cause irritation.
Chronic:	SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.
	TIN: Prolonged inhalation of fume may result in lung complications.
	<u>COPPER:</u> Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.
	<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning.
	INDIUM: May cause damage to respiratory or kidney system. May be harmful if inhaled.
NOTE:	The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.
WARNING:	This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (lead).
WARNING:	This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

omponents	% wt	CAS Registry #/EINECS#	PEL mg/m³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
N	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-

					· · · · · ·	
SILVER	*	7440-22-4/231-131-3				
SILVER		(US)	0.01	0.1	-	
		(EU)	-	0.1	-	
		(Canada)	-	0.1	0.3	
		(Singapore)	0.1	-	-	
		(Mexico)	-	0.1	-	
COPPER	*	7440-50-8/231-159-6				
		(US)	0.1 (fume)	0.2 (fume)	-	
		(EU)	-	0.2 (fume)	-	
		(Canada)	-	0.2 (fume)	0.6 (fume)	
		(Singapore)	0.2(fume)	-	-	
		(Mexico)	-	0.2(fume)	2	
		(China)	-	0.2(fume)	0.6	
LEAD	*	7439-92-1/231-100-4				
		(US)	0.05	0.05	-	
		(EU)	-	0.15	-	
		(Canada)	0.05	0.05	-	
		(Singapore)	0.15	-	-	
		(Mexico)	N.E.	0.15	-	
		(China)	-	0.05(dust) 0.03(fume)	-	
ANTIMONY	*	7440-36-0/231-146-5				
		(US)	0.5	0.5	_	
		(EU)	0.5	-	-	
		(Canada)	N.E.	0.5	1.5	
		(Singapore)	0.5	-	-	
		(Mexico)	0.5	-	-	
		(China)	-	0.5	-	
		()				

SDS – CW 4832			INDAL	LOY WITH FLUXCAKE	-807 (CW-807)
INDIUM	*	7440-74-6/231-180-0			
		(US)	0.1	0.1	-
		(EU)	-	0.1	0.3
		(Canada)	-	0.1	0.3
		(Singapore)	0.1	-	-
		(Mexico)	-	0.1	0.3
		(China)	-	0.1	0.3
MANGANESE	doped	7439-96-5	N.E.	N.E.	N.E.
ROSIN MIX	1 - 5.0	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
Symbol: Xn N.E. = Not established * See alloy table	Risk P	hrases: R20/22, R36/37	/38, R42/43	See Section 15.	

PRODUCT DOES NOT CONTAIN ANY EU LISTED SUBSTANCES OF VERY HIGH CONCERN (SVHC)

ALLOY TABLE

Metal alloy mixed with rosin (1-5%)	Metal allow	/ mixed with	rosin	(1-5%)
-------------------------------------	-------------	--------------	-------	--------

INDALLOY	Lead Pb	Tin Sn	Copper Cu	Silver Ag	Antimony Sb	Indium In	Specific Gravity (metal mix)	RoHS Compliance
106 (Sn63/Pb37)	34.2-36.7	60- 62.4	-	-	-	-	8.40	No
109 (Sn60/Pb40)	38 - 39.6	57 - 59.4		-	-	-	8.50	No
121 (96.5Sn/3.5Ag)	-	91.7 -95.5	-	3.3 - 3.47	-	-	7.50	Yes
132 (95Sn/5Ag)	-	90 - 94	-	4.75 - 4.95	-	-	7.39	Yes
133 (95Sn/5Sb)	-	90-94	-	-	4.75-4.95	-	7.25	Yes
165 (97.5Pb/1.5Ag/1Sn)	92.6 - 96.5	0.95 - 0.99	-	1.43 - 1.48	-	-	11.28	Yes*
171 (95Pb/5Sn)	90-94	4.75-4.95	-	-	-	-	11.04	Yes*
227 77.2Sn/20In/2.8Ag)	-	73-77.4	-	2.66-2.77	-	19-19.8	7.25	Yes
228 (88Pb/10Sn/2Ag)	83.6 - 87	9.5 - 9.9	-	1.9 - 1.98	-	-	10.75	Yes*
241 (SAC387) (95.5Sn/3.8Ag/0.7)	-	79-87.9	0.58-0.64	3.15-3.5	-	-	7.40	Yes
256 (SAC 305) (96.5Sn/3Ag/0.5Cu)	-	91.6 - 95.5	0.475-0.495	2.85 - 2.97	-	-	7.40	Yes
268 (SACM0510) (98.5Sn/0.5Ag/1Cu) Doped 0.05Mn	-	93.6-97.5	0.95099	0.475-0.495	-	-	7.32	Yes
Sn995 (Co995) (99.5Sn/0.5Cu/<500 ppm Co)	-	94.5 - 98.5	0.475-0.495	-	-	-	7.29	Yes
Non standard (Sn50/Pb48.5/Cu1.5)	46 - 48	47.5 - 49.5	1.43 - 1.48	-	-	-	8.84	No
Non standard (93.5Pb/5Sn/1.5Ag)	88.8 - 92.6	4.75 - 4.95	-	1.43 - 1.49	-	-	11.03	Yes*

* Review applicable exemptions that may apply, otherwise not compliant.

4. FIRST AID M	IEASURES
Eye Contact:	Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
Ingestion:	If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
Skin Contact:	Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point:	Not establis	shed. Method:	Not established.				
Auto-ignition To	emperature:	Not established.					
Flammable Limits:		Limits not established.					
Extinguishing Media:		Use extinguishers	appropriate for the surrounding fire conditions.				
Special Fire Fighting Procedures:		Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.					

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Pick up solids and put in container for reuse or recycling. Do not sweep powder or small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling

Keep containers tightly closed when not in use. Use care to avoid spills. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

Storage Precautions: Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION					
Engineering Controls:		Exhaust ventilation is recommended to keep exposures below established limits and protect operators. Use proper ventilation when working with leaded products.			
Personal protection:					
Eyes:	Chemical	safety glasses/goggles. Face shield for splash hazards.			
Respirator:	An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.				
Skin:	Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed for melting applications.				
Other:		eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas. Indard lead work practices when working with lead containing products.			
Work/Hygienic	Avoid eat	good housekeeping. Clean up spills immediately. Good personal hygiene is essential. ting, smoking or drinking in the work area. Wash hands thoroughly with soap and water ely upon leaving the work area. Follow applicable lead work practices.			

SDS – CW 4832		INDALLOY	WITH FLUXCAKE-807 (CW-807)
9. PHYSICAL A	ND CHEMICAL PROPER	RTIES	
Appearance:	Solid metal - wire	Boiling Point:	Not applicable.
Odor:	Odorless	Melting Point:	See table
Specific Gravity:	See table	pH:	Not applicable
Vapor Pressure:	Not established	Solubility in Water:	Insoluble
Vapor Density:	(air=1) Not applicable.		

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition / Combustion:	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No OSHA: 1910.102	NTP: No OSHA: 1910.1025 (lead)		
	IARC: Yes	Lead and lead compounds are listed as possible carcinogens.		
LD50:	Not established.	LC50:	Not established.	

Chronic Toxicity: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Protect not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation.

Not hazardous under shipping regulations. UN - none

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead) D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65 Silver Copper Lead

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

California Prop 65 Safe Drinking Water Standard: Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (LEAD)

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

Х

Risk Phrases:

Max I maa	
R20/22	Harmful by inhalation and if swallowed (lead)
R36/37/38	Irritating to eyes, respiratory system and skin
R42/43	May cause sensitization by inhalation and skin contact
R33	Danger of cumulative effects (lead)
R40	Limited evidence of carcinogenic effect. (lead)
R48	Danger of serious damage to health by prolonged exposure (lead)
R50/53	Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment (lead)
R61	May cause harm to the unborn child (lead)
Safety Phra	ases:
S20/21	When using do not eat, drink or smoke
S23	Do not breathe fumes
S24/25	Avoid contact with skin and eyes
S28	After contact with skin wash immediately with plenty of soap and water
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection

SDS – CW 4832	INDALLOY WITH FLUXCAKE-807 (CW-807)
S62	If swallowed, do not induce vomiting seek medical advice immediately and show container or label
S7	Keep container tightly closed

2	
1	
0	
6 FEBRUARY 2015	
Nancy Swarts, Indium Corporation of America	
Nancy Swarts, Indium Corporation of America	
1	

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.