



### SQWF09 Qualatrile SENS! White Nitrile 9" Powder-Free Gloves

### **ESD Technical Bulletin**



## Electrostatic Decay in Combination with a Person

Standard: Rate of decay shall be less than 2.0 sec-

onds @12%RH

+1kV to -100V Ave: 0.229 sec. -1kV to

-100V Ave: 0.806 sec.

Method: Mil-STD-3010C, 4046 (Modified)

@49.5%RH

# Café Glove Resistance in Combination with a Person

Target: Less than 1.0 x 10<sup>11</sup> ohms @ 12%RH

and 50%RH

Range: Min: 1.5 x 108 ohms

Max: 1.0 x 109 ohms

Method: ANSI/ESD SP15.1 @49.5%RH for 48

Hours

### **ESD Inside Shelf Life**

Requirement: 5 Years

Found: Indefinite for Storage

Reference: Contains no Antistats

#### **Surface Resistance**

Target: 1.0 x 10<sup>11</sup> ohms and greater at 12%RH

Range: Min: 1.6 x 10<sup>10</sup> ohms Max: 3.8 x 10<sup>11</sup> ohms

Method: ANSI/ESD STM11.11-2015 @

10.1%RH for 48 Hours

#### **Volume Resistance**

Standard: Less than 1.0 x 10<sup>11</sup> ohms @12%RH

Range: Min: 3.5 x 10° ohms

Max: 5.8 x 108 ohms

Method: ANSI/ESD STM11.12-2015 @ 49.5%RH

for 48 Hours

Product Recommendations: The information presented herein is not guaranteed in any way, although to the best of QRP's knowledge and belief, it is true and accurate as of this date. Because the manner and conditions of use, handling, storage and other factors may involve a variety of safety, performance, or regulatory considerations unknown to QRP, users are responsible for determining the suitability of any QRP product for their specific purpose. QRP, Inc. does not warrant the results to be obtained in using any QRP product, and disclaims all liability with respect to the use, handling or further processing of any such product.

rev: 28Sept2016

