

# 92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

## The world's leading disposable glove for chemical splash protection

- Proprietary Ansell material formulation offers enhanced chemical splash protection
- Soft nitrile provides high levels of comfort
- Robust design for superior durability
- Silicone free design is paint and finish process friendly
- Also available in packaging to fit vending machines

TOUCHNTUFF 92 600 F png

### Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical

### Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling

TouchNTuff 92-600 Glove Box

[WWW.ANSELL.COM](http://WWW.ANSELL.COM)

# 92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

## Technical Data Sheet

### Product Information

92-600

<b>Material</b>	Nitrile
<b>Color</b>	Green
<b>Glove Design</b>	Powder-Free, Chlorinated, Silicone Free, Smooth

<b>Cuff</b>	Beaded
<b>Manufacturing/QMS Audit Standards</b>	ISO 9001
<b>Regulatory/Standards Compliance</b>	Category III, EAC TP TC 019:2011, EN 374:2003, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600
<b>Packaging</b>	Bulk Pack: 100 gloves per dispenser; 10 dispensers/1000 gloves per case Vending Pack: 20 gloves per dispenser; 24 dispensers/480 gloves per case
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia, Sri Lanka, Thailand
<b>User Needs Segment</b>	Robust
<b>Available sizes</b>	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
<b>Anti-static</b>	Yes

## Physical Properties

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	4.0 AQL (North & South America) / 1.5 AQL (Europe, Middle East, Africa, Asia, Pacific)		ASTM D5151, EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.16 / 6.2		ASTM D3767, EN 420
	<b>Before Aging</b>	<b>After Aging</b>	
Ultimate Tensile Strength (MPa) $\geq$ 18	$\geq$ 18	$\geq$ 18	ASTM D412 & D573
Elongation at Break (%) $\geq$ 500	$\geq$ 500	$\geq$ 400	ASTM D412
Force at break (N) $\geq$ 6	$\geq$ 6	$\geq$ 6	EN 455-2

## ORDERING INFORMATION

**Size** S (6.5 - 7) M (7.5 - 8) L (8.5 - 9) XL (9.5 - 10)

**Product Code** 585834 585835 585836 585837

**Vending Pack Catalog №** 9260000S 9260000M 9260000L 9260000XL

## Technology

□

**For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at**

### Europe, Middle East & Africa Region

- Ansell Healthcare Europe NV
- T: +32 (0) 2 528 74 00
- F: +32 (0) 2 528 74 01

### Asia Pacific Region

- Ansell Global Trading Center  
(Malaysia) Sdn Bhd
- T: +603 8310 6688
- F: +603 8310 6699

#### **North America Region**

- Ansell Healthcare Products LLC
- T: +1 800 800 0444
- F: +1 800 800 0445

#### **Latin America & Caribbean Region**

- Ansell Commercial Mexico S.A. de C.V.
- T: +52 442 248 1544 / 248 3133

#### **Australia**

- Ansell Limited
- T: +61 1800 337 041
- F: +61 1800 803 578

#### **Russia**

- Ansell PYC
- Ten. +7 495 258 13 16

### **Performance Standards and Regulatory Compliance**

EN374\_LowChemicalResistance

EN 374 Microorganism

J K P T

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2021 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

□