



Acryl-Red Putty

05098 • 05966

Technical Data Sheet

February, 2012

3M Part No.(s)	3M Part Descriptor(s)
05098; 05966	3M™ Acryl-Red Putty

Product Description 3M™ Acryl-Red Putty is a single component air dry formula designed to be used for the repair of minor surface imperfections such as scratches, pinholes, and stone chips. The working and dry time make it suitable for small to medium area repairs, for larger areas (use 3M™ Super Red Putty PN05099)

- Features**
- Single component
 - Air dry chemistry
 - Simple application

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Container	14.5 oz. aluminum tube (05098) 21.0 oz. aluminum tube (05966)
Base	Talc, Acrylic co-polymer, Toluene, Xylene
Density	12.00 - 13.00 Lbs./Gal.
Color	Red

Product Uses Repair of minor surface imperfections prior to top coat applications. 3M™ Acryl-Red Putty works best when applied over primer or polyester body filler, it may also be applied over clean and sanded painted surfaces.

Performance Properties Air dry formula skins over quickly and may be sanded in 20 minutes when applied in 1/16" thickness or less with ambient temperature conditions of 72°F.

3M™ Acryl-Red Putty

05098 • 05966

Directions for Use

1. Do not apply when ambient temperatures are below 55°F or above 110°F. Use in a well ventilated area away from sparks or open flame.
2. For best results Apply only over clean sanded primed surfaces. (Use compressed air to remove any dust contamination).
3. Apply using a plastic or metal spreader pressing the putty firmly into the imperfections; keep the application thickness to 1/16" or less. Apply in thin coats instead of one thick application.
4. Allow to dry for 20 minutes at 72°F prior to sanding. Sand (wet or dry) using 3M™ abrasives in the following sequence P180, P220, P320. **Note:** As with any putty, longer drying times will occur with high humidity, thick applications and low temperatures.
5. Re-clean surface prior to priming or top coating. (Follow paint manufacturer's recommendation for priming and top coating).

Applications

Minor surface imperfections in properly prepared painted or primed surfaces.

Storage and Handling

HANDLING

Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly with soap and water. Keep out of the reach of children. Keep container closed when not in use. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Avoid eye contact with dust or airborne particles.

STORAGE

Product shelf life 36 months from date of manufacture. Store at 72°F for optimal shelf life.

3M™ Acryl-Red Putty

05098 • 05966

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information



Automotive Aftermarket Division

3M Center, Building 223-6N-01
St. Paul, MN 55144-1000
1-877-666-2277 (1-877-MMM-CARS)
www.3MCollision.com

3M is a trademark of 3M
Company. Printed in U.S.A.
©3M 2012 P.N. 05098, 05966 (2/12)