



## Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	19-4648-2	<b>Version Number:</b>	9.01
<b>Issue Date:</b>	01/19/18	<b>Supersedes Date:</b>	10/29/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Marine Adhesive Sealant 5200 Mahogany PN 06502

#### Product Identification Numbers

60-4400-9507-7, 60-9801-0934-6, 62-5237-5236-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Marine Adhesive Sealant, Sealant

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division Marine & Specialty Vehicle
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Respiratory Sensitizer: Category 1A.

Skin Sensitizer: Category 1A.

Carcinogenicity: Category 1B.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Health Hazard |

##### Pictograms

**Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 May cause an allergic skin reaction.  
 May cause cancer.

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 In case of inadequate ventilation wear respiratory protection.  
 Wear protective gloves.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

3% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane Prepolymer	68611-34-7	40 - 70 Trade Secret *
Talc	14807-96-6	10 - 30 Trade Secret *
Carbitol Acetate	112-15-2	1 - 5 Trade Secret *
Fumed Silica	112945-52-5	1 - 5 Trade Secret *
Titanium Dioxide	13463-67-7	1 - 5 Trade Secret *
Zinc Oxide	1314-13-2	1 - 5 Trade Secret *
Iron Oxides	Mixture	0.5 - 5 Trade Secret *
Alkyl Isocyanate Silane	85702-90-5	0.5 - 1.5 Trade Secret *
Toluene Diisocyanate	26471-62-5	< 0.5 Trade Secret *
Heptane	142-82-5	< 0.3 Trade Secret *
(Gamma-mercaptopropyl)trimethoxysilane	4420-74-0	< 0.2 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

DO NOT USE WATER. Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Isocyanates  
Carbon monoxide  
Carbon dioxide  
Hydrogen Cyanide  
Irritant Vapors or Gases  
Oxides of Nitrogen

#### Condition

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
SILICA, AMORPHOUS	112945-52-5	OSHA	TWA concentration:0.8 mg/m <sup>3</sup> ;TWA:20 millions of particles/cu. ft.	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup> ;STEL(respirable fraction):10 mg/m <sup>3</sup>	
Zinc Oxide	1314-13-2	OSHA	TWA(as fume):5 mg/m <sup>3</sup> ;TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m <sup>3</sup>	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m <sup>3</sup>	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	OSHA	TWA:2000 mg/m <sup>3</sup> (500 ppm)	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA:2 mg/m <sup>3</sup>	

Toluene Diisocyanate	26471-62-5	ACGIH	TWA(inhalable fraction and vapor):0.001 ppm;STEL(inhalable fraction and vapor):0.005 ppm	SKIN; Resp+Dermal sensitizer, A4: Not class. as human carcin
----------------------	------------	-------	--	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl Rubber

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Red/brown
<b>Odor threshold</b>	<i>No Data Available</i>

pH	No Data Available
Melting point	No Data Available
Boiling Point	Not Applicable
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	11.03 lb/gal
Specific Gravity	1.3 [Ref Std:WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	100,000 - 500,000 centipoise
Hazardous Air Pollutants	<=0.2 % weight [Test Method:Calculated]
Molecular weight	No Data Available
VOC Less H2O & Exempt Solvents	40 g/l [Test Method:tested per EPA method 24]
VOC Less H2O & Exempt Solvents	2.9 % [Test Method:tested per EPA method 24]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Amines

Alcohols

Water

### 10.6. Hazardous decomposition products

#### Substance

#### Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Toluene Diisocyanate	26471-62-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Toluene Diisocyanate	26471-62-5	Anticipated human carcinogen	National Toxicology Program Carcinogens

#### Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Fumed Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l

Fumed Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbitol Acetate	Dermal	Rabbit	LD50 15,000 mg/kg
Carbitol Acetate	Ingestion	Rat	LD50 11,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Iron Oxides	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxides	Ingestion	Not available	LD50 3,700 mg/kg
Toluene Diisocyanate	Inhalation-Vapor (4 hours)	Mouse	LC50 0.12 mg/l
Toluene Diisocyanate	Dermal	Rabbit	LD50 > 9,400 mg/kg
Toluene Diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.35 mg/l
Toluene Diisocyanate	Ingestion	Rat	LD50 > 5,000 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
(Gamma-mercaptopropyl)trimethoxysilane	Dermal	Rabbit	LD50 2,270 mg/kg
(Gamma-mercaptopropyl)trimethoxysilane	Ingestion	Rat	LD50 770 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
Zinc Oxide	Human and animal	No significant irritation
Carbitol Acetate	Human and animal	Minimal irritation
Titanium Dioxide	Rabbit	No significant irritation
Iron Oxides	Rabbit	No significant irritation
Toluene Diisocyanate	Rabbit	Irritant
Heptane	Human	Mild irritant

### Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
Zinc Oxide	Rabbit	Mild irritant
Carbitol Acetate	Rabbit	Severe irritant
Titanium Dioxide	Rabbit	No significant irritation
Iron Oxides	Rabbit	No significant irritation
Toluene Diisocyanate	Rabbit	Corrosive
Heptane	Professional judgement	Moderate irritant



**Skin Sensitization**

Name	Species	Value
Fumed Silica	Human and animal	Not classified
Zinc Oxide	Guinea pig	Not classified
Carbitol Acetate	Human and animal	Not classified
Titanium Dioxide	Human and animal	Not classified
Iron Oxides	Human	Not classified
Toluene Diisocyanate	Human and animal	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
Talc	Human	Not classified
Toluene Diisocyanate	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Fumed Silica	In Vitro	Not mutagenic
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Carbitol Acetate	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Iron Oxides	In Vitro	Not mutagenic
Toluene Diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Fumed Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Iron Oxides	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Toluene Diisocyanate	Inhalation	Human and animal	Not carcinogenic
Toluene Diisocyanate	Ingestion	Multiple animal species	Carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Fumed Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation
Toluene Diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene Diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene Diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Carbitol Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	not applicable
Carbitol Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not applicable
Toluene Diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Fumed Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Carbitol Acetate	Inhalation	respiratory system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks

Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Iron Oxides	Inhalation	pulmonary fibrosis   pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene Diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL 0 mg/l	occupational exposure
Heptane	Inhalation	liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks

**Aspiration Hazard**

Name	Value
Heptane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory

requirements.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Carcinogenicity

Respiratory or Skin Sensitization

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Zinc Oxide (ZINC COMPOUNDS)	1314-13-2	1 - 5
Carbitol Acetate (GLYCOL ETHERS)	112-15-2	1 - 5
Toluene Diisocyanate	26471-62-5	Trade Secret < 0.5
Toluene Diisocyanate (Benzene, 1,3-diisocyanatomethyl-)	26471-62-5	< 0.5

#### This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
Toluene Diisocyanate (Benzene, 1,3-diisocyanatomethyl-)	26471-62-5	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Proposed
Toluene Diisocyanate	26471-62-5	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Proposed

#### This material contains a chemical subject to a proposed EPA Significant New Use Rule (TSCA Section 5)

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Reference</u>
Toluene Diisocyanate	26471-62-5	80 FR 2068

### 15.2. State Regulations

Contact 3M for more information.

#### California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
Toluene Diisocyanate	26471-62-5	Carcinogen

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	19-4648-2	<b>Version Number:</b>	9.01
<b>Issue Date:</b>	01/19/18	<b>Supersedes Date:</b>	10/29/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)