

3M General Offices 3M Center St. Paul, MN 55144-1000 1-800-364-3577 or (651) 737-6501 (24 hours)

Safety Data Sheet

Purchase Order #: Customer Number: 68743 0016124695 2022-10-12 13:08:14.51

SDS Coordinator HISCO CONCORD PARK DR 6650 HOUSTON, TX 77040-4098 USA

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at www.3m.com/MSDSSearch.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at emsdsadmin@mmm.com

*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 10-2435-5 | Version Number: | 30.01 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 01/26/22 | Supercedes Date: | 09/24/21 |

SECTION 1: Identification

1.1. Product identifier

3M[™] Scotch-Seal[™] Metal Sealant 2084 Silver

| Product Identification N | umbers | |
|--------------------------|--------|--|
| ID Number | UPC | |

| ID Number | UPC | ID Number | UPC |
|----------------|------------------|----------------|------------------|
| 62-2084-2631-2 | 00-21200-20227-8 | 62-2084-2635-3 | |
| 62-2084-8530-0 | 00-21200-20230-8 | 62-2084-9530-9 | 00-21200-20231-5 |

7000046343, 7010309730, 7000046344, 7000046345

1.2. Recommended use and restrictions on use

Recommended use

Metal sealant., Metal Sealant

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

| 1.3. Supplier's details | |
|-------------------------|-----------------------------------------|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 2. Serious Eye Damage/Irritation: Category 1. Reproductive Toxicity: Category 1B. Carcinogenicity: Category 1A. Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements Highly flammable liquid and vapor.

Causes serious eye damage. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
IF exposed or concerned: Get medical advice/attention.
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Keep cool. Keep container tightly closed. Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------------------------------------|-------------|--------------------------|
| Acetone | 67-64-1 | 30 - 60 Trade Secret * |
| Acrylonitrile-Butadiene Polymer | 9003-18-3 | 10 - 35 Trade Secret * |
| Butylphenol-Formaldehyde Polymer | 25085-50-1 | 10 - 20 Trade Secret * |
| Kaolin | 1332-58-7 | < 10 Trade Secret * |
| Rosin Ester | 8050-31-5 | 3 - 7 Trade Secret * |
| Aluminum | 7429-90-5 | 1 - 6 Trade Secret * |
| Salicylic Acid | 69-72-7 | 1 - 5 Trade Secret * |
| Petroleum Distillates | 64742-88-7 | < 3 Trade Secret * |
| Amorphous Silica | 112945-52-5 | 0.5 - 2.5 Trade Secret * |
| Zinc Oxide | 1314-13-2 | < 1.5 Trade Secret * |
| 2,2'-Methylenebis[6-tert-Butyl-p-Cresol] | 119-47-1 | < 1 Trade Secret * |
| Quartz Silica | 14808-60-7 | < 1 Trade Secret * |
| Toluene | 108-88-3 | < 1 Trade Secret * |
| Ethylbenzene | 100-41-4 | < 0.5 Trade Secret * |
| p-Tert-Butylphenol | 98-54-4 | < 0.2 Trade Secret * |
| Formaldehyde | 50-00-0 | < 0.1 Trade Secret * |
| Benzene | 71-43-2 | < 0.05 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-------------------------|------------|--------|----------------------------------|-------------------------|
| Ethylbenzene | 100-41-4 | ACGIH | TWA:20 ppm | A3: Confirmed animal |
| | | | | carcin. |
| Ethylbenzene | 100-41-4 | OSHA | TWA:435 mg/m3(100 ppm) | |
| Toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human |
| | | | | carcin, Ototoxicant |
| Toluene | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| SILICA, AMORPHOUS | 112945-52- | OSHA | TWA:20 millions of | |
| | 5 | | particles/cu. ft.;TWA | |
| | | | concentration:0.8 mg/m3 | |
| Zinc Oxide | 1314-13-2 | ACGIH | TWA(respirable fraction):2 | |
| | | | mg/m3;STEL(respirable | |
| | | | fraction):10 mg/m3 | |
| Zinc Oxide | 1314-13-2 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3;TWA(as | |
| | | | fume):5 mg/m3 | |
| DUST, INERT OR NUISANCE | 1332-58-7 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(as total dust):50 | |
| | | | millions of particles/cu. ft.(15 | |
| | | | mg/m3);TWA(respirable | |
| | | | fraction):5 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):15 millions of | |
| | | | particles/cu. ft.(5 mg/m3) | |
| Kaolin | 1332-58-7 | ACGIH | TWA(respirable fraction):2 | A4: Not class. as human |
| | | | mg/m3 | carcin |
| KAOLIN, TOTAL DUST | 1332-58-7 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| Quartz Silica | 14808-60-7 | ACGIH | TWA(respirable | A2: Suspected human |
| | | | fraction):0.025 mg/m3 | carcin. |
| Quartz Silica | 14808-60-7 | OSHA | TWA Table Z- | |
| | | | 1(respirable):0.05 | |
| | | | mg/m3;TWA Table Z- | |
| | | | 3(respirable):0.1 mg/m3;TWA | |
| | | | concentration(respirable):0.1 | |
| | | | mg/m3(2.4 millions of | |
| | | | particles/cu. ft.) | |
| Formaldehyde | 50-00-0 | ACGIH | TWA:0.1 ppm;STEL:0.3 ppm | A1: Confirmed human |
| | | | | carcin., |
| | | | | Dermal/Respiratory |

| | | | | Sensitizer |
|----------------------|------------|-------|------------------------------------------------------------------------------|------------------------------------|
| Formaldehyde | 50-00-0 | OSHA | TWA:0.75 ppm;STEL:2 ppm | 29 CFR 1910.1048 |
| Kerosine (petroleum) | 64742-88-7 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., SKIN |
| Naphtha | 64742-88-7 | OSHA | TWA:400 mg/m3(100 ppm) | |
| Acetone | 67-64-1 | ACGIH | TWA:250 ppm;STEL:500 ppm | A4: Not class. as human carcin |
| Acetone | 67-64-1 | OSHA | TWA:2400 mg/m3(1000 ppm) | |
| Benzene | 71-43-2 | ACGIH | TWA:0.5 ppm;STEL:2.5 ppm | A1: Confirmed human carcin., SKIN |
| Benzene | 71-43-2 | OSHA | TWA:1 ppm;TWA:10 ppm;STEL:5 ppm;CEIL:25 ppm | 29 CFR 1910.1028 |
| Aluminum | 7429-90-5 | ACGIH | TWA(respirable fraction):1 mg/m3 | A4: Not class. as human carcin |
| Aluminum | 7429-90-5 | OSHA | TWA(as Al total dust):15 mg/m3;TWA(as Al, respirable fraction):5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | |
|-----------------------------------------|--------------------------------------------------------------|
| Physical state | Liquid |
| Color | Aluminum |
| Specific Physical Form: | Paste |
| Odor | Ketones |
| Odor threshold | No Data Available |
| рН | Not Applicable |
| Melting point | Not Applicable |
| Boiling Point | >=56 °C [Details: Acetone] |
| Flash Point | 15 °F [Test Method:Closed Cup] |
| Evaporation rate | 1.9 [<i>Ref Std</i> :ETHER=1] |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 2.6 % volume |
| Flammable Limits(UEL) | 12.8 % volume |
| Vapor Pressure | <=185 mmHg [@ 68 °F] |
| Vapor Density | 2.0 [Ref Std:AIR=1] \int |
| Density | 1.0 g/ml |
| Specific Gravity | 1.0 [Ref Std:WATER=1] |
| Solubility in Water | Slight (less than 10%) |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | 465 °C [Details: Acetone] |
| Decomposition temperature | No Data Available |
| Viscosity | 30,000 centipoise [@ 73.4 °F] |
| Hazardous Air Pollutants | <=0 % weight [<i>Test Method</i> :Calculated] |
| Molecular weight | No Data Available |
| Volatile Organic Compounds | 3.8 % [Test Method:calculated SCAQMD rule 443.1] |
| VOC Less H2O & Exempt Solvents | 68.5 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|-----------------------------------------------------------------|------------|--------------------------------|---------------------------------------------|
| Silica, Crystalline (Respirable Size) | 14808-60-7 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| BENZENE | 71-43-2 | | National Toxicology Program Carcinogens |
| BENZENE | 71-43-2 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| BENZENE | 71-43-2 | Cancer hazard | OSHA Carcinogens |
| Ethylbenzene | 100-41-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Formaldehyde | 50-00-0 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| Formaldehyde | 50-00-0 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| FORMALDEHYDE | 50-00-0 | Cancer hazard | OSHA Carcinogens |
| Silica dust, crystalline, in the form of quartz or cristobalite | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|----------------------------------|---------------------------------------|---------|------------------------------------------------|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Acetone | Dermal | Rabbit | LD50 > 15,688 mg/kg |
| Acetone | Inhalation- Vapor (4 hours) | Rat | LC50 76 mg/l |
| Acetone | Ingestion | Rat | LD50 5,800 mg/kg |
| Acrylonitrile-Butadiene Polymer | Dermal | Rabbit | LD50 > 15,000 mg/kg |
| Acrylonitrile-Butadiene Polymer | Ingestion | Rat | LD50 > 30,000 mg/kg |
| Butylphenol-Formaldehyde Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Butylphenol-Formaldehyde Polymer | Ingestion | Rat | LD50 5,660 mg/kg |
| Aluminum | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.888 mg/l |
| Kaolin | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Kaolin | Ingestion | Human | LD50 > 15,000 mg/kg |
| Rosin Ester | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Rosin Ester | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Salicylic Acid | Dermal | Rat | LD50 > 2,000 mg/kg |
| Salicylic Acid | Ingestion | Rat | LD50 891 mg/kg |
| Petroleum Distillates | Inhalation- Vapor | | LC50 estimated to be 20 - 50 mg/l |
| Petroleum Distillates | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Amorphous Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Amorphous Silica | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Amorphous Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Toluene | Dermal | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation- Vapor (4 hours) | Rat | LC50 30 mg/l |
| Toluene | Ingestion | Rat | LD50 5,550 mg/kg |
| Zinc Oxide | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| Zinc Oxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 5.7 mg/l |
| Zinc Oxide | Ingestion | Rat | LD50 > 5,000 mg/kg |

| Ethylbenzene | Dermal | Rabbit | LD50 15,433 mg/kg |
|------------------------------------------|-------------|--------|------------------------------------|
| Ethylbenzene | Inhalation- | Rat | LC50 17.4 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| Ethylbenzene | Ingestion | Rat | LD50 4,769 mg/kg |
| 2,2'-Methylenebis[6-tert-Butyl-p-Cresol] | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| 2,2'-Methylenebis[6-tert-Butyl-p-Cresol] | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Quartz Silica | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| p-Tert-Butylphenol | Dermal | Rabbit | LD50 2,318 mg/kg |
| p-Tert-Butylphenol | Inhalation- | Rat | LC50 > 5.6 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| p-Tert-Butylphenol | Ingestion | Rat | LD50 4,000 mg/kg |
| Formaldehyde | Dermal | Rabbit | LD50 270 mg/kg |
| Formaldehyde | Inhalation- | Rat | LC50 470 ppm |
| | Gas (4 | | |
| | hours) | | |
| Formaldehyde | Ingestion | Rat | LD50 800 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------------------|------------|---------------------------|
| | | |
| Acetone | Mouse | Minimal irritation |
| Acrylonitrile-Butadiene Polymer | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| Aluminum | Rabbit | No significant irritation |
| Kaolin | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| Rosin Ester | Rabbit | Minimal irritation |
| Salicylic Acid | Rabbit | No significant irritation |
| Petroleum Distillates | Rabbit | Irritant |
| Amorphous Silica | Rabbit | No significant irritation |
| Toluene | Rabbit | Irritant |
| Zinc Oxide | Human | No significant irritation |
| | and | |
| | animal | |
| Ethylbenzene | Rabbit | Mild irritant |
| Quartz Silica | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| p-Tert-Butylphenol | Rabbit | Irritant |
| Formaldehyde | official | Corrosive |
| | classifica | |
| | tion | |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------------------|-----------|---------------------------|
| | | |
| Acetone | Rabbit | Severe irritant |
| Acrylonitrile-Butadiene Polymer | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| Aluminum | Rabbit | No significant irritation |
| Kaolin | Professio | No significant irritation |
| | nal | |
| | judgeme | |

| | nt | |
|-----------------------|------------|---------------------------|
| Rosin Ester | Rabbit | Mild irritant |
| Salicylic Acid | Rabbit | Corrosive |
| Petroleum Distillates | Rabbit | No significant irritation |
| Amorphous Silica | Rabbit | No significant irritation |
| Toluene | Rabbit | Moderate irritant |
| Zinc Oxide | Rabbit | Mild irritant |
| Ethylbenzene | Rabbit | Moderate irritant |
| p-Tert-Butylphenol | Rabbit | Corrosive |
| Formaldehyde | official | Corrosive |
| | classifica | |
| | tion | |

Skin Sensitization

| Name | Species | Value |
|----------------------------------|---------|------------------------------------------------|
| Butylphenol-Formaldehyde Polymer | Human | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Aluminum | Guinea | Not classified |
| | pig | |
| Rosin Ester | Guinea | Not classified |
| | pig | |
| Salicylic Acid | Mouse | Not classified |
| Petroleum Distillates | Guinea | Not classified |
| | pig | |
| Amorphous Silica | Human | Not classified |
| | and | |
| | animal | |
| Toluene | Guinea | Not classified |
| | pig | |
| Zinc Oxide | Guinea | Not classified |
| | pig | |
| Ethylbenzene | Human | Not classified |
| p-Tert-Butylphenol | Human | Not classified |
| | and | |
| | animal | |
| Formaldehyde | Guinea | Sensitizing |
| | pig | |

Photosensitization

| Name | Species | Value |
|----------------|---------|-----------------|
| Salicylic Acid | Mouse | Not sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|--------------|---------|------------------------------------------------|
| | | |
| Aluminum | Human | Not classified |
| Formaldehyde | Human | Some positive data exist, but the data are not |
| | | sufficient for classification |

Germ Cell Mutagenicity

| Name | Route | Value |
|-----------------------|----------|------------------------------------------------------------------------------|
| | | |
| Acetone | In vivo | Not mutagenic |
| Acetone | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Aluminum | In Vitro | Not mutagenic |
| Rosin Ester | In Vitro | Not mutagenic |
| Salicylic Acid | In Vitro | Not mutagenic |
| Salicylic Acid | In vivo | Not mutagenic |
| Petroleum Distillates | In vivo | Not mutagenic |
| Petroleum Distillates | In Vitro | Some positive data exist, but the data are not sufficient for classification |

| Amorphous Silica | In Vitro | Not mutagenic |
|--------------------|----------|------------------------------------------------------------------------------|
| Toluene | In Vitro | Not mutagenic |
| Toluene | In vivo | Not mutagenic |
| Zinc Oxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Zinc Oxide | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Ethylbenzene | In vivo | Not mutagenic |
| Ethylbenzene | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In vivo | Some positive data exist, but the data are not sufficient for classification |
| p-Tert-Butylphenol | In Vitro | Not mutagenic |
| Formaldehyde | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Formaldehyde | In vivo | Mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------------|-------------------------------|------------------------------------------------------------------------------|
| Acetone | Not Specified | Multiple animal species | Not carcinogenic |
| Kaolin | Inhalation | Multiple animal species | Not carcinogenic |
| Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |
| Amorphous Silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Ethylbenzene | Inhalation | Multiple animal species | Carcinogenic |
| Quartz Silica | Inhalation | Human and animal | Carcinogenic |
| p-Tert-Butylphenol | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Formaldehyde | Not Specified | Human and animal | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|----------------|------------|--------------------------------------|---------|--------------------------|-----------------------------|
| Acetone | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,700 mg/kg/day | 13 weeks |
| Acetone | Inhalation | Not classified for development | Rat | NOAEL 5.2 mg/l | during organogenesi s |
| Salicylic Acid | Ingestion | Toxic to development | Rat | NOAEL 75 mg/kg/day | during organogenesi |

| | | | | | S |
|------------------------------------------|------------|----------------------------------------------------|-------------------------------|--------------------------|------------------------------------|
| Petroleum Distillates | Inhalation | Not classified for development | Rat | NOAEL 2.4 mg/l | during organogenesi s |
| Amorphous Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| Toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| Toluene | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| Toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |
| Zinc Oxide | Ingestion | Not classified for reproduction and/or development | Multiple animal species | NOAEL 125 mg/kg/day | premating & during gestation |
| Ethylbenzene | Inhalation | Not classified for development | Rat | NOAEL 4.3 mg/l | premating & during gestation |
| 2,2'-Methylenebis[6-tert-Butyl-p-Cresol] | Ingestion | Not classified for female reproduction | Rat | NOAEL 50 mg/kg/day | premating & during gestation |
| 2,2'-Methylenebis[6-tert-Butyl-p-Cresol] | Ingestion | Toxic to male reproduction | Rat | NOAEL 12.5 mg/kg/day | 50 days |
| p-Tert-Butylphenol | Ingestion | Not classified for male reproduction | Rat | NOAEL 600 mg/kg/day | 2 generation |
| p-Tert-Butylphenol | Ingestion | Not classified for development | Rat | NOAEL 70 mg/kg/day | 2 generation |
| p-Tert-Butylphenol | Ingestion | Toxic to female reproduction | Rat | NOAEL 200 mg/kg/day | 2 generation |
| Formaldehyde | Ingestion | Not classified for male reproduction | Rat | NOAEL 100 mg/kg | not applicable |
| Formaldehyde | Inhalation | Not classified for development | Rat | NOAEL 10 ppm | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|--------------------------------------|------------------------------------------------------------------------------|------------------------|------------------------|---------------------------|
| Acetone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Acetone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Acetone | Inhalation | immune system | Not classified | Human | NOAEL 1.19 mg/l | 6 hours |
| Acetone | Inhalation | liver | Not classified | Guinea pig | NOAEL Not available | |
| Acetone | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Petroleum Distillates | Inhalation | nervous system | Not classified | Dog | NOAEL 6.5 mg/l | 4 hours |
| Petroleum Distillates | Ingestion | central nervous | May cause drowsiness or | Professio | NOAEL Not | |

| | | system depression | dizziness | nal judgeme nt | available | |
|--------------------|------------|--------------------------------------|------------------------------------------------------------------------------|-----------------------------------|------------------------|---------------------------|
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| Toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Ethylbenzene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethylbenzene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Ethylbenzene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |
| p-Tert-Butylphenol | Inhalation | respiratory irritation | May cause respiratory irritation | Rat | LOAEL 5.6 mg/l | 4 hours |
| Formaldehyde | Inhalation | respiratory system | Causes damage to organs | Rat | LOAEL 128 ppm | 6 hours |
| Formaldehyde | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------|------------|-------------------------------------------|----------------------------------------------------------------|---------------|------------------------------|--------------------------|
| Acetone | Dermal | eyes | Not classified | Guinea pig | NOAEL Not available | 3 weeks |
| Acetone | Inhalation | hematopoietic system | Not classified | Human | NOAEL 3 mg/l | 6 weeks |
| Acetone | Inhalation | immune system | Not classified | Human | NOAEL 1.19 mg/l | 6 days |
| Acetone | Inhalation | kidney and/or bladder | Not classified | Guinea pig | NOAEL 119 mg/l | not available |
| Acetone | Inhalation | heart liver | Not classified | Rat | NOAEL 45 mg/l | 8 weeks |
| Acetone | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 900 mg/kg/day | 13 weeks |
| Acetone | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Acetone | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 200 mg/kg/day | 13 weeks |
| Acetone | Ingestion | liver | Not classified | Mouse | NOAEL 3,896 mg/kg/day | 14 days |
| Acetone | Ingestion | eyes | Not classified | Rat | NOAEL 3,400 mg/kg/day | 13 weeks |
| Acetone | Ingestion | respiratory system | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Acetone | Ingestion | muscles | Not classified | Rat | NOAEL 2,500 mg/kg | 13 weeks |
| Acetone | Ingestion | skin bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 11,298 mg/kg/day | 13 weeks |
| Aluminum | Inhalation | nervous system respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Kaolin | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL NA | occupational exposure |

| Kaolin | Inhalation | pulmonary fibrosis | Not classified | Rat | NOAEL Not available | |
|-----------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------------|-----------------------------|---------------------------|
| Rosin Ester | Ingestion | liver heart skin endocrine system bone, teeth, nails, and/or hair blood bone marrow hematopoietic system immune system muscles nervous system eyes kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 5,000 mg/kg/day | 90 days |
| Salicylic Acid | Ingestion | liver | Not classified | Rat | NOAEL 500 mg/kg/day | 3 days |
| Petroleum Distillates | Inhalation | nervous system | Not classified | Rat | LOAEL 4.6 mg/l | 6 months |
| Petroleum Distillates | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.9 mg/l | 13 weeks |
| Petroleum Distillates | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 0.6 mg/l | 90 days |
| Petroleum Distillates | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | Not classified | Rat | NOAEL 5.6 mg/l | 12 weeks |
| Petroleum Distillates | Inhalation | heart | Not classified | Multiple animal species | NOAEL 1.3 mg/l | 90 days |
| Amorphous Silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | auditory system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | nervous system | May cause damage to organs though prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| Toluene | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| Toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| Toluene | Inhalation | hematopoietic system vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| Toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| Toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |

| Toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |
|--------------------|------------|-----------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------|------------------------|--------------------------|
| Zinc Oxide | Ingestion | nervous system | Not classified | Rat | NOAEL 600 mg/kg/day | 10 days |
| Zinc Oxide | Ingestion | endocrine system hematopoietic system kidney and/or bladder | Not classified | Other | NOAEL 500 mg/kg/day | 6 months |
| Ethylbenzene | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 2 years |
| Ethylbenzene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 1.1 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 3.4 mg/l | 28 days |
| Ethylbenzene | Inhalation | auditory system | Not classified | Rat | NOAEL 2.4 mg/l | 5 days |
| Ethylbenzene | Inhalation | endocrine system | Not classified | Mouse | NOAEL 3.3 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | gastrointestinal tract | Not classified | Rat | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | bone, teeth, nails, and/or hair muscles | Not classified | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | heart immune system respiratory system | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Ingestion | liver kidney and/or bladder | Not classified | Rat | NOAEL 680 mg/kg/day | 6 months |
| Quartz Silica | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| p-Tert-Butylphenol | Ingestion | endocrine system liver kidney and/or bladder | Not classified | Rat | NOAEL 600 mg/kg/day | 2 generation |
| p-Tert-Butylphenol | Ingestion | blood | Not classified | Rat | NOAEL 200 mg/kg | 6 weeks |
| Formaldehyde | Dermal | respiratory system | Not classified | Mouse | NOAEL 80 mg/kg/day | 60 weeks |
| Formaldehyde | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | NOAEL 0.3 ppm | 28 months |
| Formaldehyde | Inhalation | liver | Not classified | Rat | NOAEL 20 ppm | 13 weeks |
| Formaldehyde | Inhalation | hematopoietic system | Not classified | Mouse | NOAEL 15 ppm | 3 weeks |
| Formaldehyde | Inhalation | nervous system | Not classified | Mouse | NOAEL 10 ppm | 13 weeks |
| Formaldehyde | Inhalation | endocrine system immune system muscles kidney and/or bladder | Not classified | Rat | NOAEL 15 ppm | 28 months |
| Formaldehyde | Inhalation | gastrointestinal tract | Not classified | Rat | NOAEL 15 ppm | 2 years |
| Formaldehyde | Inhalation | eyes vascular system | Not classified | Rat | NOAEL 14.3 ppm | 2 years |
| Formaldehyde | Inhalation | heart | Not classified | Mouse | NOAEL 14.3 ppm | 2 years |
| Formaldehyde | Ingestion | liver | Not classified | Rat | NOAEL 300 mg/kg/day | 2 years |
| Formaldehyde | Ingestion | immune system | Not classified | Rat | NOAEL 20 mg/kg/day | 4 weeks |
| Formaldehyde | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 15 mg/kg/day | 24 months |
| Formaldehyde | Ingestion | nervous system | Not classified | Rat | NOAEL 109 mg/kg/day | 2 years |
| Formaldehyde | Ingestion | heart endocrine system | Not classified | Rat | NOAEL 300 mg/kg/day | 2 years |

| | | hematopoietic system respiratory system vascular system | | | | |
|--------------|-----------|----------------------------------------------------------------------|----------------|-----|-----------|---------|
| Formaldehyde | Ingestion | skin muscles eyes | Not classified | Rat | NOAEL 109 | 2 years |
| | | | | | mg/kg/day | |

Aspiration Hazard

| Name | Value |
|-----------------------|-------------------|
| Petroleum Distillates | Aspiration hazard |
| Toluene | Aspiration hazard |
| Ethylbenzene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D018 (Benzene)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

| Carcinogenicity | |
|--------------------------------------------------------------|--|
| Reproductive toxicity | |
| Serious eye damage or eye irritation | |
| Specific target organ toxicity (single or repeated exposure) | |

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| Ingredient | <u>C.A.S. No</u> | <u>% by Wt</u> |
|-----------------------------|------------------|--------------------|
| Aluminum | 7429-90-5 | Trade Secret 1 - 6 |
| Aluminum (Aluminum) | 7429-90-5 | Trade Secret 1 - 6 |
| Zinc Oxide (ZINC COMPOUNDS) | 1314-13-2 | Trade Secret < 1.5 |
| Ethylbenzene | 100-41-4 | Trade Secret < 0.5 |

Additional TSCA Information

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification Health: 3 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 10-2435-5 | Version Number: | 30.01 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 01/26/22 | Supercedes Date: | 09/24/21 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com