



**3M General Offices**  
3M Center  
St. Paul, MN 55144-1000  
1-800-364-3577 or (651) 737-6501 (24 hours)

## Safety Data Sheet

2023-10-19 21:43:27.74

Purchase Order #: 146343  
Customer Number: 0016122909

SDS Coordinator  
ADHESIVE MATERIALS GROUP  
STE 150 HWY 6 N 9327  
HOUSTON, TX 77095-2403  
USA

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)\* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at [www.3m.com/MSDSSearch](http://www.3m.com/MSDSSearch).

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

**If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at [emsdsadmin@mmm.com](mailto:emsdsadmin@mmm.com)**

\*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



## Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 10-3167-3  
**Issue Date:** 10/14/22

**Version Number:** 30.02  
**Supersedes Date:** 04/10/21

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Gray Part B

#### Product Identification Numbers

| ID Number      | UPC              | ID Number      | UPC |
|----------------|------------------|----------------|-----|
| 62-2216-8530-8 | 00-21200-20360-2 | 62-2216-8535-7 |     |
| 62-2216-9530-7 | 00-21200-20361-9 | 62-2216-9531-5 |     |

7000046360, 7100050481, 7100166319

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Structural adhesive

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Industrial Adhesives and Tapes Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Causes eye irritation.  
May cause an allergic skin reaction.  
May damage fertility or the unborn child.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wear protective gloves.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

| <b>Ingredient</b> | <b>C.A.S. No.</b> | <b>% by Wt</b>         |
|-------------------|-------------------|------------------------|
| Epoxy Resin       | 25068-38-6        | 70 - 80 Trade Secret * |
| Kaolin            | 1332-58-7         | 20 - 30 Trade Secret * |
| Titanium Dioxide  | 13463-67-7        | < 1 Trade Secret *     |
| Toluene           | 108-88-3          | < 1 Trade Secret *     |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Aldehydes

Hydrocarbons

Carbon monoxide

Carbon dioxide

Hydrogen Chloride

Ketones

Toxic Vapor, Gas, Particulate

**Condition**

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient              | C.A.S. No. | Agency | Limit type  | Additional Comments                         |
|-------------------------|------------|--------|---|---|
| Toluene                 | 108-88-3   | ACGIH  | TWA:20 ppm  | A4: Not class. as human carcin, Ototoxicant |
| Toluene                 | 108-88-3   | OSHA   | TWA:200 ppm;CEIL:300 ppm  |   |
| DUST, INERT OR NUISANCE | 1332-58-7  | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m <sup>3</sup> );TWA(respirable fraction):5 mg/m <sup>3</sup> ;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m <sup>3</sup> ) |   |
| Kaolin                  | 1332-58-7  | ACGIH  | TWA(respirable fraction):2 mg/m <sup>3</sup>  | A4: Not class. as human carcin              |
| KAOLIN, TOTAL DUST      | 1332-58-7  | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>   |   |
| Titanium Dioxide        | 13463-67-7 | ACGIH  | TWA:10 mg/m <sup>3</sup>  | A4: Not class. as human carcin              |
| Titanium Dioxide        | 13463-67-7 | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup>   |   |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Provide ventilated enclosure for curing. Use general dilution ventilation and/or local exhaust ventilation to control airborne

exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields  
Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state  
Color

Liquid  
Gray

Specific Physical Form:

Viscous Liquid

Odor

Slight Epoxy

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

248 °C [Test Method: Pensky-Martens Closed Cup]

Evaporation rate

Not Applicable

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

<=0.1 mmHg [@ 25 °C]

Vapor Density

Not Applicable

Density

1.33 g/ml [@ 20 °C]

Specific Gravity

1.33 [@ 20 °C] [Ref Std: WATER=1]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

|                                |   |
|--------------------------------|---|
| Decomposition temperature      | No Data Available   |
| Viscosity                      | 75,000 - 150,000 centipoise [Test Method: Brookfield]   |
| Hazardous Air Pollutants       | 0 % weight [Test Method: Calculated]  |
| Molecular weight               | No Data Available   |
| VOC Less H2O & Exempt Solvents | 3.7 g/l [Test Method: calculated SCAQMD rule 443.1]<br>[Details: when used as intended with Part A] |
| VOC Less H2O & Exempt Solvents | 0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]                            |
| VOC Less H2O & Exempt Solvents | < 0.5 % [Test Method: calculated SCAQMD rule 443.1]<br>[Details: when used as intended with Part A] |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
|------------------|------------------|

|             |  |
|-------------|--|
| None known. |  |
|-------------|--|

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

| <b><u>Ingredient</u></b> | <b><u>CAS No.</u></b> | <b><u>Class Description</u></b> | <b><u>Regulation</u></b>                    |
|--------------------------|-----------------------|---------------------------------|---|
| Titanium dioxide         | 13463-67-7            | Grp. 2B: Possible human carc.   | International Agency for Research on Cancer |

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| <b><u>Name</u></b> | <b><u>Route</u></b>            | <b><u>Species</u></b> | <b><u>Value</u></b>                            |
|--------------------|--------------------------------|-----------------------|--|
| Overall product    | Ingestion                      |                       | No data available; calculated ATE >5,000 mg/kg |
| Epoxy Resin        | Dermal                         | Rat                   | LD50 > 1,600 mg/kg                             |
| Epoxy Resin        | Ingestion                      | Rat                   | LD50 > 1,000 mg/kg                             |
| Kaolin             | Dermal                         |                       | LD50 estimated to be > 5,000 mg/kg             |
| Kaolin             | Ingestion                      | Human                 | LD50 > 15,000 mg/kg                            |
| Toluene            | Dermal                         | Rat                   | LD50 12,000 mg/kg                              |
| Toluene            | Inhalation-Vapor (4 hours)     | Rat                   | LC50 30 mg/l                                   |
| Toluene            | Ingestion                      | Rat                   | LD50 5,550 mg/kg                               |
| Titanium Dioxide   | Dermal                         | Rabbit                | LD50 > 10,000 mg/kg                            |
| Titanium Dioxide   | Inhalation-Dust/Mist (4 hours) | Rat                   | LC50 > 6.82 mg/l                               |
| Titanium Dioxide   | Ingestion                      | Rat                   | LD50 > 10,000 mg/kg                            |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| <b><u>Name</u></b> | <b><u>Species</u></b>  | <b><u>Value</u></b>       |
|--------------------|------------------------|---------------------------|
| Epoxy Resin        | Rabbit                 | Mild irritant             |
| Kaolin             | Professional judgement | No significant irritation |
| Toluene            | Rabbit                 | Irritant                  |
| Titanium Dioxide   | Rabbit                 | No significant irritation |

**Serious Eye Damage/Irritation**

| <b><u>Name</u></b> | <b><u>Species</u></b> | <b><u>Value</u></b> |
|--------------------|-----------------------|---------------------|
|--------------------|-----------------------|---------------------|



|                  |                       |                           |
|------------------|-----------------------|---------------------------|
| Epoxy Resin      | Rabbit                | Moderate irritant         |
| Kaolin           | Professional judgment | No significant irritation |
| Toluene          | Rabbit                | Moderate irritant         |
| Titanium Dioxide | Rabbit                | No significant irritation |

**Skin Sensitization**

| Name             | Species          | Value          |
|------------------|------------------|----------------|
| Epoxy Resin      | Human and animal | Sensitizing    |
| Toluene          | Guinea pig       | Not classified |
| Titanium Dioxide | Human and animal | Not classified |

**Respiratory Sensitization**

| Name        | Species | Value          |
|-------------|---------|----------------|
| Epoxy Resin | Human   | Not classified |

**Germ Cell Mutagenicity**

| Name             | Route    | Value  |
|------------------|----------|--|
| Epoxy Resin      | In vivo  | Not mutagenic  |
| Epoxy Resin      | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Toluene          | In Vitro | Not mutagenic  |
| Toluene          | In vivo  | Not mutagenic  |
| Titanium Dioxide | In Vitro | Not mutagenic  |
| Titanium Dioxide | In vivo  | Not mutagenic  |

**Carcinogenicity**

| Name             | Route      | Species                 | Value  |
|------------------|------------|-------------------------|--|
| Epoxy Resin      | Dermal     | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Kaolin           | Inhalation | Multiple animal species | Not carcinogenic   |
| Toluene          | Dermal     | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Toluene          | Ingestion  | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Toluene          | Inhalation | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | Ingestion  | Multiple animal species | Not carcinogenic   |
| Titanium Dioxide | Inhalation | Rat                     | Carcinogenic   |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name        | Route     | Value                                  | Species | Test Result         | Exposure Duration |
|-------------|-----------|--|---------|---------------------|-------------------|
| Epoxy Resin | Ingestion | Not classified for female reproduction | Rat     | NOAEL 750 mg/kg/day | 2 generation      |
| Epoxy Resin | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 750           | 2 generation      |

|             |            |  |        |                     |                        |
|-------------|------------|--|--------|---------------------|------------------------|
|             |            |  |        | mg/kg/day           |                        |
| Epoxy Resin | Dermal     | Not classified for development         | Rabbit | NOAEL 300 mg/kg/day | during organogenesis   |
| Epoxy Resin | Ingestion  | Not classified for development         | Rat    | NOAEL 750 mg/kg/day | 2 generation           |
| Toluene     | Inhalation | Not classified for female reproduction | Human  | NOAEL Not available | occupational exposure  |
| Toluene     | Inhalation | Not classified for male reproduction   | Rat    | NOAEL 2.3 mg/l      | 1 generation           |
| Toluene     | Ingestion  | Toxic to development                   | Rat    | LOAEL 520 mg/kg/day | during gestation       |
| Toluene     | Inhalation | Toxic to development                   | Human  | NOAEL Not available | poisoning and/or abuse |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

| Name    | Route      | Target Organ(s)                   | Value  | Species | Test Result         | Exposure Duration      |
|---------|------------|-----------------------------------|--|---------|---------------------|------------------------|
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available |                        |
| Toluene | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available |                        |
| Toluene | Inhalation | immune system                     | Not classified   | Mouse   | NOAEL 0.004 mg/l    | 3 hours                |
| Toluene | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available | poisoning and/or abuse |

#### Specific Target Organ Toxicity - repeated exposure

| Name        | Route      | Target Organ(s)  | Value  | Species | Test Result           | Exposure Duration      |
|-------------|------------|--|--|---------|-----------------------|------------------------|
| Epoxy Resin | Dermal     | liver  | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 2 years                |
| Epoxy Resin | Dermal     | nervous system   | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 13 weeks               |
| Epoxy Resin | Ingestion  | auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 28 days                |
| Kaolin      | Inhalation | pneumoconiosis   | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL NA              | occupational exposure  |
| Kaolin      | Inhalation | pulmonary fibrosis   | Not classified   | Rat     | NOAEL Not available   |                        |
| Toluene     | Inhalation | auditory system   eyes   olfactory system  | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available   | poisoning and/or abuse |
| Toluene     | Inhalation | nervous system   | May cause damage to organs though prolonged or repeated exposure             | Human   | NOAEL Not available   | poisoning and/or abuse |
| Toluene     | Inhalation | respiratory system   | Some positive data exist, but the data are not sufficient for classification | Rat     | LOAEL 2.3 mg/l        | 15 months              |
| Toluene     | Inhalation | heart   liver   kidney and/or bladder  | Not classified   | Rat     | NOAEL 11.3 mg/l       | 15 weeks               |
| Toluene     | Inhalation | endocrine system   | Not classified   | Rat     | NOAEL 1.1 mg/l        | 4 weeks                |
| Toluene     | Inhalation | immune system  | Not classified   | Mouse   | NOAEL Not available   | 20 days                |
| Toluene     | Inhalation | bone, teeth, nails,  | Not classified   | Mouse   | NOAEL 1.1             | 8 weeks                |

|                  |            | and/or hair                            |  |                         | mg/l                  |                       |
|------------------|------------|--|--|-------------------------|-----------------------|-----------------------|
| Toluene          | Inhalation | hematopoietic system   vascular system | Not classified   | Human                   | NOAEL Not available   | occupational exposure |
| Toluene          | Inhalation | gastrointestinal tract                 | Not classified   | Multiple animal species | NOAEL 11.3 mg/l       | 15 weeks              |
| Toluene          | Ingestion  | nervous system                         | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 625 mg/kg/day   | 13 weeks              |
| Toluene          | Ingestion  | heart                                  | Not classified   | Rat                     | NOAEL 2,500 mg/kg/day | 13 weeks              |
| Toluene          | Ingestion  | liver   kidney and/or bladder          | Not classified   | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks              |
| Toluene          | Ingestion  | hematopoietic system                   | Not classified   | Mouse                   | NOAEL 600 mg/kg/day   | 14 days               |
| Toluene          | Ingestion  | endocrine system                       | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 28 days               |
| Toluene          | Ingestion  | immune system                          | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 4 weeks               |
| Titanium Dioxide | Inhalation | respiratory system                     | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 0.01 mg/l       | 2 years               |
| Titanium Dioxide | Inhalation | pulmonary fibrosis                     | Not classified   | Human                   | NOAEL Not available   | occupational exposure |

**Aspiration Hazard**

| Name    | Value             |
|---------|-------------------|
| Toluene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not applicable

**Health Hazards**

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification**

**Health:** 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 10-3167-3

**Version Number:** 30.02

**Issue Date:** 10/14/22

**Supersedes Date:** 04/10/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product,

some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**