



Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: SCOTCHKOTE 323 C Patch Compound
MANUFACTURER: 3M
DIVISION: Electrical Markets Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/13/14
Supersedes Date: 04/21/14
Document Group: 27-7248-1

ID Number(s):

80-6300-0191-7

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

27-7240-8, 27-7243-2

Reason for Reissue: The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes: Not Applicable

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 27-7243-2

Version Number: 9.02

Issue Date: 07/26/18

Supersedes Date: 01/04/18

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchkote™ Liquid Epoxy Coating 323C Patch Compound, Part B

1.2. Recommended use and restrictions on use

Recommended use

Coating, Part B of 2 Part Liquid Epoxy Coating System

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Electrical Markets Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.
Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

7% of the mixture consists of ingredients of unknown acute oral toxicity.
7% of the mixture consists of ingredients of unknown acute dermal toxicity.
7% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------------------------|------------|------------------------|
| P-TERT-BUTYLPHENOL | 98-54-4 | 20 - 30 Trade Secret * |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | 20 - 30 Trade Secret * |
| M-XYLENE-.ALPHA.ALPHA'.-DIAMINE | 1477-55-0 | 5 - 15 Trade Secret * |

| | | |
|-----------------------------------|-------------|-----------------------|
| PHENOL, 4-NONYL-, branched | 84852-15-3 | 5 - 15 Trade Secret * |
| TRIMETHYLHEXAMETHYLENEDIAMINE | 25620-58-0 | 5 - 15 Trade Secret * |
| C.I. PIGMENT GREEN 7 | 1328-53-6 | 3 - 10 Trade Secret * |
| PHENOL FORMALDEHYDE AMINE POLYMER | 104242-08-2 | 3 - 10 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Ammonia
Oxides of Nitrogen

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation

to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------------------|------------|--------|---|--------------------------------|
| COPPER COMPOUNDS | 1328-53-6 | ACGIH | TWA(as Cu dust or mist):1 mg/m ³ ;TWA(as Cu, fume):0.2 mg/m ³ | |
| M-XYLENE-.ALPHA.ALPHA'.-DIAMINE | 1477-55-0 | ACGIH | CEIL:0.1 mg/m ³ | SKIN |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | ACGIH | TWA(respirable fraction):2 mg/m ³ | A4: Not class. as human carcin |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | OSHA | TWA:2 mg/m ³ | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------------------|---|
| General Physical Form: | Liquid |
| Odor, Color, Grade: | Viscous, Green, Strong Amine Odor |
| Odor threshold | <i>Not Applicable</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>No Data Available</i> |
| Boiling Point | > 200 °F |
| Flash Point | > 200 °F [<i>Test Method</i> :Pensky-Martens Closed Cup] |
| Evaporation rate | < 1 [<i>Ref Std</i> :BUOAC=1] |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 1 % volume |
| Flammable Limits(UEL) | 7 % volume |
| Vapor Pressure | 0.05 mmHg [<i>Test Method</i> :Calculated] [<i>Details</i> :at 25C, Raoult's Law] |

| | |
|---|---|
| Vapor Density | > 1 [Ref Std: AIR=1] |
| Density | 1.2 g/ml |
| Specific Gravity | 1.2 [Ref Std: WATER=1] |
| Solubility in Water | Slight (less than 10%) |
| Solubility- non-water | Not Applicable |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | Not Applicable |
| Viscosity | 13,000 - 20,000 centipoise [@ 72 °F] [Test Method: Brookfield] |
| Volatile Organic Compounds | 12 g/l [Details: For coating mixture of Parts A and B] |
| Percent volatile | 1.28 % volume |
| VOC Less H2O & Exempt Solvents | Not Applicable |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Reducing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| Carbon monoxide | During Storage |
| Carbon dioxide | During Storage |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or coloration.

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------|--------------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE5 - 12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| P-TERT-BUTYLPHENOL | Dermal | Rabbit | LD50 2,318 mg/kg |
| P-TERT-BUTYLPHENOL | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.6 mg/l |
| P-TERT-BUTYLPHENOL | Ingestion | Rat | LD50 4,000 mg/kg |

| | | | |
|---------------------------------|--------------------------------|--------|------------------------------------|
| HYDROUS MAGNESIUM SILICATE | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| HYDROUS MAGNESIUM SILICATE | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Inhalation-Dust/Mist (4 hours) | Rat | LC50 1.2 mg/l |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Ingestion | Rat | LD50 980 mg/kg |
| PHENOL, 4-NONYL-, branched | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| PHENOL, 4-NONYL-, branched | Ingestion | Rat | LD50 1,531 mg/kg |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Ingestion | Rat | LD50 910 mg/kg |
| C.I. PIGMENT GREEN 7 | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| C.I. PIGMENT GREEN 7 | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------------------|---------------|---------------------------|
| P-TERT-BUTYLPHENOL | Rabbit | Irritant |
| HYDROUS MAGNESIUM SILICATE | Rabbit | No significant irritation |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Rat | Corrosive |
| PHENOL, 4-NONYL-, branched | Rabbit | Corrosive |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Not available | Corrosive |
| C.I. PIGMENT GREEN 7 | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------------------|---------|---------------------------|
| P-TERT-BUTYLPHENOL | Rabbit | Corrosive |
| HYDROUS MAGNESIUM SILICATE | Rabbit | No significant irritation |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Rabbit | Corrosive |
| PHENOL, 4-NONYL-, branched | Rabbit | Corrosive |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Rabbit | Corrosive |
| C.I. PIGMENT GREEN 7 | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---------------------------------|------------------|----------------|
| P-TERT-BUTYLPHENOL | Human and animal | Not classified |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Guinea pig | Sensitizing |
| PHENOL, 4-NONYL-, branched | Guinea pig | Not classified |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Guinea pig | Sensitizing |
| C.I. PIGMENT GREEN 7 | Guinea pig | Not classified |

Respiratory Sensitization

| Name | Species | Value |
|----------------------------|---------|----------------|
| HYDROUS MAGNESIUM SILICATE | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------------------|----------|---------------|
| P-TERT-BUTYLPHENOL | In Vitro | Not mutagenic |
| HYDROUS MAGNESIUM SILICATE | In Vitro | Not mutagenic |
| HYDROUS MAGNESIUM SILICATE | In vivo | Not mutagenic |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | In Vitro | Not mutagenic |

| | | |
|---------------------------------|----------|--|
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | In vivo | Not mutagenic |
| PHENOL, 4-NONYL-, branched | In Vitro | Not mutagenic |
| PHENOL, 4-NONYL-, branched | In vivo | Not mutagenic |
| TRIMETHYLHEXAMETHYLENEDIAMINE | In vivo | Not mutagenic |
| C.I. PIGMENT GREEN 7 | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|----------------------------|------------|-------------------------|--|
| P-TERT-BUTYLPHENOL | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| HYDROUS MAGNESIUM SILICATE | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---------------------------------|-----------|--|-------------------------|---------------------|----------------------|
| P-TERT-BUTYLPHENOL | Ingestion | Not classified for male reproduction | Rat | NOAEL 600 mg/kg/day | 2 generation |
| P-TERT-BUTYLPHENOL | Ingestion | Not classified for female reproduction | Rat | NOAEL 600 mg/kg/day | 2 generation |
| P-TERT-BUTYLPHENOL | Ingestion | Not classified for development | Rat | NOAEL 70 mg/kg/day | 2 generation |
| HYDROUS MAGNESIUM SILICATE | Ingestion | Not classified for development | Rat | NOAEL 1,600 mg/kg | during organogenesis |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Ingestion | Not classified for female reproduction | Rat | NOAEL 450 mg/kg/day | 1 generation |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Ingestion | Not classified for male reproduction | Rat | NOAEL 450 mg/kg | 1 generation |
| M-XYLENE-.ALPHA.ALPHA'-.DIAMINE | Ingestion | Not classified for development | Rat | NOAEL 450 mg/kg/day | 1 generation |
| PHENOL, 4-NONYL-, branched | Ingestion | Not classified for male reproduction | Rat | NOAEL 400 mg/kg/day | 28 days |
| PHENOL, 4-NONYL-, branched | Ingestion | Toxic to female reproduction | official classification | NOAEL Not available | |
| PHENOL, 4-NONYL-, branched | Ingestion | Toxic to development | official classification | NOAEL Not available | |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Ingestion | Not classified for male reproduction | Rat | NOAEL 120 mg/kg/day | 2 generation |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Ingestion | Not classified for development | Rat | NOAEL 120 mg/kg/day | 2 generation |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Ingestion | Not classified for female reproduction | Rat | NOAEL 10 mg/kg/day | 2 generation |

Lactation

| Name | Route | Species | Value |
|----------------------------|-----------|---------|--|
| PHENOL, 4-NONYL-, branched | Ingestion | Rat | Not classified for effects on or via lactation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------------|------------|------------------------|---|---------------|---------------------|-------------------|
| P-TERT-BUTYLPHENOL | Inhalation | respiratory irritation | May cause respiratory irritation | Rat | LOAEL 5.6 mg/l | 4 hours |
| M-XYLENE-.ALPHA.ALPH | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for | Not available | NOAEL Not available | |

| | | | | | | |
|------------|--|--|----------------|--|--|--|
| A'-DIAMINE | | | classification | | | |
|------------|--|--|----------------|--|--|--|

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------------|------------|---|--|---------|---------------------|-----------------------|
| P-TERT-BUTYLPHENOL | Ingestion | endocrine system liver kidney and/or bladder | Not classified | Rat | NOAEL 600 mg/kg/day | 2 generation |
| P-TERT-BUTYLPHENOL | Ingestion | blood | Not classified | Rat | NOAEL 200 mg/kg | 6 weeks |
| HYDROUS MAGNESIUM SILICATE | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| HYDROUS MAGNESIUM SILICATE | Inhalation | pulmonary fibrosis respiratory system | Not classified | Rat | NOAEL 18 mg/m3 | 113 weeks |
| M-XYLENE-ALPHA.ALPH A'-DIAMINE | Ingestion | endocrine system blood bone marrow | Not classified | Rat | NOAEL 600 mg/kg/day | 28 days |
| PHENOL, 4-NONYL-, branched | Ingestion | endocrine system hematopoietic system liver | Not classified | Rat | NOAEL 400 mg/kg/day | 28 days |
| PHENOL, 4-NONYL-, branched | Ingestion | kidney and/or bladder heart bone, teeth, nails, and/or hair immune system muscles nervous system respiratory system | Not classified | Rat | NOAEL 150 mg/kg/day | 90 days |
| TRIMETHYLHEXAMETHYLENEDIAMINE | Ingestion | hematopoietic system liver | Not classified | Rat | NOAEL 180 mg/kg/day | 13 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

This material contains a chemical which requires export notification under TSCA Section 12[b]:

| <u>Ingredient (Category if applicable)</u> | <u>C.A.S. No</u> | <u>Regulation</u> | <u>Status</u> |
|---|------------------|--|---------------|
| PHENOL, 4-NONYL-, branched (Phenol, 4-nonyl-, branched) | 84852-15-3 | Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals | Proposed |
| PHENOL, 4-NONYL-, branched (Phenol, nonyl-) | 84852-15-3 | Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals | Proposed |
| PHENOL, 4-NONYL-, branched | 84852-15-3 | Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals | Proposed |

This material contains a chemical subject to a proposed EPA Significant New Use Rule (TSCA Section 5)

| <u>Ingredient (Category if applicable)</u> | <u>C.A.S. No</u> | <u>Reference</u> |
|--|------------------|------------------|
| PHENOL, 4-NONYL-, branched | 84852-15-3 | 79 FR 59186 |

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Listing</u> |
|----------------------------------|-------------------|---------------------------|
| Benzene | None | Male reproductive toxin |
| Benzene | None | Carcinogen |
| Benzene | None | Developmental Toxin |
| Benzene, 1,2,3,4,5,6-hexachloro- | None | Carcinogen |
| Benzene, 1,2,3,4,5,6-hexachloro- | None | Developmental Toxin |
| Cadmium | None | Male reproductive toxin |
| Cadmium | None | Carcinogen |
| Cadmium | None | Developmental Toxin |
| Lead | None | Female reproductive toxin |
| Lead | None | Male reproductive toxin |
| Lead | None | Carcinogen |
| Lead | None | Developmental Toxin |
| Mercury | None | Developmental Toxin |

| | | |
|---------------------------------|----------|---------------------------|
| 1,3-BUTADIENE | 106-99-0 | Female reproductive toxin |
| 1,3-BUTADIENE | 106-99-0 | Male reproductive toxin |
| 1,3-BUTADIENE | 106-99-0 | Carcinogen |
| 1,3-BUTADIENE | 106-99-0 | Developmental Toxin |
| CHROMIUM (HEXAVALENT COMPOUNDS) | None | Female reproductive toxin |
| CHROMIUM (HEXAVALENT COMPOUNDS) | None | Male reproductive toxin |
| CHROMIUM (HEXAVALENT COMPOUNDS) | None | Carcinogen |
| CHROMIUM (HEXAVALENT COMPOUNDS) | None | Developmental Toxin |

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None
Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 27-7243-2 | Version Number: | 9.02 |
| Issue Date: | 07/26/18 | Supersedes Date: | 01/04/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 27-7240-8
Issue Date: 07/26/18

Version Number: 8.02
Supersedes Date: 01/04/18

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchkote™ Liquid Epoxy Coating 323C Patch Compound, Part A

1.2. Recommended use and restrictions on use

Recommended use

Coating, Part A of 2 Part Liquid Epoxy Coating System

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Electrical Markets Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|------------|------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | 25068-38-6 | 60 - 70 Trade Secret * |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | 20 - 30 Trade Secret * |
| TITANIUM DIOXIDE | 13463-67-7 | 1 - 5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|--------------------------|-------------------|
| Aldehydes | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Chloride | During Combustion |
| Irritant Vapors or Gases | During Combustion |
| Ammonia | During Combustion |
| Oxides of Nitrogen | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid eye contact. Avoid breathing of vapors created during cure cycle. Avoid skin contact with hot material. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------------|-------------------|---------------|----------------------------------|--------------------------------|
| TITANIUM DIOXIDE | 13463-67-7 | ACGIH | TWA:10 mg/m3 | A4: Not class. as human carcin |
| TITANIUM DIOXIDE | 13463-67-7 | OSHA | TWA(as total dust):15 mg/m3 | |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | ACGIH | TWA(respirable fraction):2 mg/m3 | A4: Not class. as human carcin |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 | OSHA | TWA:2 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| General Physical Form: | Liquid |
| Specific Physical Form: | Viscous |
| Odor, Color, Grade: | Viscous, White |
| Odor threshold | No Data Available |
| pH | Not Applicable |
| Melting point | No Data Available |
| Boiling Point | > 200 °F |
| Flash Point | > 200 °F [Test Method: Tagliabue Closed Cup] |
| Evaporation rate | < 1 [Ref Std: BUOAC=1] |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | 0.01 mmHg [Test Method: Calculated] [Details: at 25C, Raoult's Law] |
| Vapor Density | > 1 [Ref Std: AIR=1] |
| Density | 1.425 g/ml |
| Specific Gravity | 1.425 [Ref Std: WATER=1] |
| Solubility In Water | No Data Available |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | 120,000 - 280,000 centipoise [@ 72 °F] [Test Method: Brookfield] |

Volatile Organic Compounds

12 g/l [Details: For coating mixture of Parts A and B]

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|-------------------|----------------|-------------------------------|---|
| TITANIUM DIOXIDE | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------------|----------------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Dermal | Rat | LD50 > 1,600 mg/kg |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Ingestion | Rat | LD50 > 1,000 mg/kg |
| HYDROUS MAGNESIUM SILICATE | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| HYDROUS MAGNESIUM SILICATE | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| TITANIUM DIOXIDE | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| TITANIUM DIOXIDE | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| TITANIUM DIOXIDE | Ingestion | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|----------------|---------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Rabbit | Mild irritant |
| HYDROUS MAGNESIUM SILICATE | Rabbit | No significant irritation |
| TITANIUM DIOXIDE | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|----------------|---------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Rabbit | Moderate irritant |
| HYDROUS MAGNESIUM SILICATE | Rabbit | No significant irritation |
| TITANIUM DIOXIDE | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|------------------|----------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Human and animal | Sensitizing |
| TITANIUM DIOXIDE | Human and | Not classified |

| | | |
|--|--------|--|
| | animal | |
|--|--------|--|

Respiratory Sensitization

| Name | Species | Value |
|---|---------|----------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Human | Not classified |
| HYDROUS MAGNESIUM SILICATE | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | In vivo | Not mutagenic |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| HYDROUS MAGNESIUM SILICATE | In Vitro | Not mutagenic |
| HYDROUS MAGNESIUM SILICATE | In vivo | Not mutagenic |
| TITANIUM DIOXIDE | In Vitro | Not mutagenic |
| TITANIUM DIOXIDE | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------|-------------------------|--|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| HYDROUS MAGNESIUM SILICATE | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| TITANIUM DIOXIDE | Ingestion | Multiple animal species | Not carcinogenic |
| TITANIUM DIOXIDE | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|-----------|--|---------|---------------------|----------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesis |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| HYDROUS MAGNESIUM SILICATE | Ingestion | Not classified for development | Rat | NOAEL 1,600 mg/kg | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|--------|-----------------|----------------|---------|-----------------------|-------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| 4,4'- | Dermal | nervous system | Not classified | Rat | NOAEL | 13 weeks |

| | | | | | | |
|--|------------|--|--|-------|-----------------------------|--------------------------|
| ISOPROPYLIDENEDIPH ENOL- EPICHLOROHYDRIN POLYMER | | | | | 1,000 mg/kg/day | |
| 4,4'- ISOPROPYLIDENEDIPH ENOL- EPICHLOROHYDRIN POLYMER | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| HYDROUS MAGNESIUM SILICATE | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| HYDROUS MAGNESIUM SILICATE | Inhalation | pulmonary fibrosis respiratory system | Not classified | Rat | NOAEL 18 mg/m3 | 113 weeks |
| TITANIUM DIOXIDE | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| TITANIUM DIOXIDE | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *2 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 27-7240-8
Issue Date: 07/26/18

Version Number: 8.02
Supersedes Date: 01/04/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com