



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-4961-8	Version Number:	3.02
Issue Date:	04/12/18	Supersedes Date:	04/10/18

SECTION 1: Identification

1.1. Product identifier

3M™ Finesse-It™ Polish - Final Finish 28796, 84224, 82877, 82878, 88753

1.2. Recommended use and restrictions on use

Recommended use

Polish, Industrial use

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Abrasive Systems Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

20% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	45 - 60
Aluminum Oxide Mineral	1344-28-1	10 - 20
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	64742-48-9	5 - 20
Glycerin	56-81-5	5 - 15
Petroleum Distillates	64742-14-9	5 - 10 Trade Secret *
Mineral Oil	8042-47-5	1 - 5

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid eye contact. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep from freezing. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Aluminum Oxide Mineral	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Glycerin	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Naphtha	64742-48-9	OSHA	TWA:400 mg/m3(100 ppm)	
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Odor, Color, Grade:	Light solvent odor, Gray Liquid
Odor threshold	<i>No Data Available</i>
pH	8.3 - 8.7
Melting point	<i>No Data Available</i>
Boiling Point	Approximately 212 °F
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	1 [Ref Std:ETHER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	1.00 [Ref Std:AIR=1]
Density	8.45 - 8.85 lb/gal
Specific Gravity	1.014 - 1.062 [Ref Std:WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	13,000 - 18,000 centipoise

Hazardous Air Pollutants*No Data Available***Molecular weight***No Data Available***VOC Less H₂O & Exempt Solvents**465 g/l [*Test Method: tested per EPA method 24*]**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

Carbon monoxide

Not Specified

Carbon dioxide

Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Petroleum Distillates	Dermal	Rabbit	LD50 > 2,000 mg/kg
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
Petroleum Distillates	Professional judgement	Mild irritant
Mineral Oil	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
Petroleum Distillates	Professional judgement	Mild irritant
Mineral Oil	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Glycerin	Guinea pig	Not classified
Petroleum Distillates	Guinea pig	Not classified
Mineral Oil	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral	In Vitro	Not mutagenic
Petroleum Distillates	In Vitro	Not mutagenic
Mineral Oil	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral	Inhalation	Rat	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide Mineral	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational

					available	exposure
Glycerin	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	Aspiration hazard
Petroleum Distillates	Aspiration hazard
Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Hazard Not Otherwise Classified (HNOC)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	34-4961-8	Version Number:	3.02
Issue Date:	04/12/18	Supersedes Date:	04/10/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com