



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 07-2674-5
Issue Date: 01/19/18

Version Number: 34.03
Supersedes Date: 08/09/16

SECTION 1: Identification

1.1. Product identifier

3M™ Anisotropic Conductive Film 7303

Product Identification Numbers

70-0000-8559-0, 70-0062-2961-4, 70-0063-3554-4, 70-0063-3595-7, 70-0063-3596-5, 70-0063-3597-3, 70-0063-3598-1, 70-0063-3648-4, 70-0063-3649-2, 70-0063-3650-0, 70-0064-1740-9, 70-0064-1746-6, 70-0064-1760-7, 70-0064-5719-9, 70-0064-5736-3, 70-0064-5737-1, 70-0064-5738-9, 70-0064-5739-7, 70-0064-5740-5, 70-0064-5918-7, 70-0064-6007-8, 70-0064-6127-4

1.2. Recommended use and restrictions on use

Recommended use

Bonding

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Electronics Materials Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

51% of the mixture consists of ingredients of unknown acute oral toxicity.

51% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-propenoic acid, 2-phenoxyethyl ester, homopolymer	34962-82-8	30 - 45
epoxy resin	25068-38-6	30 - 45 Trade Secret *
aliphatic amine	Trade Secret*	10 - 20
acrylate polymer	Trade Secret*	5 - 15
oxide glass chemicals	65997-17-3	2 - 5
siliver	7440-22-4	0.1 - 2 Trade Secret *
phenol	108-95-2	0 - 0.5

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin contact with hot material. For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this

product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
phenol	108-95-2	ACGIH	TWA:5 ppm	SKIN, A4: Not class. as human carcin
phenol	108-95-2	OSHA	TWA:19 mg/m3(5 ppm)	SKIN
siliver	7440-22-4	ACGIH	TWA(as dust and fume):0.1 mg/m3	
siliver	7440-22-4	OSHA	TWA(as Ag):0.01 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber
Fluoroelastomer

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

None required.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

General Physical Form:	Solid
Specific Physical Form:	Roll of Tape
Odor, Color, Grade:	Yellow/Tan Color
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	≥ 200 °F [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Density	1.2 g/cm ³
Specific Gravity	1.2 [<i>Ref Std</i> :WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Generic: GLASS FILAMENTS	65997-17-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
epoxy resin	Dermal	Rat	LD50 > 1,600 mg/kg
epoxy resin	Ingestion	Rat	LD50 > 1,000 mg/kg
acrylate polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
acrylate polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
siliver	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg

silver	Ingestion	Rat	LD50 > 2,000 mg/kg
phenol	Inhalation-Vapor		LC50 estimated to be 2 - 10 mg/l
phenol	Dermal	Rat	LD50 670 mg/kg
phenol	Ingestion	Rat	LD50 340 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
epoxy resin	Rabbit	Mild irritant
acrylate polymer	Professional judgment	Minimal irritation
oxide glass chemicals	Professional judgment	No significant irritation
phenol	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
epoxy resin	Rabbit	Moderate irritant
acrylate polymer	Professional judgment	Mild irritant
oxide glass chemicals	Professional judgment	No significant irritation
phenol	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
epoxy resin	Human and animal	Sensitizing
phenol	Guinea pig	Not classified

Respiratory Sensitization

Name	Species	Value
epoxy resin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
epoxy resin	In vivo	Not mutagenic
epoxy resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
phenol	In Vitro	Some positive data exist, but the data are not sufficient for classification
phenol	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
epoxy resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
phenol	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
phenol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
epoxy resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
epoxy resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
epoxy resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
epoxy resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
phenol	Ingestion	Not classified for development	Rat	NOAEL 120 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
phenol	Dermal	hematopoietic system	Causes damage to organs	Rat	LOAEL 108 mg/kg	not available
phenol	Dermal	heart nervous system kidney and/or bladder	Causes damage to organs	Rat	LOAEL 107 mg/kg	24 hours
phenol	Dermal	liver	Not classified	Human	NOAEL Not available	not available
phenol	Inhalation	respiratory irritation	May cause respiratory irritation	Multiple animal species	NOAEL Not available	not available
phenol	Ingestion	kidney and/or bladder	Causes damage to organs	Rat	NOAEL 120 mg/kg/day	not applicable
phenol	Ingestion	respiratory system	Causes damage to organs	Human	NOAEL not available	poisoning and/or abuse
phenol	Ingestion	endocrine system liver	Not classified	Rat	NOAEL 224 mg/kg	not applicable
phenol	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
epoxy resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
epoxy resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000	13 weeks

epoxy resin	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	mg/kg/day NOAEL 1,000 mg/kg/day	28 days
oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
phenol	Dermal	nervous system	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 260 mg/kg/day	18 days
phenol	Inhalation	heart liver kidney and/or bladder respiratory system	Causes damage to organs through prolonged or repeated exposure	Guinea pig	LOAEL 0.1 mg/l	41 days
phenol	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	LOAEL 0.1 mg/l	14 days
phenol	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
phenol	Inhalation	immune system	Not classified	Rat	NOAEL 0.1 mg/l	2 weeks
phenol	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 12 mg/kg/day	14 days
phenol	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Mouse	LOAEL 1.8 mg/kg/day	28 days
phenol	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 308 mg/kg/day	13 weeks
phenol	Ingestion	liver	Not classified	Rat	NOAEL 40 mg/kg/day	14 days
phenol	Ingestion	respiratory system	Not classified	Rat	LOAEL 40 mg/kg/day	14 days
phenol	Ingestion	immune system	Not classified	Mouse	NOAEL 1.8 mg/kg/day	28 days
phenol	Ingestion	endocrine system	Not classified	Rat	NOAEL 120 mg/kg/day	14 days
phenol	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Multiple animal species	NOAEL 1,204 mg/kg/day	103 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D011 (Silver)

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
siliver	7440-22-4	Trade Secret 0.1 - 2
siliver (Silver)	7440-22-4	0.1 - 2

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	07-2674-5	Version Number:	34.03
Issue Date:	01/19/18	Supersedes Date:	08/09/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com