

Highland™ Transparent Tape 5910

Technical Data

April, 2006

Product Description Highland™ Tape 5910 is a utility grade transparent tape designed for light-duty packaging applications, that is typically used for bag closing, temporary holding, and L-clip applications that do not put severe stress on the tape.

Construction	Backing	Adhesive
	Polypropylene film	Pressure sensitive acrylic

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

ASTM Test Method

Adhesion to Steel:	16 oz./in. width (17 N/100 mm width)	D-3330
Longitudinal Tensile Strength:	18 lbs./in. width (315 N/100 mm width)	D-3759
Elongation at Break:	90%	D-3759
Thickness - Backing:	1.4 mil (0.036 mm)	D-3652
Total:	2.0 mil (0.051 mm)	D-3652

Note: Highland™ Film Tapes have physical properties that vary over broader ranges than Scotch® Tapes.

Available Sizes	Standard Widths:	3/8 in., 1/2 in., 3/4 in. and 1 in.
	Core Size (ID):	3 in.
	Lengths:	2592 in.

Application Techniques An extensive line of manual dispensers is available to facilitate application of Highland tape 5910.

Storage Conditions Storage of tape at 70°F (21°C) and 40-50% relative humidity is recommended.

Highland™ Transparent Tape

5910

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.

3M

**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2006 70-0710-0230-0 (4/06)