

# **Material Safety Data Sheet**

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** EPS-200 HEAT SHRINK TUBING

**MANUFACTURER:** 3M

**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/30/09 Supercedes Date: Initial Issue

**Document Group:** 26-5668-4

**Product Use:** 

Intended Use: Electrical

Specific Use: Electrical insulation for wires and cables.

# **SECTION 2: INGREDIENTS**

Ingredient	C.A.S. No.	% by Wt
EVA COPOLYMER	24937-78-8	0 - 40
FLAME RETARDANT	Trade Secret	10 - 35
POLYMER	Trade Secret	10 - 25
ADDITIVE	Trade Secret	5 - 15
POLYMER WITH ETHENE	Trade Secret	5 - 15
ACID POLYMER	Trade Secret	5 - 15
PIGMENT	Trade Secret	1 - 15
INSULATOR	Trade Secret	1 - 10
VULCANIZATION CATALYST	Trade Secret	1 - 10
VULCANIZING AGENT	Trade Secret	1 - 10
BLEACHING AGENT	Trade Secret	1 - 10
RED PIGMENT	Trade Secret	0 - 5
COPOLYMER	25087-34-7	0 - 5
METAL DEACTIVATOR	Trade Secret	0 - 5
ANTIOXIDANT	Trade Secret	0 - 5
UV RESISTER	Trade Secret	0 - 5
LIMESTONE	Trade Secret	0 - 5
PLASTIC	Trade Secret	0 - 5
COLORING AGENT	Trade Secret	0 - 5

# **SECTION 3: HAZARDS IDENTIFICATION**

#### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: different lengths and diameters and colors of tubing

Odor, Color, Grade: Tubing, various sizes, colors

General Physical Form: Solid

Immediate health, physical, and environmental hazards:

## 3.2 POTENTIAL HEALTH EFFECTS

## **Eye Contact:**

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Skin Contact:**

No health effects are expected.

#### **Inhalation:**

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

## **Ingestion:**

No health effects are expected.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** No need for first aid is anticipated.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**If Swallowed:** No need for first aid is anticipated.

# **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNo Data AvailableFlash PointNo Data AvailableFlammable Limits - LELNo Data AvailableFlammable Limits - UELNo Data AvailableOSHA Flammability Classification:Not Applicable

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** See Hazardous Decomposition section for products of combustion. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Not applicable. No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Not applicable.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. Avoid skin contact with hot material. Do not breathe vapors. Avoid breathing of fumes. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Wash hands after handling and before eating. Avoid contact with oxidizing agents. For industrial or professional use only.

## 7.2 STORAGE

Store away from heat. Store in a cool, dry place.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

If exhaust ventilation is not available, use appropriate respiratory protection. Provide appropriate local exhaust when product is heated.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

## 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact with hot material. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

#### **8.2.3 Respiratory Protection**

Avoid breathing of fumes. Do not breathe vapors.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece air-purifying respirator with organic vapor/acid gas cartridges and P95 particulate prefilters. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

## 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

#### 8.3 EXPOSURE GUIDELINES

None Established

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Specific Physical Form:** different lengths and diameters and colors of tubing

Odor, Color, Grade: Tubing, various sizes, colors

General Physical Form: Solid

Autoignition temperatureNo Data AvailableFlash PointNo Data AvailableFlammable Limits - LELNo Data AvailableFlammable Limits - UELNo Data AvailableBoiling pointNot Applicable

Vapor Density Not Applicable

Vapor Pressure Not Applicable

Specific Gravity
No Data Available

Melting pointNo Data AvailableSolubility In WaterNot Applicable

Solubility in Water Ni

Volatile Organic CompoundsNot ApplicablePercent volatileNot ApplicableVOC Less H2O & Exempt SolventsNot ApplicableViscosityNot Applicable

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: None known

#### MATERIAL SAFETY DATA SHEET EPS-200 HEAT SHRINK TUBING 03/30/09

Hazardous Polymerization: Hazardous polymerization will not occur.

# **Hazardous Decomposition or By-Products**

<u>Substance</u> <u>Condition</u>

Aldehydes During Combustion
Carbon monoxide During Combustion
Carbon dioxide During Combustion
Hydrogen Chloride During Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### ECOTOXICOLOGICAL INFORMATION

Not determined.

## CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in the presence of a combustible material in an industrial or commercial facility capable of handling halogenated waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

#### **ID Number(s):**

80-6102-2017-2, 80-6102-2018-0, 80-6102-2019-8, 80-6102-2020-6, 80-6102-2021-4, 80-6102-2022-2, 80-6102-5117-7, 80-6103-2170-7, 80-6103-3560-8, 80-6103-3562-4, 80-6103-3563-2, 80-6106-4547-7, 80-6106-4548-5, 80-6106-4549-3, 80-6106-4550-1, 80-6106-4551-9, 80-6106-4552-7, 80-6106-4553-5, 80-6106-4586-5, 80-6106-4587-3, 80-6106-4588-1, 80-6106-4589-9, 80-6106-4590-7, 80-6106-4591-5, 80-6106-4592-3, 80-6106-4876-0, 80-6106-4997-4, 80-6106-7581-3, 80-6106-7950-0, 80-6106-7951-8, 80-6106-8979-8, 80-6106-9040-8, 80-6106-9100-0, 80-6106-9130-7, 80-6106-9350-1, 80-6106-9378-2, 80-6107-5102-8, 80-6107-5103-6, 80-6107-5104-4, 80-6107-5105-1, 80-6107-5399-0, 80-6107-5407-1, 80-6107-5409-7, 80-6107-5410-5, 80-6107-5411-3, 80-6107-5434-5, 80-6107-8481-3, 80-6107-8482-1, 80-6107-8483-9, 80-6107-8484-7, 80-6107-8485-4, 80-6107-8486-2, 80-6107-8487-0, 80-6107-8488-8, 80-6107-8489-6, 80-6107-8563-8, 80-6107-8767-5, 80-6107-8768-3, 80-6107-8769-1, 80-6107-8770-9, 80-6107-8771-7, 80-6107-8772-5, 80-6107-8773-3, 80-6107-8774-1, 80-6107-8775-8, 80-6108-1974-2, 80-6108-2039-3, 80-6108-2054-2, 80-6108-2415-5, 80-6108-2416-3, 80-6108-2468-4, 80-6109-0696-0, 80-6109-0697-8, 80-6109-0698-6, 80-6110-0355-1, 80-6110-0360-1, 80-6109-0769-5, 80-6109-0783-6, 80-6109-0783-6, 80-6109-0595-5, 80-6109-5594-7, 80-6110-0355-1, 80-6110-0360-1, 80-6109-0769-5, 80-6109-0783-6, 80-6109-0783-6, 80-6109-0595-5, 80-6109-5594-7, 80-6110-0355-1, 80-6110-0360-1, 80-6109-0769-5, 80-6109-0783-6, 80-6109-0783-6, 80-6109-0595-5, 80-6109-5594-7, 80-6110-0355-1, 80-6110-0360-1, 80-6109-0769-5, 80-6109-0769-5, 80-6109-0769-5, 80-6109-0783-6, 80-6109-0595-5, 80-6109-5594-7, 80-6110-0355-1, 80-6110-0360-1, 80-6109-0769-5, 80-6109-0769

#### MATERIAL SAFETY DATA SHEET EPS-200 HEAT SHRINK TUBING 03/30/09

6110-0408-8, 80-6110-0439-3, 80-6110-0461-7, 80-6110-0534-1, 80-6110-0535-8, 80-6110-0536-6, 80-6110-7037-8, 80-6110-7039-4, 80-6110-7063-4, 80-6110-7064-2, 80-6110-7065-9, 80-6110-7066-7, 80-6110-7067-5, 80-6110-7068-3, 80-6110-7069-1, 80-6110-7070-9, 80-6110-7147-5, 80-6110-7223-4, 80-6110-7224-2, 80-6110-7227-5, 80-6110-7351-3, 80-6110-7355-4, 80-6110-7428-9, 80-6110-7482-6, 80-6110-7857-9, 80-6110-7858-7, 80-6110-7883-5, 80-6110-7891-8, 80-6110-7898-3, 80-6110-7915-5, 80-6112-6847-7, 80-6112-6866-7, 80-6112-6899-8, 80-6112-6962-4, 80-6112-6982-2, 80-6114-2452-6, 80-6114-2453-4, 80-6114-2753-7, 80-6114-3160-4, 80-6114-3516-7, 80-6114-3520-9, 80-6114-3653-8, 80-6114-3654-6, 80-6114-3772-6, 80-6114-4056-3, 80-6114-4143-9

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

### US FEDERAL REGULATIONS

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

## Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
PIGMENT (ANTIMONY COMPOUNDS)	Trade Secret	1 - 15
VULCANIZATION CATALYST (ZINC	Trade Secret	1 - 10
COMPOUNDS)		

### STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

#### INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

No revision information is available.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com