



Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	27-1614-0	Version Number:	2.03
Issue Date:	10/15/20	Supersedes Date:	01/18/18

SECTION 1: Identification

1.1. Product identifier

3M(TM) Sealant 730 UV, Clear

Product Identification Numbers

ID Number	UPC	ID Number	UPC
62-5292-3930-3		62-5292-3935-2	
62-5292-5230-6		62-5292-5235-5	

7100003045, 7000121507

1.2. Recommended use and restrictions on use

Recommended use

Sealant

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.
 Skin Corrosion/Irritation: Category 2.
 Skin Sensitizer: Category 1.
 Reproductive Toxicity: Category 1B.
 Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Causes serious eye damage.
 Causes skin irritation.
 May cause an allergic skin reaction.
 May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:
 respiratory system |

Precautionary Statements

Prevention:

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wear protective gloves and eye/face protection.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF ON SKIN: Wash with plenty of soap and water.
 Immediately call a POISON CENTER or doctor/physician.
 If skin irritation or rash occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyether (NJTS Reg. No. 04499600-6767)	Trade Secret*	50 - 70
CALCIUM CARBONATE	471-34-1	15 - 25
Fumed Silica	68611-44-9	10 - 20
Organofunctional Silane Ester (NJTS Reg. No. 04499600-6769)	Trade Secret*	1 - 20
Plasticizer (NJTS Reg. No. 04499600-6768)	Trade Secret*	5 - 15
Organosilane (NJTS Reg. No. 04499600-6770)	Trade Secret*	1 - 10
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	1760-24-3	0.5 - 2

Dibutyltin Oxide	818-08-6	< 1
DIISOOCTYL PHTHALATE	27554-26-3	< 1
Hindered Amine	63843-89-0	<= 0.2

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Irritant Vapors or Gases
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Limestone	471-34-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
SILICA, AMORPHOUS	68611-44-9	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
TIN, ORGANIC COMPOUNDS	818-08-6	ACGIH	TWA(as Sn):0.1 mg/m3;STEL(as Sn):0.2 mg/m3	A4: Not class. as human carcin, Danger of cutaneous absorption
TIN, ORGANIC COMPOUNDS	818-08-6	OSHA	TWA(as Sn):0.1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Solid
Yellow

Specific Physical Form:

Paste

Odor

Mild Odor, Sweet Odor

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

Not Applicable

Flash Point

> 200 °F [Test Method:Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

Negligible

Vapor Density

No Data Available

Density

1.05 g/ml

Specific Gravity

1.05

Solubility in Water	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	450,000 centipoise
Hazardous Air Pollutants	0 % weight [<i>Test Method:Calculated</i>]
Molecular weight	No Data Available
Volatile Organic Compounds	1.0 % [<i>Test Method:tested per EPA method 24</i>]
VOC Less H2O & Exempt Solvents	11 g/l [<i>Test Method:tested per EPA method 24</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether (NJTS Reg. No. 04499600-6767)	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyether (NJTS Reg. No. 04499600-6767)	Ingestion	Rat	LD50 5,000 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
Fumed Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation-Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Rat	LD50 1,897 mg/kg
Dibutyltin Oxide	Dermal	Rat	LD50 > 2,000 mg/kg
Dibutyltin Oxide	Ingestion	Rat	LD50 164 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
CALCIUM CARBONATE	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Mild irritant
Dibutyltin Oxide	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
CALCIUM CARBONATE	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Corrosive
Dibutyltin Oxide	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Fumed Silica	Human and animal	Not classified
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Multiple animal species	Sensitizing
Dibutyltin Oxide	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Fumed Silica	In Vitro	Not mutagenic
Dibutyltin Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dibutyltin Oxide	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Fumed Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Fumed Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Dibutyltin Oxide	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	prematuring into lactation
Dibutyltin Oxide	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

Dibutyltin Oxide	Ingestion	immune system	Causes damage to organs	Rat	LOAEL 5 mg/kg	
------------------	-----------	---------------	-------------------------	-----	---------------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Fumed Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.015 mg/l	90 days
Dibutyltin Oxide	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	2 weeks
Dibutyltin Oxide	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable
Health Hazards
Reproductive toxicity
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation
Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	27-1614-0	Version Number:	2.03
Issue Date:	10/15/20	Supersedes Date:	01/18/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available

directly from 3M.

3M USA SDSs are available at www.3M.com

