

Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:FP-301 BLACK HEAT SHRINK TUBING**MANUFACTURER:**3M**DIVISION:**Electrical Markets Division

ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/24/09 **Supercedes Date:** 10/01/08

Document Group: 06-2459-3

Product Use:

Intended Use:ElectricalSpecific Use:Electrical insulation for wires/cables

SECTION 2: INGREDIENTS

Ingredient	<u>C.A.S. No.</u>	<u>% by Wt</u>
COPOLYMER	Trade Secret	50 - 60
BISETHANE	Trade Secret	20 - 25
ANTIMONY TRIOXIDE	1309-64-4	10 - 15
AMORPHOUS SILICA	Trade Secret	1 - 5
CARBON BLACK	1333-86-4	< 2

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Black tubing, various sizes, odorless

General Physical Form: Solid

Immediate health, physical, and environmental hazards: Contact with aluminum or zinc in a pressurized system may generate hydrogen gas which could create an explosion hazard.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion: No health effects are expected.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. If exposed to vapors or smoke, immediately flush eyes with large amounts of water. Get immediate medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL OSHA Flammability Classification: No Data Available No Data Available No Data Available No Data Available Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

MATERIAL SAFETY DATA SHEET FP-301 BLACK HEAT SHRINK TUBING 03/24/09

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Contact with aluminum or zinc in a pressurized system may generate hydrogen gas which could create an explosion hazard.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Not applicable.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. Avoid skin contact with hot material. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Do not ingest. For industrial or professional use only.

7.2 STORAGE

Store away from heat. Store in a cool, dry place.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust when product is heated.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors or smoke resulting from overheating or when used in confined areas.

8.2.2 Skin Protection

Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns. Avoid skin contact with hot material.

8.2.3 Respiratory Protection

Avoid breathing of fumes.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface supplied-air respirator. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Not applicable.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
ANTIMONY COMPOUNDS	ACGIH	TWA, as Sb	0.5 mg/m3	
ANTIMONY COMPOUNDS	OSHA	TWA, as Sb	0.5 mg/m3	Table Z-1A
ANTIMONY TRIOXIDE	ACGIH	TWA, as Sb	0.5 mg/m3	
ANTIMONY TRIOXIDE	CMRG	TWA, as Sb	0.2 mg/m3	
CARBON BLACK	ACGIH	TWA	3.5 mg/m3	Table A4
CARBON BLACK	CMRG	TWA	0.5 mg/m3	
CARBON BLACK	OSHA	TWA	3.5 mg/m3	Table Z-1
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4

SOURCE OF EXPOSURE LIMIT DATA: ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odan Calan Crada	Diastrubing verieus sizes adortass		
Odor, Color, Grade:	Black tubing, various sizes, odorless		
General Physical Form:	Solid		
Autoignition temperature	No Data Available		
Flash Point	No Data Available		
Flammable Limits - LEL	No Data Available		
Flammable Limits - UEL	No Data Available		
Boiling point	No Data Available		
Density	No Data Available		
Vapor Density	Not Applicable		
Vapor Density	Not Applicable		
Vapor Pressure	Not Applicable		
Vapor Pressure	Not Applicable		
Specific Gravity	No Data Available		
рН	Not Applicable		
Melting point	No Data Available		
Solubility In Water	Not Applicable		
Solubility in Water	Not Applicable		
Evaporation rate	Not Applicable		
Volatile Organic Compounds	Not Applicable		
Percent volatile	Not Applicable		
VOC Less H2O & Exempt Solvents	Not Applicable		
Viscosity	Not Applicable		

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Reactive metals; High shear and high temperature conditions

MATERIAL SAFETY DATA SHEET FP-301 BLACK HEAT SHRINK TUBING 03/24/09

Avoid overheating to decomposition during application, irritating or toxic fumes may result.

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Bromide	During Combustion
Oxides of Antimony	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion
Oxides of Zinc	During Combustion

Hazardous Decomposition: Heating product beyond temperature recommended by instruction sheet may cause release of the following compounds: Benzene, Toluene, Formaldehyde, Acetaldehyde, and Hydrogen Bromide.

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not applicable.

CHEMICAL FATE INFORMATION

Not applicable.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in the presence of a combustible material in an industrial or commercial facility capable of handling halogenated waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

78-8126-6258-9, 78-8126-6259-7, 78-8126-6260-5, 78-8126-6261-3, 80-6102-1904-2, 80-6102-1934-9, 80-6102-1940-6, 80-6102-1946-3, 80-6102-1953-9, 80-6102-2030-5, 80-6102-2034-7, 80-6102-2038-8, 80-6102-2726-8, 80-6102-2729-2, 80-6102-2733-4, 80-6102-2736-7, 80-6102-2759-9, 80-6102-2760-7, 80-6102-2761-5, 80-6102-2763-1, 80-6102-2878-7, 80-6102-2906-6, 80-6102-2909-0, 80-6102-3429-8, 80-6102-3452-0, 80-6102-3522-0, 80-6102-3545-1, 80-6102-3836-4, 80-6102-3884-4, 80-6102-5193-8, 80-6102-519-8, 80-6102-519-8, 80-6102-519-8, 80-6102-519-8, 80-6102-519-8, 8

MATERIAL SAFETY DATA SHEET FP-301 BLACK HEAT SHRINK TUBING 03/24/09

5194-6, 80-6102-5195-3, 80-6102-5196-1, 80-6105-4585-9, 80-6106-4519-6, 80-6106-4520-4, 80-6106-4521-2, 80-6106-4643-4, 80-6106-4769-7, 80-6106-4817-4, 80-6106-7531-8, 80-6106-7568-0, 80-6106-7808-0, 80-6106-9072-1, 80-6106-9328-7, 80-6106-9332-9, 80-6106-9333-7, 80-6107-5214-1, 80-6107-5220-8, 80-6107-5226-5, 80-6107-5232-3, 80-6107-5313-1, 80-6107-5452-7, 80-6107-6663-8, 80-6107-6743-8, 80-6107-6760-2, 80-6107-6766-9, 80-6107-6933-5, 80-6107-6934-3, 80-6107-8420-1, 80-6107-8429-2, 80-6107-8477-1, 80-6107-8574-5, 80-6107-8581-0, 80-6107-8588-5, 80-6107-8595-0, 80-6107-8671-9, 80-6107-8678-4, 80-6107-8685-9, 80-6107-8692-5, 80-6107-8741-0, 80-6107-8743-6, 80-6107-8744-4, 80-6107-8745-1, 80-6108-1904-9, 80-6108-1930-4, 80-6108-2081-5, 80-6108-5415-2, 80-6108-5417-8, 80-6108-5419-4, 80-6108-5421-0, 80-6109-0693-7, 80-6109-5700-5, 80-6109-5788-0, 80-6109-5976-1, 80-6109-5977-9, 80-6110-0131-6, 80-6110-0281-9, 80-6110-7166-5, 80-6110-7249-9, 80-6110-7338-0, 80-6110-7483-4, 80-6110-7820-7, 80-6110-7838-9, 80-6110-7840-5, 80-6110-7844-7, 80-6110-7854-6, 80-6110-7896-7, 80-6112-6398-1, 80-6112-6838-6, 80-6114-1910-4, 80-6114-1999-7, 80-6114-2629-9, 80-6114-2629-9, 80-6114-2732-1, 80-6114-2746-1, 80-6114-3137-2, 80-6114-3138-0, 80-6114-3147-1, 80-6114-3703-1, A0-6107-6749-5

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
ANTIMONY TRIOXIDE (ANTIMONY	1309-64-4	10 - 15
COMPOUNDS)		

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

Additional Information: See Section 4 for Hazardous Decomposition Products.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

- Copyright was modified.
- Section 7: Handling information was modified.
- Section 7: Storage information was modified.
- Section 13: Waste disposal method information was modified.
- Section 3: Carcinogenicity phrase was deleted.
- Section 3: Immediate other hazard(s) was deleted.
- Section 4: First aid for inhalation none was deleted.
- Section 3: Carcinogenicity table was deleted.
- Section 3: Carcinogenicity heading was deleted.
- Section 15: California proposition 65 ingredient information was deleted.
- Section 15: California proposition 65 heading was deleted.
- Section 15: California proposition 65 cancer warning was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com