

# **Safety Data Sheet**

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	30-3799-1	Version Number:	3.01
Issue Date:	10/25/17	Supercedes Date:	06/13/17

#### **Product identifier**

3M<sup>™</sup> Surface Pre-Treatment AC-130-2

### **ID** Number(s):

70-0052-0012-9, 70-0052-0013-7, 70-0052-0016-0, 70-0052-0017-8, 70-0052-0018-6, 70-0052-0019-4, 70-0052-0773-6, 70-0052-2083-8, 70-0052-2084-6, 70-0052-2085-3, 70-0052-2086-1, 70-0052-2087-9, 70-0052-2088-7, 70-0052-2100-0, 70-0052-2101-8, 70-0052-2102-6, 70-0052-2103-4, 70-0052-2104-2, 70-0052-2105-9, 70-0052-2106-7, 70-0052-2107-5, 70-0052-2108-3, 70-0052-2109-1

#### Recommended use

Metal Adhesion Promoter

#### Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

**Emergency telephone number** 1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

#### 30-3802-3, 30-3803-1

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may

#### 3M<sup>TM</sup> Surface Pre-Treatment AC-130-2 10/25/17

have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

### 3M USA SDSs are available at www.3M.com



# Safety Data Sheet

#### Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	30-3802-3	Version Number:	3.00
Issue Date:	05/22/18	Supercedes Date:	05/08/17

# **SECTION 1: Identification**

## 1.1. Product identifier

3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part A

#### **Product Identification Numbers**

LC-B100-1104-5, LC-B100-1104-6, LC-B100-1104-7, LC-B100-1104-8, LC-B100-1148-4, LC-B100-1148-5

#### 1.2. Recommended use and restrictions on use

**Recommended use** Part A of Metal Adhesion Promoter, For industrial or professional use only.

1.3. Supplier's details	
MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

**1.4. Emergency telephone number** 

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements Signal word Not applicable.

**Symbols** Not applicable.

Pictograms

Not applicable.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	98 - 99
ZIRCONIUM N-PROPOXIDE	23519-77-9	< 1
ACETIC ACID	64-19-7	< 0.5 Trade Secret *
PROPYL ALCOHOL	71-23-8	< 0.5

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

No need for first aid is anticipated.

### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

No need for first aid is anticipated.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide

# **Condition**

During Combustion During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or

#### 3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part A 05/22/18

exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid release to the environment.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

#### **8.1.** Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ZIRCONIUM COMPOUNDS	23519-77-9	ACGIH	TWA(as Zr):5	A4: Not class. as human
			mg/m3;STEL(as Zr):10 mg/m3	carcin
ZIRCONIUM COMPOUNDS	23519-77-9	OSHA	TWA(as Zr):5 mg/m3	
ACETIC ACID	64-19-7	ACGIH	TWA:10 ppm;STEL:15 ppm	
ACETIC ACID	64-19-7	OSHA	TWA:25 mg/m3(10 ppm)	
PROPYL ALCOHOL	71-23-8	ACGIH	TWA:100 ppm	A4: Not class. as human
				carcin
PROPYL ALCOHOL	71-23-8	OSHA	TWA:500 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **8.2. Exposure controls**

#### **8.2.1.** Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### **8.2.2.** Personal protective equipment (PPE)

#### Eye/face protection

None required.

## **Skin/hand protection**

No chemical protective gloves are required.

### **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

1.1. Information on basic physical and chemical pro	operties
General Physical Form:	Liquid
Odor, Color, Grade:	Vinegar-like odor; Clear liquid
Odor threshold	No Data Available
рН	3.5 - 4
Melting point	No Data Available
Boiling Point	No Data Available
Flash Point	>=200 °F [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density	No Data Available
Specific Gravity	1.0 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Complete
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	No Data Available
Molecular weight	No Data Available
VOC Less H2O & Exempt Solvents	530.2 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

# 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

# 10.6. Hazardous decomposition products

# **Substance**

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

No health effects are expected.

### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

No known health effects.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ACETIC ACID	Dermal	Rabbit	LD50 1,060 mg/kg
ACETIC ACID	Inhalation- Vapor (4 hours)	Rat	LC50 11.4 mg/l
ACETIC ACID	Ingestion	Rat	LD50 3,310 mg/kg
PROPYL ALCOHOL	Dermal	Rabbit	LD50 4,000 mg/kg
PROPYL ALCOHOL	Inhalation- Vapor (4 hours)	Rat	LC50 > 34 mg/l
PROPYL ALCOHOL	Ingestion	Rat	LD50 estimated to be 2,000 - 5,000 mg/kg

ATE = acute toxicity estimate

### **Skin Corrosion/Irritation**

Name	Species	Value
ACETIC ACID	Rabbit	Corrosive
PROPYL ALCOHOL	Rabbit	Minimal irritation

# Serious Eye Damage/Irritation

Name	Species	Value
ZIRCONIUM N-PROPOXIDE	Professio	Mild irritant
	nal	
	judgeme	
	nt	
ACETIC ACID	Rabbit	Corrosive
PROPYL ALCOHOL	Rabbit	Severe irritant

## **Skin Sensitization**

Name	Species	Value
PROPYL ALCOHOL	Guinea	Not classified
	pig	

# **Respiratory Sensitization**

Name	Species	Value
ACETIC ACID	Human	Not classified

# Germ Cell Mutagenicity

Name	Route	Value
ACETIC ACID	In Vitro	Not mutagenic
PROPYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification

# Carcinogenicity

Name	Route	Species	Value
ACETIC ACID	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
ACETIC ACID	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
PROPYL ALCOHOL	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

# **Reproductive Toxicity**

# **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
ACETIC ACID	Ingestion	Not classified for development	Rat	NOAEL 80 mg/kg/day	during gestation
PROPYL ALCOHOL	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.6 mg/l	6 weeks
PROPYL ALCOHOL	Inhalation	Not classified for development	Rat	NOAEL 8.6 mg/l	during gestation

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ZIRCONIUM N- PROPOXIDE	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
ACETIC ACID	Inhalation	respiratory system	Causes damage to organs	Human	NOAEL Not available	not applicable
ACETIC ACID	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
ACETIC ACID	Ingestion	blood   kidney and/or bladder	Causes damage to organs	Human	NOAEL Not available	not applicable
PROPYL ALCOHOL	Inhalation	central nervous	May cause drowsiness or	Mouse	NOAEL 5	4 hours

#### 3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part A 05/22/18

		system depression	dizziness		mg/l	
PROPYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the	Mouse	NOAEL Not	
			data are not sufficient for		available	
			classification			
PROPYL ALCOHOL	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	
		system depression	dizziness	nal	available	
				judgeme		
				nt		

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PROPYL ALCOHOL	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 70 mg/kg/day	83 weeks
PROPYL ALCOHOL	Ingestion	liver	Not classified	Rat	LOAEL 70 mg/kg/day	83 weeks

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

### EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### **15.1. US Federal Regulations**

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

Physical Hazards Not applicable

### Health Hazards

Not applicable

#### 15.2. State Regulations

Contact 3M for more information.

#### **15.3.** Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	30-3802-3	Version Number:	3.00
Issue Date:	05/22/18	Supercedes Date:	05/08/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

#### 3M USA SDSs are available at www.3M.com



# Safety Data Sheet

#### Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	30-3803-1	Version Number:	4.00
Issue Date:	05/22/18	Supercedes Date:	06/13/17

# **SECTION 1: Identification**

## 1.1. Product identifier

3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part B

### **Product Identification Numbers**

LC-B100-1104-9, LC-B100-1105-0, LC-B100-1105-1, LC-B100-1105-2, LC-B100-1148-6, LC-B100-1148-7, 42-0044-2187-3

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Part B of Metal Adhesion Promoter, For industrial or professional use only.

1.3. Supplier's details	
<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

**1.4. Emergency telephone number** 1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1. Reproductive Toxicity: Category 2. Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements Signal word Danger

Symbols Corrosion | Health Hazard |

#### Pictograms



Hazard Statements Causes serious eye damage. Suspected of damaging fertility or the unborn child.

Causes damage to organs: sensory organs |

### **Precautionary Statements**

### **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. Specific treatment (see Notes to Physician on this label).

### Storage:

Store locked up.

### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### Notes to Physician:

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL	2530-83-8	97 - 100 Trade Secret *
ETHER		
METHYL ALCOHOL	67-56-1	0 - 3 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	
Formaldehyde	
Carbon monoxide	
Carbon dioxide	

<u>Condition</u> During Combustion During Combustion During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially

#### 3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part B 05/22/18

available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
METHYL ALCOHOL	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	SKIN
METHYL ALCOHOL	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

3M <sup>™</sup> Surface Pre-Treatment AC-130-2 Part B	05/22/18
---	----------

Gloves made from the following material(s) are recommended: Butyl Rubber Polymer laminate

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Odor, Color, Grade:	Clear liquid; slight odor
Odor threshold	No Data Available
рН	Not Applicable
Melting point	No Data Available
Boiling Point	120 °C [@ 2 mmHg]
Flash Point	>=200 °F [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	2 mmHg [@ 120 °C]
Vapor Density	8.1 [@ 20 °C] [ <i>Ref Std</i> :AIR=1]
Density	1.07 g/ml
Specific Gravity	1.07 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Complete [Details: Reacts with water.]
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	231 °C
Decomposition temperature	No Data Available
Viscosity	No Data Available
Molecular weight	No Data Available
Volatile Organic Compounds	21.4 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
VOC Less H2O & Exempt Solvents	21.4 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

# **10.2.** Chemical stability

Stable.

# **10.3.** Possibility of hazardous reactions

Hazardous polymerization will not occur.

# **10.4. Conditions to avoid** Heat

3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part B 05/22/18

**10.5. Incompatible materials** Strong oxidizing agents Amines

# 10.6. Hazardous decomposition products <u>Substance</u>

None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

### Skin Contact:

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. May cause additional health effects (see below).

### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### **Additional Health Effects:**

### Single exposure may cause target organ effects:

May cause blindness.

### **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Dermal	Rabbit	LD50 4,000 mg/kg
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Rat	LD50 7,010 mg/kg
METHYL ALCOHOL	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
METHYL ALCOHOL	Inhalation- Vapor		LC50 estimated to be 10 - 20 mg/l
METHYL ALCOHOL	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Mild irritant
METHYL ALCOHOL	Rabbit	Mild irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Corrosive
METHYL ALCOHOL	Rabbit	Moderate irritant

#### **Skin Sensitization**

Name	Species	Value
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Guinea	Not classified
	pig	
METHYL ALCOHOL	Guinea	Not classified
	pig	

#### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	In vivo	Not mutagenic
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
METHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
METHYL ALCOHOL	In vivo	Some positive data exist, but the data are not
		sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Dermal	Mouse	Not carcinogenic
METHYL ALCOHOL	Inhalation	Multiple	Not carcinogenic
		animal	
		species	

#### **Reproductive Toxicity**

#### **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesi s
METHYL ALCOHOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
METHYL ALCOHOL	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesi s
METHYL ALCOHOL	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesi s

### Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ALCOHOL	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
METHYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
METHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
METHYL ALCOHOL	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
METHYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
3- (TRIMETHOXYSILYL)P ROPYL GLYCIDYL ETHER	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
METHYL ALCOHOL	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
METHYL ALCOHOL	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
METHYL ALCOHOL	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

# on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

# **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# **15.1. US Federal Regulations**

Contact 3M for more information.

# EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Reproductive toxicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u> METHYL ALCOHOL <u>C.A.S. No</u>

 $\frac{\text{$ **6 by Wt}}{\text{Trade Secret}} \quad 0 - 3** 

### 15.2. State Regulations

### 3M<sup>™</sup> Surface Pre-Treatment AC-130-2 Part B 05/22/18

Contact 3M for more information.

#### **California Proposition 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	Listing
METHYL ALCOHOL	67-56-1	Developmental Toxin

#### **15.3.** Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### **15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	30-3803-1	Version Number:	4.00
Issue Date:	05/22/18	Supercedes Date:	06/13/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

#### 3M USA SDSs are available at www.3M.com