



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	35-1661-4	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	05/23/18	<b>Supersedes Date:</b>	07/25/17

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Electrical Insulating Sealer 1601-C, Clear

#### Product Identification Numbers

80-6116-1660-0

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Electrical

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Electrical Markets Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Aerosol: Category 2.  
Gas Under Pressure: Liquefied gas.  
Serious Eye Damage/Irritation: Category 2A.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 2.  
Simple Asphyxiant.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:  
cardiovascular system |

May cause damage to organs:  
respiratory system |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

13% of the mixture consists of ingredients of unknown acute oral toxicity.

42% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	33 - 35 Trade Secret *
Methyl Ethyl Ketone	78-93-3	24 - 26 Trade Secret *
Propane	74-98-6	12 - 14 Trade Secret *
Butane	106-97-8	11 - 13 Trade Secret *
Resin Epoxy Ester	Trade Secret*	5 - 10 Trade Secret *
BISPHENOL A-FORMALDEHYDE RESIN	25085-75-0	2 - 5 Trade Secret *
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	6846-50-0	2 - 4 Trade Secret *
MIBK	108-10-1	1 - 3 Trade Secret *
N-Butyl Acetate	123-86-4	1 - 3 Trade Secret *
Ca 2-Ethylhexanoate	136-51-6	0 - 1 Trade Secret *
Zirconium Alkonate	22464-99-9	0 - 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

### SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Butane	106-97-8	ACGIH	STEL:1000 ppm	
MIBK	108-10-1	ACGIH	TWA:20 ppm;STEL:75 ppm	A3: Confirmed animal carcin.
MIBK	108-10-1	OSHA	TWA:410 mg/m3(100 ppm)	
N-Butyl Acetate	123-86-4	ACGIH	TWA:50 ppm;STEL:150 ppm	
N-Butyl Acetate	123-86-4	OSHA	TWA:710 mg/m3(150 ppm)	
ZIRCONIUM COMPOUNDS	22464-99-9	ACGIH	TWA(as Zr):5 mg/m3;STEL(as Zr):10 mg/m3	A4: Not class. as human carcin
ZIRCONIUM COMPOUNDS	22464-99-9	OSHA	TWA(as Zr):5 mg/m3	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	
Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
Methyl Ethyl Ketone	78-93-3	OSHA	TWA:590 mg/m3(200 ppm)	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Aerosol
Odor, Color, Grade:	Clear, MEK odor
Odor threshold	No Data Available
pH	No Data Available
Melting point	Not Applicable
Boiling Point	No Data Available
Flash Point	-20.2 °F [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	5.6 [Ref Std:BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1.38 %
Flammable Limits(UEL)	16 %
Vapor Pressure	13.5 kPa
Vapor Density	1.55 [Ref Std:AIR=1]
Density	6.15 lb/gal
Solubility In Water	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	<=20.5 centistoke

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

### 10.5. Incompatible materials

Not determined

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

May be harmful if inhaled.

Intentional concentration and inhalation may be harmful or fatal.

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
MIBK	108-10-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	Dermal	Guinea pig	LD50 > 18,800 mg/kg
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 8 mg/l
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	Ingestion	Rat	LD50 > 3,200 mg/kg
MIBK	Dermal	Rabbit	LD50 > 16,000 mg/kg
MIBK	Inhalation-Vapor (4 hours)	Rat	LC50 >8.2,<16.4 mg/l
MIBK	Ingestion	Rat	LD50 3,038 mg/kg
N-Butyl Acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-Butyl Acetate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.4 mg/l
N-Butyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 20 mg/l
N-Butyl Acetate	Ingestion	Rat	LD50 > 8,800 mg/kg
Ca 2-Ethylhexanoate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Ca 2-Ethylhexanoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
Ca 2-Ethylhexanoate	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

<b>Name</b>	<b>Species</b>	<b>Value</b>
Methyl Acetate	Rabbit	No significant irritation
Methyl Ethyl Ketone	Rabbit	Minimal irritation



Propane	Rabbit	Minimal irritation
Butane	Professional judgement	No significant irritation
MIBK	Rabbit	Mild irritant
N-Butyl Acetate	Rabbit	Minimal irritation
Ca 2-Ethylhexanoate	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Methyl Ethyl Ketone	Rabbit	Severe irritant
Propane	Rabbit	Mild irritant
Butane	Rabbit	No significant irritation
MIBK	Rabbit	Mild irritant
N-Butyl Acetate	Rabbit	Moderate irritant
Ca 2-Ethylhexanoate	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
Methyl Acetate	Human	Not classified
MIBK	Guinea pig	Not classified
N-Butyl Acetate	Multiple animal species	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic
Butane	In Vitro	Not mutagenic
MIBK	In Vitro	Not mutagenic
N-Butyl Acetate	In Vitro	Not mutagenic
Ca 2-Ethylhexanoate	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
MIBK	Inhalation	Multiple animal species	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
MIBK	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
MIBK	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000	13 weeks

				mg/kg/day	
MIBK	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
MIBK	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
N-Butyl Acetate	Inhalation	Not classified for female reproduction	Rat	NOAEL 7.1 mg/l	prematuring & during gestation
N-Butyl Acetate	Inhalation	Not classified for development	Rat	NOAEL 7.1 mg/l	prematuring & during gestation
Ca 2-Ethylhexanoate	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
Ca 2-Ethylhexanoate	Ingestion	Toxic to male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
Ca 2-Ethylhexanoate	Ingestion	Toxic to development	Rat	NOAEL 100 mg/kg/day	1 generation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Butane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
Butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	
MIBK	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours

MIBK	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL 0.9 mg/l	7 minutes
MIBK	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
MIBK	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
N-Butyl Acetate	Inhalation	respiratory system	May cause damage to organs	Rat	LOAEL 2.6 mg/l	4 hours
N-Butyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
N-Butyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	not available
N-Butyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Ca 2-Ethylhexanoate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Methyl Ethyl Ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver   kidney and/or bladder   heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Butane	Inhalation	kidney and/or bladder   blood	Not classified	Rat	NOAEL 4,489 ppm	90 days
MIBK	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
MIBK	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
MIBK	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
MIBK	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
MIBK	Inhalation	endocrine system   hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
MIBK	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
MIBK	Ingestion	endocrine system	Not classified	Rat	NOAEL	13 weeks

		hematopoietic system   liver   kidney and/or bladder			1,000 mg/kg/day	
MIBK	Ingestion	heart   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days
N-Butyl Acetate	Inhalation	olfactory system	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
N-Butyl Acetate	Inhalation	liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 7.26 mg/l	13 days

**Aspiration Hazard**

Name	Value
MIBK	Some positive data exist, but the data are not sufficient for classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D035 (Methyl ethyl ketone)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

**Health Hazards**

Carcinogenicity

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):****Ingredient**

MIBK

**C.A.S. No**

108-10-1

**% by Wt**

Trade Secret 1 - 3

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65****Ingredient**

MIBK

MIBK

**C.A.S. No.**

108-10-1

108-10-1

**Listing**

Carcinogen

Developmental Toxin

**15.3. Chemical Inventories**

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.
---

**SECTION 16: Other information****NFPA Hazard Classification****Health: 2 Flammability: 4 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 35-1661-4  
**Issue Date:** 05/23/18

**Version Number:** 3.00  
**Supersedes Date:** 07/25/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**