



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	18-1856-6	Version Number:	7.02
Issue Date:	06/27/23	Supersedes Date:	01/10/23

Product identifier

3M™ Lightweight Body Filler - PN 05800, 05801, 05803, 05804, 05805, 35801

ID Number(s):

LB-K100-0692-1, LB-K100-0692-2, 41-0003-6599-3, 41-0003-6644-7, 41-0003-6664-5, 41-0003-6730-4, 41-0003-6769-2, 60-4550-6996-7, 60-9801-0559-1, 60-9801-0561-7, 60-9801-0579-9

7000045749, 7010364116

Recommended use

Automotive, Automotive Body Filler

Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

29-5993-0, 32-1433-5

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 29-5993-0
Issue Date: 02/10/25

Version Number: 6.01
Supersedes Date: 02/24/22

SECTION 1: Identification

1.1. Product identifier

3M™ Cream Hardener (Red, White & Blue)

Product Identification Numbers

LB-K100-0965-7, LB-K100-0965-8, LB-K100-0965-9, LB-K100-0966-0, LB-K100-0966-1, LB-K100-0966-2, LB-K100-0966-3, LB-K100-1035-6, LB-K100-1045-4, LB-K100-1286-7, 41-0003-6674-4, 41-0003-6682-7, 41-0003-6685-0, 41-0003-6686-8, 41-0003-6687-6, 41-0003-7901-0, 41-0003-7903-6, 41-0003-7904-4, 41-0003-7922-6, 41-0003-7928-3, 41-0003-7930-9, 41-0003-7931-7, 41-0003-7932-5, 41-0003-7933-3, 41-0003-7935-8, 41-0003-7987-9, 41-0003-8059-6, 41-0003-8072-9, 41-0003-8073-7, 41-0003-8074-5, 41-0003-8146-1, 60-4550-6981-9, 60-4550-6982-7, 60-4550-8123-6, 60-4551-0388-1
7000120133, 7100191003

1.2. Recommended use and restrictions on use

Recommended use

Automotive, hardener for body fillers & glazes

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Automotive Aftermarket
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Organic Peroxide: Type E.

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Heating may cause a fire.

Causes serious eye irritation.

May cause an allergic skin reaction.

Causes damage to organs:

cardiovascular system |

nervous system |

kidney/urinary tract |

respiratory system |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep away from clothing and other combustible materials.

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight.

Store at temperatures not exceeding 32°C/90°F. Keep cool.

Store locked up.

Store separately.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

7% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Benzoyl Peroxide	94-36-0	30 - 60 Trade Secret *
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	10 - 30 Trade Secret *
Water	7732-18-5	10 - 30 Trade Secret *
Calcium Sulfate	7778-18-9	1 - 10 Trade Secret *
Zinc Stearate	557-05-1	1 - 10 Trade Secret *
Ethylene Glycol	107-21-1	<= 7.5 Trade Secret *
Iron Oxide (Fe ₂ O ₃)	1309-37-1	<= 5 Trade Secret *
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	<= 5 Trade Secret *
Ferric Ammonium Ferrocyanide	25869-00-5	<= 1 Trade Secret *
Ferric Ferrocyanide	14038-43-8	<= 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Eliminate all ignition sources if safe to do so. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Keep container tightly closed. Protect from sunlight. Protect from sunlight. Store away from heat. Store away from heat. Store at temperatures not exceeding 32°C/90°F. Keep cool. Store at temperatures not exceeding 32°C/90°F. Keep cool. Keep only in original container. Keep only in original container. Store separately. Store separately. Keep/store away from clothing and other combustible materials. Keep/store away from clothing and other combustible materials.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylene Glycol	107-21-1	ACGIH	TWA(Vapor fraction):25 ppm;STEL(Vapor fraction):50 ppm;STEL(Inhalable aerosol):10 mg/m3	A4: Not class. as human carcin
Iron Oxide (FE2O3)	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m3	A4: Not class. as human carcin
Iron Oxide (FE2O3)	1309-37-1	OSHA	TWA(as fume):10 mg/m3	
CYANIDES	14038-43-8	OSHA	TWA(as CN):5 mg/m3	SKIN
Zinc Stearate	557-05-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Calcium Sulfate	7778-18-9	ACGIH	TWA(inhalable fraction):10 mg/m3	
Calcium Sulfate	7778-18-9	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Benzoyl Peroxide	94-36-0	ACGIH	TWA:5 mg/m3	A4: Not class. as human carcin
Benzoyl Peroxide	94-36-0	OSHA	TWA:5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Provide ventilation adequate to maintain dust concentration below minimum explosive concentrations. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

Red

Specific Physical Form:

Paste

Odor

Slight Ester

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

111 °C [*Test Method*:Estimated]

Evaporation rate

No Data Available

Flammability (solid, gas)

Organic Peroxide: Type E.

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

Not Applicable

Vapor Density

Not Applicable

Density

1.2 g/cm³

Specific Gravity

1.2 [*@ 25 °C*] [*Ref Std*:WATER=1]

Solubility in Water

Negligible

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

50 °C [*Details*:SADT >=50C (122F)]

Viscosity

No Data Available

Hazardous Air Pollutants

0 - 0.1209 lb HAPS/lb solids [*Test Method*:Calculated]

Molecular weight

Not Applicable

Volatile Organic Compounds

0 - 90 g/l [*Test Method*:calculated SCAQMD rule 443.1]

Volatile Organic Compounds

0 % weight [*Test Method*:calculated per CARB title 2]

Percent volatile

21 - 28.5 %

VOC Less H₂O & Exempt Solvents

0 - 121 g/l [*Test Method*:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable. Stable unless exposed to heat, flames and drying conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Accelerators

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

May be harmful in contact with skin.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart

rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzoyl Peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Benzoyl Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
Benzoyl Peroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.5 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Sulfate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.61 mg/l
Calcium Sulfate	Ingestion	Rat	LD50 > 1,581 mg/kg
Calcium Sulfate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation-Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
Iron Oxide (FE2O3)	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxide (FE2O3)	Ingestion	Not available	LD50 3,700 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Dermal	Rabbit	LD50 > 16,960 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	LD50 4,240 mg/kg
Ferric Ferrocyanide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Ferric Ammonium Ferrocyanide	Dermal	Rat	LD50 > 2,000 mg/kg
Ferric Ammonium Ferrocyanide	Ingestion	Rat	LD50 > 2,000 mg/kg
Ferric Ferrocyanide	Ingestion	similar compounds	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Minimal irritation
Benzoic Acid, C9-11-Branched Alkyl Esters	Rabbit	Minimal irritation
Calcium Sulfate	Rabbit	No significant irritation
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Minimal irritation
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	Minimal irritation
Ferric Ammonium Ferrocyanide	Rabbit	No significant irritation
Ferric Ferrocyanide	similar compounds	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Severe irritant
Benzoic Acid, C9-11-Branched Alkyl Esters	Rabbit	Mild irritant
Calcium Sulfate	Rabbit	Mild irritant
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Mild irritant
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	No significant irritation
Ferric Ammonium Ferrocyanide	Rabbit	Mild irritant
Ferric Ferrocyanide	similar compounds	No significant irritation

Skin Sensitization

Name	Species	Value
Benzoyl Peroxide	Guinea pig	Sensitizing
Benzoic Acid, C9-11-Branched Alkyl Esters	Guinea pig	Not classified
Calcium Sulfate	Guinea pig	Not classified
Zinc Stearate	Human	Not classified
Ethylene Glycol	Human	Not classified
Iron Oxide (FE2O3)	Human	Not classified
Ferric Ammonium Ferrocyanide	Mouse	Not classified
Ferric Ferrocyanide	similar compounds	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Benzoyl Peroxide	In Vitro	Not mutagenic
Benzoyl Peroxide	In vivo	Not mutagenic
Benzoic Acid, C9-11-Branched Alkyl Esters	In Vitro	Not mutagenic
Benzoic Acid, C9-11-Branched Alkyl Esters	In vivo	Not mutagenic
Calcium Sulfate	In Vitro	Not mutagenic
Calcium Sulfate	In vivo	Not mutagenic
Zinc Stearate	In Vitro	Not mutagenic
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
Iron Oxide (FE2O3)	In Vitro	Not mutagenic

Ferric Ammonium Ferrocyanide	In Vitro	Not mutagenic
Ferric Ferrocyanide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Benzoyl Peroxide	Ingestion	Multiple animal species	Not carcinogenic
Benzoyl Peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
Iron Oxide (FE ₂ O ₃)	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Benzoyl Peroxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Benzoyl Peroxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	premating & during gestation
Benzoyl Peroxide	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating & during gestation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for female reproduction	Rat	NOAEL 641 mg/kg/day	2 generation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for male reproduction	Rat	NOAEL 676 mg/kg/day	2 generation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for development	Rat	NOAEL 191 mg/kg/day	2 generation
Calcium Sulfate	Ingestion	Not classified for female reproduction	Rat	NOAEL 790 mg/kg/day	premating into lactation
Calcium Sulfate	Ingestion	Not classified for male reproduction	Rat	NOAEL 790 mg/kg/day	35 days
Calcium Sulfate	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,600 mg/kg/day	during organogenesis
Ethylene Glycol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
Ethylene Glycol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesis
Ethylene Glycol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 1 mg/l	2 weeks

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethylene Glycol	Ingestion	heart nervous system kidney and/or bladder respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

Ethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	liver	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 619 mg/kg/day	91 days
Calcium Sulfate	Ingestion	liver kidney and/or bladder heart endocrine system gastrointestinal tract hematopoietic system immune system nervous system respiratory system	Not classified	Rat	NOAEL 790 mg/kg/day	35 days
Zinc Stearate	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart hematopoietic system liver immune system muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
Iron Oxide (Fe ₂ O ₃)	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 1 mg/l	2 weeks

Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.005 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.001 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	heart	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	heart endocrine system respiratory system	Not classified	Rat	NOAEL 3,770 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Organic peroxide

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**Ingredient****C.A.S. No****% by Wt**

Ethylene Glycol

107-21-1

Trade Secret <= 7.5

Zinc Stearate (ZINC COMPOUNDS)

557-05-1

Trade Secret 1 - 10

Benzoyl Peroxide

94-36-0

Trade Secret 30 - 60

Ferric Ferrocyanide (CYANIDES)

14038-43-8

Trade Secret <= 1

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**SECTION 16: Other information****NFPA Hazard Classification****Health: 2 Flammability: 1 Instability: 0 Special Hazards: Oxidizer**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health: 4 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 29-5993-0**Version Number:**

6.01

Issue Date: 02/10/25**Supersedes Date:**

02/24/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-1433-5	Version Number:	6.01
Issue Date:	08/10/23	Supersedes Date:	06/27/23

SECTION 1: Identification

1.1. Product identifier

3M™ Lightweight Body Filler PN 05800, 05801, 05804, 05805

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Body Repair

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 2B.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Health Hazard |

Pictograms

**Hazard Statements**

Flammable liquid and vapor.

Causes eye irritation.

May cause cancer.

Causes damage to organs:

liver |
sensory organs |

Causes damage to organs through prolonged or repeated exposure:

respiratory system |
sensory organs |

May cause damage to organs through prolonged or repeated exposure:

liver |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyester Resin	26123-45-5	20 - 30 Trade Secret *
Talc	14807-96-6	15 - 30 Trade Secret *
Styrene Monomer	100-42-5	< 20 Trade Secret *
Magnesium Carbonate	546-93-0	5 - 15 Trade Secret *
UNDISCLOSED MATERIAL	None	5 - 10 Trade Secret *
Inert Filler	Trade Secret*	5 - 10 Trade Secret *
Limestone	1317-65-3	1 - 5 Trade Secret *
Silica Gel	112926-00-8	1 - 5 Trade Secret *
Chlorite	1318-59-8	< 2 Trade Secret *
Dolomite	16389-88-1	< 2 Trade Secret *
Titanium Dioxide	13463-67-7	< 1 Trade Secret *
Quartz Silica	14808-60-7	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Hydrocarbons
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Styrene Monomer	100-42-5	ACGIH	TWA:10 ppm;STEL:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Styrene Monomer	100-42-5	OSHA	TWA:100 ppm;CEIL:200 ppm	
SILICA, AMORPHOUS	112926-00-8	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Limestone	1317-65-3	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1317-65-3	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1317-65-3	ACGIH	TWA(respirable particles):3 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA - Use asbestos limits:	
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz Silica	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
DUST, INERT OR NUISANCE	16389-88-1	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	16389-88-1	ACGIH	TWA(inhalable particulates):10 mg/m3	

Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	16389-88-1	ACGIH	TWA(respirable particles):3 mg/m3	
Magnesium Carbonate	546-93-0	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	546-93-0	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	546-93-0	ACGIH	TWA(respirable particles):3 mg/m3	
Inert Filler	Trade Secret	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):1 fiber/cc	A4: Not class. as human carcin
Inert Filler	Trade Secret	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polyvinyl Alcohol (PVA)
Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Gray

Specific Physical Form:

Paste

Odor

Pungent Styrene

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

293 °F

Flash Point

88 °F [*Test Method:*Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

0.9 % [*Details:*based on styrene]

Flammable Limits(UEL)

6.8 % [*Details:*based on styrene]

Vapor Pressure

No Data Available

Vapor Density

3.6 [*Ref Std:*AIR=1]

Density

1.14 g/ml

Specific Gravity

1.14 [*Ref Std:*WATER=1]

Solubility in Water

Negligible

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

200,000 - 244,000 centipoise

Hazardous Air Pollutants

0.355 lb HAPS/lb solids

Volatile Organic Compounds

17.6 % weight [*Test Method:*calculated per CARB title 2]

Volatile Organic Compounds

200 g/l [*Test Method:*calculated SCAQMD rule 443.1]

Percent volatile

17.9 % weight

VOC Less H2O & Exempt Solvents

201 g/l [*Test Method:*calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable. Stable under normal conditions. May become unstable at elevated temperatures and/or pressure.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

Heat

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

Alkali and alkaline earth metals

Strong bases

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Silica, Crystalline (Respirable Size)	14808-60-7	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Inert Filler	Trade Secret	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Inert Filler	Trade Secret	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Inert Filler	Trade Secret	Anticipated human carcinogen	National Toxicology Program Carcinogens
Inert Filler	Trade Secret	Anticipated human carcinogen	National Toxicology Program Carcinogens
Talc containing asbestiform fibres	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Styrene	100-42-5	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Styrene	100-42-5	Anticipated human carcinogen	National Toxicology Program Carcinogens
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyester Resin	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyester Resin	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Styrene Monomer	Dermal	Rat	LD50 > 2,000 mg/kg
Styrene Monomer	Inhalation-Vapor (4 hours)	Rat	LC50 11.8 mg/l
Styrene Monomer	Ingestion	Rat	LD50 5,000 mg/kg
Magnesium Carbonate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Carbonate	Ingestion	Rat	LD50 > 2,000 mg/kg
Inert Filler	Dermal		LD50 estimated to be > 5,000 mg/kg
Inert Filler	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-	Rat	LC50 3 mg/l

	Dust/Mist (4 hours)		
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Silica Gel	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica Gel	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica Gel	Ingestion	Rat	LD50 > 5,110 mg/kg
Chlorite	Dermal		LD50 estimated to be > 5,000 mg/kg
Chlorite	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dolomite	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Dolomite	Ingestion	Rat	LD50 > 2,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Styrene Monomer	Professional judgement	Mild irritant
Magnesium Carbonate	In vitro data	No significant irritation
Inert Filler	Professional judgement	No significant irritation
Limestone	Rabbit	No significant irritation
Silica Gel	Rabbit	No significant irritation
Chlorite	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Quartz Silica	Professional judgement	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Styrene Monomer	Professional judgement	Moderate irritant
Magnesium Carbonate	Rabbit	Mild irritant
Inert Filler	Professional judgement	No significant irritation

Limestone	Rabbit	No significant irritation
Silica Gel	Rabbit	No significant irritation
Chlorite	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Styrene Monomer	Guinea pig	Not classified
Silica Gel	Human and animal	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Styrene Monomer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Styrene Monomer	In vivo	Some positive data exist, but the data are not sufficient for classification
Inert Filler	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica Gel	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Styrene Monomer	Ingestion	Mouse	Carcinogenic
Styrene Monomer	Inhalation	Human and animal	Carcinogenic
Inert Filler	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica Gel	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Quartz Silica	Inhalation	Human and animal	Carcinogenic
---------------	------------	------------------	--------------

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Styrene Monomer	Ingestion	Not classified for female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
Styrene Monomer	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	60 days
Styrene Monomer	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during gestation
Styrene Monomer	Inhalation	Not classified for development	Multiple animal species	NOAEL 2.1 mg/l	during gestation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Silica Gel	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica Gel	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica Gel	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Styrene Monomer	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
Styrene Monomer	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
Styrene Monomer	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Styrene Monomer	Inhalation	endocrine system	Not classified	Rat	NOAEL Not available	not available
Styrene Monomer	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2.1 mg/l	not available
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Styrene Monomer	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
Styrene Monomer	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
Styrene Monomer	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
Styrene Monomer	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.85 mg/l	7 days
Styrene Monomer	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.6 mg/l	10 days
Styrene Monomer	Inhalation	respiratory system	Not classified	Multiple animal species	LOAEL 0.09 mg/l	not available
Styrene Monomer	Inhalation	heart gastrointestinal tract bone, teeth, nails, and/or hair muscles kidney and/or bladder	Not classified	Multiple animal species	NOAEL 4.3 mg/l	2 years
Styrene Monomer	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
Styrene Monomer	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
Styrene Monomer	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 677 mg/kg/day	6 months
Styrene Monomer	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 600 mg/kg/day	470 days
Styrene Monomer	Ingestion	heart respiratory system	Not classified	Rat	NOAEL 35 mg/kg/day	105 weeks
Inert Filler	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Silica Gel	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Styrene Monomer	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Carcinogenicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Styrene Monomer	100-42-5	Trade Secret < 20

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	32-1433-5	Version Number:	6.01
Issue Date:	08/10/23	Supersedes Date:	06/27/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.