Keysight 53200 RF/Universal Frequency Counter/Timers Models: 53210A, 53220A and 53230A



From top: 53210A RF Counter 53220A Universal Frequency Counter/Timer 53230A Universal Frequency Counter/Timer The Keysight 53200 Series is a new generation of 350 MHz RF/universal frequency counter/timers with optional 6 GHz or 15GHz inputs. The first frequency counters with LXI Class C compliance, the 53200 family is built with LAN and USB I/O for ease of connectivity and data collection. The combination of high-speed measurements and built-in analysis and graphical display provides new functionality that has not previously been available in basic frequency counter/timers.

Key features

- More frequency:
 350 MHz baseband frequency, 6 or 15GHz optional microwave channels
- More resolution:
 Up to 12 digits/sec and 20-ps single-shot time interval
- More information accessibility:
 1 M reading memory, up to 75,000 frequency readings/sec, strip chart/trend plot, cumulative histograms
- More connectivity:
 First LXI-compliant counters (LXI/Ethernet, USB, GPIB connectivity)
- More measurement capability:
 Gap-free/continuous measurements and timestamping for basic modulation domain analysis and pulse/burst microwave measurements. The optional battery supports remote usage and helps maintain accurate measurements by keeping the timebase warm at all times.
- Frequency counter emulation mode: 53131A, 53132A, 53181A

Learn more at: www.keysight.com



Product specifications

	53210A RF frequency counter	53220A universal frequency counter/timer	53230A universal frequency counter/timer
Channels	Channel 1: 350 MHz Opt channel 2: 6 or 15 GHz	Channel 1 and 2: 350 MHz Opt channel 3: 6 or 15 GHz	
Frequency resolution	10 digits/sec	12 d	igits/sec
Time interval resolution	NA	100 psec	20 psec
Measurements	Frequency, period, frequency ratio, max/min/peak to peak input voltage	Frequency, period, frequency ratio, max/min/peak to peak input voltage, time interval, single period, pulse width, rise/fall time, duty cycle, phase, totalize	Frequency, period, frequency ratio, max/min/peak to peak input voltage, time interval, single period, pulse width, rise/fall time, duty cycle, phase, totalize, timestamp/MDA
Burst/pulse microwave measurements	NA		Carrier frequency, PRI, PRF, PW
Math	Smoothing (Reading moving average), scaling, ∆-change, null		
Statistics	Mean, standard deviation, max, peak-to-peak, count	Mean, standard deviation, max,	peak-to-peak, count, Allan deviation
Graphical display	Digits, trend, histogram, limit test, markers		

Accessories

Part	Description
1250-1476	Adapter: Type-N (m) to BND (f), DC to 4 GHz
N2874A	Passive probe: 10:1, 1.5 GHz, 1.3 m
34190A	Rack mount kit
34191A	2U dual flange kit
34194A	Dual lock link kit

Options

Part	Description	
Option 010	Ultra high-stability OCXO timebase	
106/115	Add 6/15 GHz CW microwave channel	
203	Move microwave channel input to rear	
201	Add rear panel parallel inputs for channel 1 and	
	channel 2	
300	Internal lithium ion battery charger for unstable AC	
	power or timebase stability	

Please consult with your distributor for final pricing.

For more details on the Keysight 53200 Series and ordering information see: Keysight 53200 Series Datasheet, literature number 5990-6283EN Keysight 53200 Family Brochure, literature number 5990-6339EN

For more information on the Keysight 53200 Series, please visit: www.keysight.com/find/FrequencyCounterSpotlight

To find a distributor in your area, go to: www.keysight.com/find/distributors

Learn more at: www.keysight.com

