

## SHOWA



Created with 13-gauge HPPE and polyurethane reinforcement, SHOWA 540's lightweight construction fits and feels like a second skin, empowering you with the ultimate grip and comfort, matched by dextrous durability.

## **FEATURES**

- 13-gauge seamless, cut-resistant, HPPE liner
- Durable palm-coated white colored polyurethane coated
- Elastic knit-wrist
- Launderable

## **BENEFITS**

- ANSI Cut Level A2
- HPPE lining provides extremely comfortable fit
- Lightweight but durable coating provides outstanding grip
- Knit-wrist secures glove above the wrist for comfort and prevents debris from entering the glove

## **INDUSTRY**



Automotive



Construction



Manufacturing



Mechanical



**Municipal Services** 

## **IDEAL APPLICATIONS**

- Light assembly of oil-coated pieces
- Sanding
- Canning
- Component Assembly
- HVAC
- Public utility



#### **MATERIAL**

- HPPE
- Seamless knit

#### **COATING**

Polyurethane

#### GRIP

Rough

#### **STANDARDS**



0598

1









## SHOWA

# 540



### PACKAGING

- 12 Pair per polybag6 Polybags per case
- 72 Pair per case



### **SIZES**

- S
- M
- L
- XL



#### COLOUR

• White w/ white coating



# YOU MIGHT ALSO BE INTERESTED IN





MATERIAL Kevlar COATING Foam nitrile





MATERIAL HPPE COATING Polyurethane SHOWA **545** 



MATERIAL
HPPE
COATING
Nitrile

# **USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## **DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

