

**Directions:**

Store in a cool, dry, and ventilated environment away from direct sunlight or sources of heat. Wash with mild detergent and warm water. Air dry to extend the life of the gloves, or tumble dry on low heat up to 77°F (25°C) to minimize shrinking and fiber degradation. Electrical values will diminish with each washing; gloves may be laundered up to three times, although results may vary.

Note:

Staticide® Knit ESD Gloves are not for use with chemicals. Avoid contact with corrosive or toxic chemicals. Use extreme caution when working around moving equipment and machinery. Failure to observe these cautions could result in personal injury, illness, or even death.

Staticide® Knit ESD Gloves, Uncoated Fingertips:

(6 pairs per pack; 6 packs per case)

GLK-S: Small

GLK-M: Medium

GLK-L: Large

GLK-XL: Extra Large

GLK-2XL: Double Extra Large

Staticide® Knit ESD Gloves, Coated Fingertips:

(6 pairs per pack; 6 packs per case)

GLKT-S: Small

GLKT-M: Medium

GLKT-L: Large

GLKT-XL: Extra Large

GLKT-2XL: Double Extra Large



Staticide® Knit ESD Gloves

ESD Assembly & Inspection Glove

ACL Staticide® Knit ESD Gloves protect against static discharge without sacrificing ergonomic performance. Static control and comfort makes these gloves ideal for detailed assembly and inspection work.

The blended nylon-conductive carbon yarn reduces tribocharging and integrates volume resistivity throughout the fabric for maximum static control. Lightweight and seamless in construction, Staticide® Knit ESD Gloves with spandex cuffs provide a comfortable, breathable fit with low moisture absorption. The micro-knit fingertips offer superb dexterity, and for additional durability and grip, these gloves are available with micro-foam polyurethane-coated fingertips.

Ideal for the following applications:

- ✿ EPAs and other ESD-sensitive areas
- ✿ Electronics manufacturing
- ✿ Assembly and packaging
- ✿ Inspection

FEATURES:

- ✿ Seamless knit construction
- ✿ Nylon conductive carbon fiber blend yarn
- ✿ Available with micro-knit fingertips for dexterity or dipped for durability
- ✿ Low moisture absorption
- ✿ Wrist bands color coded for sizing
- ✿ GLK gauge 13, GLKT gauge 15
- ✿ CAFE RGP per ANSI/ESD SP15.1 @ 12% RH for 48 hours (average):
GLK: 107 ohms, GLKT: 108 ohms
- ✿ 107 ohms CAFE RGP per ANSI/ESD SP15.1 @ 50% RH for 48 hours (average)
- ✿ Surface Resistance: 108 ohms as per ANSI/ESD STM11.11 @ 50% RH & 10% RH for 48 hours (average)