



#### Directions:

Staticide® topicals can be applied by spraying, wiping, dipping, transfer roller coating, gravure coating, or flexographic printing. For high production applications, mechanically apply solution by using fine-mist sprayers or foam rollers. The product can also be manually sprayed using a trigger sprayer at 8-12" from desired surface. For carpet, apply so that fibers absorb anti-stat. It should feel damp but not saturated.

Allow solution to dry.

SDS available at [www.aclstaticide.com](http://www.aclstaticide.com).



#### Product# 520:

4-oz bottle; 12 per case (finger-pump sprayer)

#### Product# 2005:

1-quart bottle; 12 per case (trigger sprayer)

#### Product# 2002:

1-gallon bottle; 4 per case

#### Product# 2002-5:

5-gallon pail

#### Product# 2002-2:

50-gallon drum



# Heavy Duty Staticide®

## Static control for porous surfaces

Heavy Duty Staticide® anti-static topical is easy to use and highly effective in controlling electrostatic charges in industrial manufacturing and static-sensitive environments.

As a key component in any static control program, it is non-toxic, non-flammable, and non-staining. This ready-to-use solution formulated specifically for porous surfaces is ideal for eliminating static on carpets, upholstery, and fabrics. With a similar viscosity to water, Heavy Duty Staticide can be applied in various ways such as spraying, wiping, or transfer roller coating.

#### Ideal for the following applications:

- Dust attraction; keep equipment cleaner longer
- Damage potential to sensitive electronic components and subassemblies during manufacture, testing, packaging, shipping, and receiving
- Data errors, paper jams, and other office machine glitches
- Jamming or slipping of paper, plastics, and other materials during printing, packaging, and converting
- Ignition of combustible vapors, dust, and solvents, causing fire or explosion
- Irregularities caused by static in quality printing, heat sealing, silk-screening, lamination, and other special applications
- Static discharge on workbenches and production surfaces

#### FEATURES

- ❖ Formulated for porous surfaces
- ❖ Exceeds MIL-B-81705 and NFPA-56A electrostatic decay criteria
- ❖ Meets requirements for topical anti-stats as listed in the Military Handbook DOD-HDBK-263
- ❖ Proven effective in relative humidity below 15%
- ❖ Decays static in less than 2 seconds
- ❖ Surface resistance between  $10^9$  -  $10^{10}$  ohms
- ❖ One gallon covers approximately 2000 sq.ft. per gallon
- ❖ Lasts from weeks to months depending on application