

CARE INSTRUCTIONS

With routine care and maintenance, your BEVCO chairs and backless stools should provide years of comfortable and trouble-free seating. Occasional light cleaning along with proper use and maintenance is all that is necessary. Follow the general guidelines below for best results and preservation of the warranty:

STANDARD FABRIC ESD FABRIC CARRINGTON, DORAL, EVANSTON, INTEGRA, CARRINGTON, DORAL, EVANSTON, INTEGRA, LEXINGTON, VERSA, WESTMOUND LEXINGTON (V8), VERSA > Regularly clean chair fabric by vacuuming or light brushing. > Regularly clean chair fabric by vacuuming or light brushing. > Test cleaning product in an inconspicuous area first to guard > Spot treat with mild soap and water or ESD-safe cleaner. against color bleeding or fabric shrinkage is recommended. > All commercial cleaning agents and solvents may be used: · Water-based stains should be treated with water-based cleaning agents. · Oil-based stains should be treated with a solvent cleaner. STANDARD VINYL **ESD VINYL** CARRINGTON, DORAL, EVANSTON, INTEGRA, CARRINGTON, DORAL, EVANSTON, INTEGRA, VERSA, WESTMOUND VERSA, WESTMOUND > Use a soft, non-abrasive cleaning cloth or sponge. > Use a soft, non-abrasive cleaning cloth or sponge. > Always rub gently and rinse with a water damped > Use any ESD-safe cleaner for non-porous surfaces. cloth/sponge. > Always rub gently and rinse with a water damped > For light soiling, use a solution of 10% household cloth/sponge. liquid dish soap in warm water. > For heavy soiling, use a 1:1 solution of Formula 409® or Fantastik® and water. > For more difficult stains, use a solution of household bleach (10% bleach and 90% water). POLYURETHANE > Avoid harsh cleaning products and solvent chemicals. > Spot clean with mild soap and water. (Standard, ESD, CR and ESD/CR) On ESD or ESD/CR Polyurethane, be sure to use an BREVA, DURA, EVERLAST, ERGOLUX, ERGOLUX JR., ESD-Safe Cleaner. SIT-STANDS, SPRINGDALE, VERSA-P

PROPER USE & MAINTENANCE

Use this product only for its intended purpose as an office or industrial seating product.



Do not stand on footring, it is meant as a footrest and is not designed to support full body weight.

- Do not overtighten handwheels located on chair back, underneath the seat, or the footring adjustment.
- Check that all bolts, screws, and knobs are tightly secured every three months or as needed.
 - Immediately remove the chair from service if any damage or failure is found and contact our customer service department at 800-864-2991 x107 Monday-Friday 7:30 am-4:00 pm CST.