



Cortek SE-2420 Specifications

- External Dimensions: 24" (W) x 20" (D) x 12.5" (H)
- Internal Dimensions: 22" (W) x 18" (D) x 11" (H)
- Weight: 36 lbs
- Tester Compatibility: Compatible with most HiPot testers for easy enclosure connection

SE 2420 Hipot Safety Enclosure

Dimensions: 24" W x 20" D x 12.5" H

The SE 2420 ensures electrical safety by reducing shock risks. Ideal for testing small electronic units like medical devices, it adapts easily to various UUT sizes.

Features:

- Aluminum Frame & Acrylic Cover.
- Magnetic Interlock Safety Switch.
- Chassis Ground Wire Connection (customer-installed).
- Yellow Safety Panels & High-Voltage Warning Stickers.
- 20-Position Terminal Block & 9-Pin D-Sub Connector.
- 2" Flexible Grommet for Cable Pass-Through.
- Wide Opening for Easy UUT Handling.
- Custom Sizes Available.

Options:

- Safety Light Tower (Red/Green or Red/Yellow/Green).
- Start/Stop Buttons & Emergency Stop (E-Stop).
- Extra Grommets (1–4).
- Insulation Mat & Instrument Shelf (1 or 2).

Specifications:

Weight: 36 lbs | Height: 12.5 in | Depth: 20 in | Width: 24 in