

Components:

- A. 0.080" thick, 1.50" wide, dual layer rubber, black conductive exterior with a non-marring interior. Tear resistant nylon reinforced 4.3 oz. inner scrim layer prevents the rubber from tearing.
- B. 3/8" wide, 30" long blue polyester tab contains electrically conductive carbon suffused fibers.
- C. 3/4" wide blue elastic material stretches for comfort.
- D. Adjustable snap-loc fastening system.
- E. A 1/4 watt, 2 megohm resistor.
- F Stretch elastic back.

listed and date coded.

Electrical Properties

Property Flooring contact surface (sole) to body contacting surface (tab) resistance. Test MethodValueANSI/ESD STM97.1, ESD SP9.2,< 1 x 10⁹ ohmsESD TR53

Item	<u>17239</u>	<u>17240</u>	<u>17241</u>	<u>17242</u>	<u>17243</u>
Size	XSmall	Small	Medium	Large	XLarge
Shoe Size Women	5 - 7	6 - 8	7 - 9	8 - 11	11+
Shoe Size Men	N/A	6 - 9	8 - 11	10 - 13	12+

Recommended sizing. Request samples HERE.



Made in the United States of America

Specifications and procedures subject to change without notice.	SOLE GROUNDER WITH SNAP-LOC			
DESCO	DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172	DRAWING NUMBER 17239	DATE: January 2016	

© 2016 DESCO INDUSTRIES INC. Employee Owned