

Requirements for Statshield ESD Bag Storage

For best results, bag inventory should be continually replenished. It is recommended that bags be stored in its original packaging. The user must determine the suitability for use of an ESD bag for his particular application. Bags should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Bags should not be stored in ultraviolet sunlight, moisture, or heat because the aluminum shielding layer could oxidize if exposed to these conditions. Bags should be evaluated by the user to determine acceptability for the user's application. Mishandling or improper storage may render an ESD Bag unusable to perform its function. ESD Bags that are ripped, torn, or scratched should be discarded. Desco Industries, Inc. recommends those tracking useful life of product to use shipping/invoice date as Desco Industries, Inc. expressly warrants that for a period of one (1) year from the date of purchase, Desco Statshield ESD bags will be free of defects in material (parts) and workmanship (labor).

See Desco Industries Inc. limited warranty at Descoindustries.com/Warranty.aspx which states in part: Desco Industries Inc. only obligation shall be to replace such quantity of the product proved to be defective. Desco Industries Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith.

