


Hollow Heater Soldering Tools and Stations


Part No.	Description
930	Soldering Station with CL1080 Soldering Tool and IP329 Base
935	Soldering Station with CL1080 Soldering Tool and PS536 Power Supply
951DX-230	Deluxe Soldering Station (includes all 230V models)
951SX	Soldering Station (includes all 230V models)
952DX-230	Dual Deluxe Soldering Station (includes all 230V models)
952SX	Dual Soldering Station (includes all 230V models)
CL1080	Temperature Controlled Soldering Tool
CL1180	Temperature Controlled Soldering Tool
CL1280I	Temperature Controlled Soldering Tool (230V)
CL1580I	Temperature Controlled Soldering Tool (230V)



Hollow Threaded Heater Soldering Tools and Stations

Part No. Description

CL1481 Constant Temperature Soldering Tool



Hollow Heater Soldering Tools and Stations

Part No. Description

PSS2000 Hybrid Portable Soldering System



Hollow Heater LTC7 Collet Soldering Tip RCS7 Retaining Sleeve
NOTE: Loosen collar when changing tips.
DO NOT remove sleeve.

Front Loading Hollow Heater Soldering Tools and Stations

Part No.	Description
971	Deluxe High Performance Soldering Station (includes all 230V models)
971DX-230	Deluxe High Performance Soldering Station (includes all 230V models)
2020	Microprocessor Controlled Digital Soldering Station (includes all 230V models)









Front Loading Hollow Heater

LTC71 Collet

RCS71 Retaining Sleeve
NOTE: Loosen collar when changing tips.
DO NOT remove sleeve.

Soldering Tip

www.edsyn.com





General Purpose Spade Tips		← B →	
Part No.	Tip Image	Width A	 Length B
LT375		.06" (1.5mm)	.48" (12.2mm)
LT376		.12" (3.0mm)	.48" (12.2mm)
LT394		.07" (1.8mm)	.93" (23.6mm)
LT395		.069" (2.3mm)	.74" (18.8mm)
LT431		.07" (1.8mm)	.74" (18.8mm)
LT444		.04" (1.0mm)	.78" (19.8mm)
General Purpo	ose Conical Tips		$\begin{array}{c} \\ \\ \\ \\ \\ \\ \end{array}$
LT374		.03" (0.8mm)	.48" (12.2mm)
LT382		.02" (1.5mm)	.62" (15.8mm)
LT429		.02" (0.5mm)	.74" (18.8mm)
General Purpo	se Angled Conical Tip		B →
LT429-1		.02" (0.5mm)	.74" (18.8mm)





LONER_® High Temperature Tips

High Temperature	Rated Spade Tips		B →
Part No.	Tip Image	Width A	Length B
LT371LF		.03" (0.8mm)	.55" (14.0mm)
LT375LF		.06" (1.5mm)	.48" (12.2mm)
LT376LF		.12" (3.0mm)	.48" (12.2mm)
LT394LF		.07" (1.8mm)	.93" (23.6mm)
LT395LF		.09" (2.3mm)	.74" (18.8mm)
LT424LF		.06" (1.5mm)	.74" (18.8mm)
LT425LF		.05" (1.3mm)	.93" (23.6mm)
LT431LF		.07" (1.8mm)	.74" (18.8mm)
LT444LF		.04" (1.0mm)	.78" (9.8mm)
High Temperature	Rated Conical Tips		B →
			— A□
LT374LF		.03" (0.8mm)	.48" (12.2mm)
LT374LF LT380LF		.03" (0.8mm) .02" (0.5mm)	.48" (12.2mm) .32" (8.1mm)
LT380LF		.02" (0.5mm)	.32" (8.1mm)
LT380LF LT382LF		.02" (0.5mm) .02" (0.5mm)	.32" (8.1mm) .62" (15.8mm)
LT380LF LT382LF LT383LF		.02" (0.5mm) .02" (0.5mm) .02" (0.5mm)	.32" (8.1mm) .62" (15.8mm) .72" (18.3mm)
LT380LF LT382LF LT383LF LT392LF		.02" (0.5mm) .02" (0.5mm) .02" (0.5mm) .01" (0.3mm)	.32" (8.1mm) .62" (15.8mm) .72" (18.3mm) 1.13" (28.8mm)
LT380LF LT382LF LT383LF LT392LF LT429LF		.02" (0.5mm) .02" (0.5mm) .02" (0.5mm) .01" (0.3mm) .02" (0.5mm)	.32" (8.1mm) .62" (15.8mm) .72" (18.3mm) 1.13" (28.8mm) .74" (18.9mm)

www.edsyn.com





High Temperat	ture Rated Angle Face Tips		B → A
Part No.	Tip Image	Width A	Length B
LT298LF		.12" (3.1mm)	.59" (15.0mm)
LT299LF		.16" (4.0mm)	.59" (15.0mm)
LT373LF		.09" (2.3mm)	.59" (15.0mm)
LT387LF		.06" (1.5mm)	.48" (12.2mm)
LT393LF		.06" (1.5mm)	.94" (23.9mm)
LT398LF		.12" (3.0mm)	.59" (15.0mm)
LT399LF		.16" (4.0mm)	.59" (15.0mm)
LT430LF		.06" (1.5mm)	.74" (18.8mm)
LT433LF		.04" (1.2mm)	.69" (17.5mm)
LT443LF		.09" (5.6mm)	.69" (17.5mm)
High Temperat	ture Rated Angled Spade Tips		B → 3
LT444-1LF		.064" (1.0mm)	.78" (9.8mm)
LT392-1LF	ture Rated Angled Conical Tips	.01" (0.3mm)	1.13" (28.8mm)
LT439-1LF		.03" (0.8mm)	.50" (12.7mm)
LT602-1LF		.02" (0.5mm)	.44" (11.2mm)
High Temperat	ture Rated Mini Flow Rework Tips		B → ↓ A →
LT396LF		.13" (3.3mm)	.69" (17.5mm)

